

Douglas County Surveyor's Record of
Government Corners Renewed

J. W. Cole Co. Surveyor
Witnesses
H. Bergh
E. Richardson
W. H. Coats
Walter Coats
February 13, 1923.

OLD REV. Vol 1
PG 113

J. W. Cole Co. Surveyor
Witnesses
W. H. Coats, E. Richardson, H. Bergh
February 1923.

(SEE FB. 33 P. 27)

WITNESS CORNER TO CORNER OF SECTIONS 25 and 26 ON TOWNSHIP 36 ~~Corrected 10-25-30~~ 39
LINE. (HATHORNES CORNER).

Section corner is in creek account of channel having changed. Set an Iron Pipe 1" x 30" for Witness Corner 25 feet West of true corner from which
An Ash 30" dia. bears N.28°W., 28.5 ft. See G.L.O. FIELD NOTES Vol. 14, Pg. 5921 for BRASS CAP
A Maple 14" dia. bears N.21°30'E., 11.4 ft.

The fallen and decaying remains, position uncertain, of old B.T. Ash bears N.66°E., 50.0 ft. This tree bore scribe marks and was chopped open years ago and W. H. Coats testifies that it is remains of B.T. S.35°E., 24 lks. from corner.

N.E. CORNER OF COATS D.L.C. # 59. Renewed from the original B.T. which is alive and standing but scribe marks were rotted out. I remarked the tree and set an Iron Pipe 1" x 30 pipe as per field notes. 120 40

N.W. CORNER OF COATS D.L.C. # 59. Set on E. line of Lathrope Claim and on a distance of 9.00 chains North of S.E. Corner of Lathrope Claim. Set a rock for corner marked Cl. 59 C.S. - SEE COR. No. 136, T28-8 41

1/4 CORNER BETWEEN SECTIONS 30 and 31. Could not find trees given in Government field notes but found stake in fence corner from which trees bearing scars indicating bearing trees as follows
A Black Oak 30" dia. N.9°00'W., 83.0 ft.
A Black Oak 30" dia. S.62°E., 19.0 ft. OBSOLETE
A Black Oak 46" dia. N.42°30'E., 69.4 ft.
A Black Oak 24" dia. S.22°00'W., 32.5 ft.] F.B. 33 P. 25 42

HATHORNE'S CORNER TO TWPS. 28 and 29 S. Rg's. 7 and 8W. Set a Cedar Post from which
A White Oak 16" dia. bearing old scribe marks bears N.0°30'E., 168.9 ft. An Original B.T.
A Black Oak which has chopped open chips show scribe marks N.5°00'W., 222.6 ft. SEE COR. No. 155 & 36 FOR COR. 31/6
A Black Oak original B.T. showing scars and alive and standing bears S.27°00'W., 463.6 ft.
An Oak stump bears S.76 1/2°E., I did not measure this distance.
I marked
An 8" White Oak N.87°30'E., 11.0 ft. marked C.S.B.T. OBSOLETE 43

HATHORNES 1/4 CORNER W. SIDE OF SECTION 31. Set from original B.T.s Laurel was heavily rotted away so I marked a New tree. #264 (35 FOR COR. 31/6)
An 18" Fir S.80 1/2°E., 27.6 ft. SEE CORNER NO. OBSOLETE
Set Iron Pipe 1" x 24" for corner also Maple Post 3"x 3"x 36". 44

CORNER TO SECTIONS 31, 32, 5 and 6. Set a flat rock, erected around a rock, marked with X with a Rock on top bearing old mark, S. T. Flat Rock 6" x 12" x 18" from which original B.T.s
Laurel with scribe marks rotted off N.30°E., 16.5 ft.
Laurel bearing old scribe marks N.15°W., 66.0 ft.
Fir B.T. bearing scars which I did not open bears S.75°E., 12.0 ft.
Original Oak B.T. down and decaying bears S.43°W., 28.4 ft.
Corner as set by Gordon Stewart bears N.85°30'W., 36.7 ft. #549 61 45

1/4 S. BOUNDARY OF SECTION 31. Could find no evidence of the original B.T.s. I determined the original position of this corner from tie given in field notes of the McCulloch D.L.C. also by testimony of W. H. Coats who calimed that he had been told by Tom McCulloch that he had dug out witness trees while preparing the ground for a garden. Also the tie given by the field notes of the Twp line to the creek checked within a few feet. The old fence line built on the Survey for the W. Side of Thomas Coats Cl. if continued would run to this corner. (?) SEE COR. # 10 46
OBSOLETE