

Douglas County Surveyor's Record of  
Government Corners Renewed

28 T. S. 7 R. W. W. M.

All this evidence corresponding closely, I renewed the corner by evidence on the ground instead of proportionate measure. The  $\frac{1}{4}$  Corner set by Gordon Stewart bears North 195.8 ft. and West 267.0 ft.

SECTION CORNER COMMON TO SECTIONS 30 and 31 on THE TOWNSHIP LINE BETWEEN T. 28 S. R. 7 and 8 W. **OBSOLETE 47**

I renewed this corner from stump of 30" Oak which I believed to be the remains of the original B.T. called for in field notes as N.85°00'E., 671.2 ft. Fords Measurement South of creek would check closely also line East to Quarter Corner passes between to large Oaks bearing very old blazes. I set a 2" x 60" Iron Pipe for corner and marked new trees as follows

- White Oak 14" dia. bears N.53°30'W., 188.0 ft.
- White Oak 30" dia. bears N.84°00'E., 673.0 ft.
- White Oak 20" dia. bears S.69°40'E., 569.0 ft.

These trees were marked to face a point 78 ft. North of corner but I afterward decided to move same to correspond to evidence found.

HATHORN'S  $\frac{1}{4}$  CORNER ON EAST SIDE OF SECTION 25. **TRSR 48**

I renewed this corner from stumps of original B.T.s which I identified by their size and position. Set a steel plow post  $\frac{1}{2}$ " x 3" x 24" for corner from which

- Stump bears N.35°W., 108.6 ft.
- Stump of 30" Oak bears N.30°E., 136.6 ft.

Marked new trees

- White Oak 18" dia. bears N.81°30'W., 72.2 ft.
- White Oak 18" dia. bears N.32°30'E., 56.6 ft.
- Trees marked  $\frac{1}{4}$  S. C. S. B.T.

$\frac{1}{4}$  CORNER W. SIDE OF SECTION 30 (FORD'S CORNER). **49**

I renewed this corner from original B.T.s which are alive and showed scribe marks plainly when chopped. I could not harmonize the calls for directions and distances to these trees with the facing of the blazes so I set the corner where both trees faced and this position also checked with the tie to this corner made by Hathorne during his retracement of the township line. I set an Iron bar  $1\frac{1}{2}$ " x 30" and a Cedar Post 4 x 4 x 36 from which original B.T.s bear as follows

- A Black Oak 14" dia. bears N.25°E., 91.7 ft.
- A Black Oak 18" dia. bears N.1°00'W., 85.1 ft.

Marked new trees

- A Fir 24" dia. bears N.69°W., 5.4 ft.
- A Fir 16" dia. bears N.27°E., 17.0 ft.

CORNER TO SECTIONS 24 and 25, on the Township Line between Ranges 7 and 8. **50**

I renew this corner from Original B.T.s

- A large Black Oak bearing scribe marks N.58°E., 30 lks.
- A White Oak 20" dia. bearing scars S.72°E., 76 lks.
- A Hole where a tree stood bears N.18°W., 38 lks.
- A Stump of a large Black Oak S.72°W., 30 lks.

I set a Fir Post 5" x 5" x 50" also two conglomerate rocks 8" x 10" x 12" from which

- Fir 8" dia. bears N.46°15'E., 17.6 ft.
- Fir 10" dia. bears S.38°W., 19.8 ft.
- Fir 12" dia. bears N.24°W., 12.3 ft.
- Fir 24" dia. bears S.52°30'E., 20.0 ft.

S.W. CORNER OF COATS D.L.C. # 59 ON TOWNSHIP LINE **51**

Set a rock 10" x 10" x 12" on Hathornes township line at proper distance from N. W. Corner of section 31 no evidence of witness trees to be found.

"L" Corner on South and West Boundary is a similiar rock set as the S.W. corner is by measurement **52**

Jesse W. Cole Co. Surveyor  
Witnesses  
W. H. Coats, Walter Coats, N. E. Richardson  
February and March 1925.

These two corners were set by Heydon 20 years ago.

SEE 1924 RESURVEY BY G.L.O.

(See Oak Rem #105 in R.8 or #114 in R.7 1/2)