

28 T. S. 7 R. W. W. M.

YOKE-CHAPMAN CO., EUGENE, ORE. 21881

Bowker  
 Mar. 19, 1926  
 Wit. P. D. Wolford

Section Corner to Sections 32, 33, 28, & 29.  
 No Original trees. A stake is in place which Mr. Sprague says is the Section Corner. Fir trees near this stake blazed but no scribe marks visible. Marked new trees as follows:

- Red Fir 16" diam. bears N. 54° E., 47 ft.
- Red Fir 14" diam. bears S. 55° W., 31.2 ft.
- Fir 12" diam. bears N. 10° W., 13.3 ft.
- Fir 24" diam. bears S. 10½° E., 31.0 ft.

66

H. L. Eppstein, Co. Surveyor  
 Wit. Harry McCabe  
 Nichols  
 Smith  
 Jan. 25, 1928  
 C.S. 7/45

Section Corner <sup>T28-1</sup> 36, 31, 1, & <sup>T29-4</sup> ~~6~~ ~~T28-7~~  
 Set corner from old BT. which were all in place, but trees in S.E. and N.W. quadrant reversed, bearing & distance all right.

- Marked following trees:
- Oak N. 71° 15' W., 56.1 ft. Old tree.
  - Fir 14" diam. bears N. 22° E., 39 ft.
  - Fir 12" diam. bears S. 71° 30' E., 10 ft.
  - Fir 15" diam. bears S. 63° 30' W., 33 ft.

67

¼ Section Corner between 1 & 36. - S. LINE T28-TW.  
 This corner was gone and no indication of old BTs., so ran line from S.E. Corner of 36 and 1 to S.W. corner of 36 and 1 and set quarter corner on line half way between.

- Marked new bearing trees:
- Fir 18" diam. bears N. 16° E., 31 ft.
  - Fir 16" diam. bears S. 47° W., 15 ft.

68

Corner Sections 14, 15, 22 & 23.  
 Set 14 x 6 x 8 boulder from which:  
 A Fir 8" diam. bears N. 28° 50' E., 24.6 ft.  
 A Fir 28" diam. bears N. 37° 30' W., 21.4 ft.  
 F. C. Frear, in August 8, 1935, drove a 1" x 24" Ford Axle North 25.0 ft. & remarked the two old BTs.

69

¼ Section Corner between sections 14 & 23.  
 I find two witness trees as noted below:  
 W. Oak 15" diam. bears S. 77° E., 240 lks. My measurements S. 77° E., 233 lks., tree marked.  
 W. Oak 6" diam. bears N. 88° E., 260 lks. My measurements N. 88° E., 269 lks., tree marked.  
 I set a 6" x 6" x 14" Sandstone with a cross marked in the top.

70

S. E. Corner of N. Huntley D.L.C. #47.  
 I reset corner from a Black Oak 18" diam. bears N. 40° W., 47 lks. This corner I reset by a 12" x 12" x 8" Boulder set 3" deep.

71

S. W. Corner of Claim #37.  
 Rock corner in place but BTs. gone. Marked:  
 White Oak 12" diam. bears N. 32° E., 39.5 ft.

72

Corner between 10, 11, 15, & 14.  
 Reset per old BTs. 1" x 36" Iron Bar. Found stake with tack. One old 36" White Oak BT. N. 84½° E., 85.0 ft.  
 Marked: Laurel 8" diam. bears N. 24½° E., 30.6 ft.  
 White Oak 6" diam. bears S. 2½° W., 83.7 ft.

73

Section Corner to Sections 21, 22, 27, & 28.  
 Found - Hard Rock with + on top & all BTs. scribed by B.B.I., 1926. REN. #27  
 34" now 36" W.O. record S. 15° E., I find to be S. 17° E. 191.9 ft. (check Rec. Dist)  
 16" now 20" W.O. record N. 88° 41' E., I find to be N. 87° E. 134.0 ft.  
 record 184.1 ft.  
 26" now 30" W.O. record N. 27° 51' W., I find to be N. 30° W. & record dis.  
 I open this BT. center rotted but I find good reverse scribing.  
 The two other BTs. show good faces. I do not open. S21 | S22  
 Set Brass Cap alongside Hard Rock 6" X 10" X 24" mkd. T28S R7W S28 | S27  
 County Surveyor's Office, 1957 (cont. over)

74

F. C. Frear  
 June, 1917

Eppstein  
 Wit. Lane  
 McKay  
 Feb. 24, 1935

F. C. Frear  
 Wit. Richardson  
 F. D. Wolford  
 J. H. Wolford  
 Bert Lane - Swan  
 Aug. 6, 1936

James W. Byron  
 M. Godfrey  
 S. Edlow  
 Dec. 23, 1957  
 C.S. File 49/50