

Douglas County Surveyor's Record of  
Government Corners Renewed

28 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

cont.-

New Bearing Trees:

- 14" R. Fir bears N.71°W. 75.2 ft. scribed S21 T28S R7W CS BT.
- 10" Pine bears S.67°W. 56.5 ft. scribed S28 T28S R7W CS BT.

Section Corner to Sections 15, 16, 21, & 22.

Found - 1" Iron Pipe & conglomerate Rock at corner & all BTs. recorded **REN. #25** by B.B.I. have been cut except the N.E. BT. shows good scar. I do not open. I open the N.E. BT., now stump, find good scribing:

B.B.I. find Original 20" B.O. S.7°W. 56.0 ft., now down. I ~~do~~ find ~~good scribing~~ I do find 30" Oak Snag S.28°E. 79.0 ft., has been opened years ago, large chip at base, shows good scribing (Reverse) "B-S".

Set Brass Cap alongside 1" I.P. marked S16/S15 T28S R7W, County S21/S22 Surveyor's Office, 1957

- New BTs: 18" R.Fir N.12½°W. 9.5 ft. scribed T28S R7W S16 CS BT.
- 18" R.Fir S. 4°W. 31.8 ft. scribed T28S R7W S21 CS BT.
- 16" R.Fir S 11°E. 38.8 ft. scribed T28S R7W S22 CS BT.
- B.B.I. N.48°E. 43.3 ft. BT. should be N.50°E. 43.3 ft.

3/22/69 - FOUND OK. V.R.T. C.S. 511/3

Section Corner to Sections 9, 10, 15, & 16.

Found ¾" & 1¼" I.P. at Corner & three of the original BTs.

12" now 24" Laurel S.20°E. 11.2 ft., I open old scar, old face rotted but find good scribe mark near edge.

The original N.W. & N.E. BTs. now down. Have old rotted faces, check for bearings & distances.

Set Brass Cap at corner marked S 9/S10 T28S R7W County Surveyor's S16/S15 Office, 1957.

- New BTs: 16" R.Fir bears N.35°W. 13.0 ft. scribed T28S R7W. S9 CS BT.
- 18" R.Fir bears N. 6°E. 18.2 ft. scribed T28S R7W. S10 CS BT.
- 16" R.Fir bears S.86°E. 34.5 ft. scribed T28S R7W S15 CS BT.
- 11" R.Fir bears S.57°W. 42.3 ft. scribed T28S R7W S16 CS BT.

Section Corner to Sections 33 & 34, T28S R7W, & Sec. 3 & 4, T29S R7W.

From O. B. T. S.80°E. 235 lks., which Eugene Ollivant testifies is Orig. B.T. This tree has deep cut on N.W. face & old axe marks in cut & is E. 2647 ft. from N½ Corner Section 4.

Drove 2" Sq. Hd. Bolt & remarked Orig. B.T. Scribed new areas:

- 24" Cedar S.27½°E. 44.5 ft. "S3 T29S R7W 1581 BT".
- 14" Forked W.Oak N.34°E. 181.0 ft. "S34 T28S R7W".
- 7" W. Oak S.89°W. 61.0 ft. "S4 T29S R7W 1581 BT".

Corner is about 300 ft. W. of Cen. Olalla Ck. & N. Side of Dry Creek.

½ Section Corner between Section 34, T28S R7W, & Sec. 3, T29S R7W.

Set on line at mid-pt. bet. cors. ½ mi. to E. & W.

Drove Cedar Post & buried rock 4x8x10 & scribed:

- 48" Oak N.32°E. 254 ft. "½ S34 T28S R7W 1581 BT".
- 15" Forked W.Oak S.80°E. 29½ ft. "½ S34 T28S R7W 1581 BT".
- 10" W.Oak on an E.& W. fence line N.58°W. 386 ft. "½ S34 T28S R7W".

Section Corner to Sections 25, 26, 35, & 36.

Found - Orig. 15", now 36" B. Oak S.5°W. 458.7 ft. I find this dist. should be S.3°W. 445.7 ft., previously opened, shows good scribing "S BT".

30" W. Oak shows old scar, I open center, rotted, no scribing found. I believe this to be the Orig. N.60°W. 42.9 ft. BT. See Statement below by A. Boyer. I use this BT. to determine position of corner.

Set Brass Cap at Corner Mkd; S26/S25 T28S R7W County Surveyor's S35/S36 Office, 1958.

- New BTs: 10" W.Oak N.84°W. 4.4 ft. scribed T28S R7W S26 CS BT.
- 8" B.Oak S.51°W. 46.9 ft. scribed T28S R7W S35 CS BT.
- 13" W.Oak N.89°E. 12.8 ft. scribed T28S R7W S25 CS BT.
- 13" W.Oak S65°E. 13.7 ft. scribed T28S R7W S36 CS BT.

Fence Corner bears N.9°W. 7.0 ft.

Note: - See Statement by A. Boyer is C. S. File No. 49/50

75

FO 8.0  
7/24  
G. BAUGHMAN  
Rm 3-62

James W. Byron, Dep. Co. Surveyor  
M. Godfrey  
S. Blaw  
Dec. 30, 1957  
C.S. File No. 49/50

76

FO 7/8  
G. BAUGHMAN  
Rm 3-62

Arthur Boyer  
For A. Gilbert  
October, 1958 (filed)  
Map File M 12 - 72

78

79

James W. Byron, Deputy  
Milo Godfrey  
S. A. Blaw  
Nov. 7, 1958  
C. S. File No. 49/50

FO OK 2/10/68  
0.5.110  
C.S. 42/9