

Douglas County Surveyor's Record of  
Government Corners Renewed

28 T. S. 7 R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97196

1/4 Section Corner to Sections 23 & 26.

85

Found - Both Orig. BT's.

Orig. 13", now 24" W. Oak bears N.65°W. 11.9 ft. This BT. has been opened years ago, old face & center rotted, no scribing found.

Orig. 6", now 10" W. Oak Snag S.60°E. 19.8 ft., scribing visible on old face "BT".

Set Brass Cap at Corner Mkd.: County Surveyor's Office, 1958

1/4 S23 T28S R7W  
S26 213

New BT's: 17" R.Fir S.12°W. 13.4 ft. scribed 1/4 S26 CS BT.

17" R.Fir N.50°W. 18.2 ft. scribed 1/4 S23 CS BT.

1/4 Section Corner to Sec. 25, T28S.R.7W. & Sec. 30, T28S. R6W.

86

Found - Orig. 24", now 36" W. Oak S.17 1/2°W. 248.8 ft. I open & find good scribing "BT".

No trace of Orig. S. E. BT. found.

Set Brass Cap at Corner Mkd. County Surveyor's Office, 1958 1/4 S25/S30 R7W R6W

New BT's: 8" B. Oak bears N.25°E. 96.7 ft. scribed 1/4 S30 CS BT.

6" Pine bears S.22 1/2°W. 173.3 ft. " 1/4 S25 CS BT.

Note: See Sketch in file for exact location of this corner.

Fd. O.K. by  
D. BENTZ FEB. 1983  
C.S. 58/282  
NOV. 17, 1958  
S. A. BLOW  
C. S. File No. 49/50  
FD. OK 3/85  
OSHD-2563/9

SEE NEXT PAGE FOR NO. 86A


Section Corner to Sec. 36, T28/R7; Sec. 1, T29/R7; Sec. 31, T28/R6; Sec. 6, T29/R6.

Found - Orig. N.W. BT. I find 24" Oak Snag, I open & find good scribing, "S36 BT".

I do not find other Orig. BT's. I do find partly rotted Laurel Stump that was opened years ago, no scribing found today, record S.22°E. 54.2 ft., I find to be S.26°E. 51.0 ft. I believe these are the BT's. found by Eppstein, 1928. All of Eppstein's BT's. have been cut & no scribing can be found on any stump except I do find good scribing on S.W. BT. which is in slide area & far out of position. I find 18" cut Fir in slide area scribed for S.E. BT. The evidence I find of Eppstein's BT's. do not agree with Orig. nor do they come to a common corner, therefore I use the Orig. record bearing & distance from N. W. BT. to set Corner, N.71 1/2°W. 39.6 ft.

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1958

S36|S31 T28S  
S 1|S 6 T29S  
R7W R6W



New BT's: 15" R.Fir bears N.27°E. 55.6 ft. scribed T28S R6W S31 CS BT.  
15" R.Fir bears N.28°W. 47.9 ft. scribed T28S R7W S36 CS BT.  
13" R.Fir bears S.54°W.124.6 ft. scribed T29S R7W S 1 CS BT.  
No trees near to S. E.

Duplicate of #117

REN. #67

James W. Byron, Deputy County Surveyor  
M. Godfrey  
S. A. Blow  
Nov. 17, 1958  
C. S. File No. 49/50

1/4 Section Corner to Sections 25 & 36.

105

Found - W. Oak N.10°W. 26.4 ft. (Now 30" diam.), chopped open & found reverse scribing "1/4 S BT".

Oak, S.42°W. 57.4 ft., down & rotted too badly to find any trace of scribing.

At Corner Set Iron Pipe with Brass Cap Mkd: "County Surveyor's Office, 1958, T28S R7W, 1/4 S25 " & blaze & scribe following trees:

16" Fir N.82°E. 37.6 ft. Mkd. "1/4 S25 CS BT."  
8" W.Oak S.21°W. 6.0 ft. mkd.: "1/4 S36 CS BT."

RE-RENEWED, SEE CORNER NO. #247

South 1/4 Corner Section 6.

106

Set Stake - 21" Fir S.6°30'W. 35 ft. scribed 1/4 S7, 1581 B.T. 182  
21" Fir N.34°W. 39 ft. scribed 1/4 S6, 1581 B.T.

50' W. of a Creek-C. N. & S., 700' S. of mouth of Ck. on N.E. slope by uproot.

Center of Section 6. Stake.

#227 107

14" W. Fir N.75°30'W. 64 ft., scribed Cen. S.6, 1581 B.T.  
18" W. Fir N.38°E. 35 ft. scribed Cen. S.6, 1581 B.T.  
On steep sidehill slope 300 ft. S. of a Creek

Arthur Boyer 1581  
W. Menger-W. Lockwood &  
H. Eppstein, Wit.  
Nov. 17, 1958  
Map M. 13 - 19