

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 7 R. W. W. M.

KOKE-CHARMAN CO., EUGENE, ORE. 21881

137

N. W. Corner Section 5.

Found - Brass Cap at Corner & Both BT's: S. E. BT. now
snag only, shows good scribing ~~W. S. BT. now 30"~~ #230

New BT: 24" W. Fir bears ~~E. 49°E. 45.0 ft.~~ scribed N W S 5 CSET.

RE-NEWED, SEE CORNER

138

N. E. Corner Section 6.

Found - Brass Cap at Corner and Stump of S. W. BT.

New BT's: 12" R. Fir bears N. 53°W. 35.5 ft. scribed NE S6 CS BT.
5" R. Fir bears S. 13°W. 15.7 ft. scribed NE S6 CS BT.

James W. Byron, Deputy
Milo Godfrey
Clete E. Putnam
February & March 1961
C. S. File No. 49/79

Renew.

S 2/S 1 T28S R7W

139

Found - Brass Cap at Corner.

Set - 3/4" Iron Rod in E. W. Fence Line & Scribed BT:

Set Iron Rod 35.0 ft. South of Corner.

5" Ash bears S. 57°E. 67.0 ft. scribed S 1 CS BT.

North 1/4 Corner Section 5.

Found - 14", now 18" R. Fir S. 36°W. 30.4 ft., shows good scars. #140

S. E. BT. standing but dead.

Brass Cap at Corner.

New BT: 20" R. Fir bears S. 51°E. 12.5 ft. scribed 1/4 S 5 CS BT.

W. P. for above Corner (N. 4°54'W. from North 1/4 S. 5, T28-7W. #141

Found - Brass Cap at Corner & Stump of Orig. S.W. BT., shows
good reverse scribing.

Stump of S.E. BT. Orig. N. W. BT. not found.

New BT's: 11" Laurel N. 7°E. 24.4 ft. scribed WP CS BT.

8" R. Fir bears S. 68°W. 45.8 ft. scribed WP CS BT.

1/4 Section

1/4 Section Corner to Sections 4 and 3.

FD OK PER ARTMAN
M110-5 4-90

142

Found - Both BT's. as recorded in Gov't. Field Notes, 1924.

Iron Bar not found. S.W. BT., now 24" Fir, shows REN #8
good scar.

N.W. BT., now mostly rotted. Oak Stump shows good
scribing "SS"

Set Brass Cap at Corner Mkd: County Surveyor's Office, 1961

1/4 S4/S3 T28S R7W

New BT: 11" R. Fir bears N. 44°W. 101.8 ft. scribed 1/4 S 4 CS BT.

Note - Corner is under N S Fence and about 100 ft. N. of Barn.

James W. Byron
Milo Godfrey & Clete Putnam
Feb. & March 1961
C.S. File No. 49/50

Section Corner to Sections 3 - 4 - 9 - 10. #143

Found - 1/2" I. P. over 1/2" I. P. at Corner & record N. W. BT., REN #9
shows good scar. We also find rotted Stump, N.E. BT.

New BT: 11" W. Oak bears N. 6 1/2°E. 31.9 ft. scribed S 3 T28S R7W CS BT.

FD OK 7/30/79
K. REED
SURVEYOR
OFFICE
C.S. 60/34

Section Corner to Secs. 4 - 5 - 8 - 9. #232 144

Found - Brass Cap at Corner & Stump of 8" now 14" Ash,
N. 77°E. 11.9 ft., shows good scribing.

Now 16" Cedar, down, that shows good scar, N. 62°W. 15.2 ft.

No other Orig. or 1924 survey BT's. found.

New BT's: 6" W. Oak bears N. 41°E. 27.3 ft. scribed S4 T28S R7W CS BT.

18" Cedar bears S. 61 1/2°W. 49.5 ft. scribed S8 T28S R7W CS BT.

5" W. Oak bears N. 19°E. 23.5 ft. scribed S4 CS BT (No Trees near to N.W.)

18" R. Fir bears S. 5 1/2°E. 56.0 ft. scribed S 9 T28S R7W CS BT.

RE-NEWED, SEE CORNER

1/4 Section Corner to Section 8 and 9. #145

Found - Both BT's. as recorded by Kerr, 1953. REN #58

Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1961

1/4 S8/S9 T28S R7W