

Douglas County Surveyor's Record of
Government Corners Renewed

"T 28 T. S. 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

*found at
Bellevue
6/5/73
10/24/75
9/20/75*

Sec. Cor. 34 & 35, T28-7W. & Secs. 2 & 3, T29-7W. **171**
Found - Geared Axle at Corner. Orig. 30", now 36" W. Oak N.73°E. *see also*
132 ft., shows good scar. I do not open. #211 T29SR7W
Orig. 30", now 40" down Oak. We open & find good reverse
scribing "B" (Record S.73°E. 159.7 ft.) Should be S.59°E. 102.0 ft.
If we use record dist. & bear. to locate Sec. Cor. from SE BT.
It wouldn't check for with real old stump section in NW Quad.
New BT: 34" W. Oak bears N.24½°W. 410.0 ft. This BT. scribed within the
last few years but not of record. See Map File, M 12 - 72.

¼ Section Cor. Sec. 35, T28-7W. & Sec. 2, T29-7W. *same as 180* **172**
Found - Boyer's scribed stake at corner, down. and both BT's thus:
12", now 1" R. Fir shows good scar N.35°E. 2.5 ft.
15", now 19" R. Fir shows good scar, S.45°E. 12.0 ft.
Set - Brass Cap at Corner Mkd: County Surveyor's ¼ S35 T28S
Office, 1961 S 2 T29S R7W

Section Corner to Sections 19 and 30 Only. **173**
Found - Brass Cap set by Mensch in 1924.
12" Fir, Now 16", S.61°E. 11.2 ft.
Old Oak N.33°E. 29 ft. is down & badly rotted.
New BT: 27" Fir N.35°E. 5.0 ft. Mkd: T28S R7W S19 CS BT.

West ¼ Corner to Section 19. **174**
Found - Brass Cap Set by Mensch in 1924.
8" W. Oak, now 10", N.68°E. 56.1 ft.
30" W. Oak, orig, S.89°E. 39.6 ft., now dead & badly decayed.
New BT; 9" W. Oak N.87°E. 40.3 ft. Mkd: ¼ S19 CS BT.

Section Corner to Sections 19 - 20 - 29 - 30. **175**
Found - Brass Cap at Corner and all Mensch BT's. All show good
scars and are in good condition.
New BT- 18" R. Fir bears N.72°W. 11.3 ft. scribed S19 T28S R7W CS BT.

Section Corner to Sections 18 and 19 only. **176**
Found - Brass Cap at Corner. Both BT's. by Mensch, now down.
Orig. NE BT now partly rotted snag, shows scribe marks.
New BT's: 11" W. Fir bears N.69°E. 47.7 ft. scribed S18 T28S R7W CS BT.
6" W. Fir bears S.64°E. 5.0 ft. scribed S18 CS BT.

West ¼ Corner to Section 30. **177**
Found - Brass Cap at Corner & Stump on SE BT shows good scribing, ¼ S30.
New BT's: 9" W. Oak S.25°E. 33.1 ft. scribed ¼ S30 CS BT. #49
23" Cedar N. 6°E. 46.0 ft. scribed ¼ S30 CS BT.

¼ Section Corner to Sections 19 and 30. **178**
Found - Both BT's. OK. I open NW BT. & find good scribing.
SW BT. bears S.48°W. 9.6 ft., record S.60°W. 6.0 ft. #269
We do not find Brass Cap.
Set - Brass Cap under E. W. Fence Mkd: County Surveyor's ¼ S19 T28SR7W
Office, 1961 S30
New BT's: 7" W. Oak bears N. 2°W. 18.7 ft. scribed ¼ S19 CS BT.
18" R. Fir bears N.55°E. 15.6 ft. scribed ¼ S19 CS BT.

N. E. Corner D. L. C. No. 40. **179**
Found - Orig. 34", now 50" W. Oak S.76½°W. 134.0 ft., previously
opened, shows good scribing C 40 BT. By ring count & growth
of tree, this BT. was rescribed. I believe Orig. face is still covrd
Also find 6" x 10" x 30" Sandstone at corner.
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's Office, 1962
New BT: 14" W. Oak bears N.16°W. 140.3 ft.
scribed CL 40 CS BT. DLC 40 T28S R7W
Rescribe 50" W.O. S.76½°W. 135.3 ft. mkd. NE
NE CL 40 CS BT. August 8, 1962

James W. Byron, Deputy County Surveyor
Milo Godfrey
Clete Putnam
May 1961
C. S. File No. 49/50

*Fo. B. C. 3/85
E. Bloom
M 98-32*