

Douglas County Surveyor's Record of
Government Corners Renewed

T. 28 S. T. S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

186

$\frac{1}{4}$ Corner to Sections 16 and 17.
Established by Single prop. measurement, N.1°37'37"E. 2558.14 ft. from
corner to sections 16-17-20-21, See Ren. #184.

Set - $1\frac{1}{2}$ " Gal. Iron Pipe, from which:
24" Oak bears N. 88°28'03" E. 33.8 ft., scribed $\frac{1}{4}$ S16 BT.
16" Oak bears S. 51°00'45" W., 40.0 ft., scribed $\frac{1}{4}$ S17 BT.

SEE CORNER NO. #248

187

$\frac{1}{4}$ Corner btwn. Sections 17 and 20.
Established by single prop. meas. S.89°30'31"W. 2599.04 ft. from
section corner 16-17-20-21.

Set - $1\frac{1}{2}$ " Gal Iron Pipe, from which:
A nail in a rock face bears N. 39°37'26" E., 16.20 ft.
A chiseled "X" in a large stone bears S. 38°28'26" W., 36.60 ft.

188

$\frac{1}{4}$ Corner btwn. Sections 19 and 20.
Established by single prop. measmt. S.0°13'03" E. 2440.10 ft. from
corner to Sections 17-18-19-20.

At the point for the corner, a nail was set and an "X" chiseled in Rock,
from which: 18" Cedar scribed $\frac{1}{4}$ S19 BT bears S. 77°04'02" W. 75.5 ft.
14" Cedar scribed $\frac{1}{4}$ S20 BT. bears N. 84°23'42" E., 83.3ft.

189

Interior $\frac{1}{4}$ Corner between Sections 20 - Center of Section 20.
Point for corner is midway btwn. N. & S $\frac{1}{4}$ corners & E & W. $\frac{1}{4}$ Corners.
A nail was driven in a rock face, from which:

12" Cedar scribed C $\frac{1}{4}$ S20 BT bears N. 49°06'03"E. 74.98 ft.
6" Oak scribed C $\frac{1}{4}$ S20 BT bears S. 28°48'38" W., 8.95 ft. (S.25 W) SEE
12" Oak scribed C $\frac{1}{4}$ S20 BT bears S. 39°47'17" E. 76.59 ft. (S.42 E) C.S.
An "X" chiseled in a rock face bears N. 56° 44' 47" W., 30.4 FEET 54/113
J.M.P.

All bearings were established through solar observation.

190

$\frac{1}{4}$ Corner betwn. Sections 20 and 21.
(Was established by single prop. meas.)
At the point for the corner a $1\frac{1}{2}$ " Gal. Iron Pipe was set from which:
a 12" Madrone bears N. 42°57'31" E. 19.32 ft. scribed $\frac{1}{4}$ S21 BT.
a 8" D. Fir bears S. 40°29'21" W. 36.25 ft. scribed $\frac{1}{4}$ S20 BT.

MICROFILM TO HERE 10/67

191

S. W. Corner D. L. C. #43.
Found - Post with scribing of "S", See Ren. #57.
16", now 20" D. Fir, N.49°E. 19.1 ft., shows scribing "DL".
No trace of other BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 28 S R 7 W
Office S.W. Cor.
1968 DLC #43

New BT: 8" D. Fir N. 17° E. 47.1 ft. mkd. S.W. DLC #43 CS BT.
Note - This corner lies in fence corner, fences to south and west.

Feb. 1, 1968

FD. 8/17
H. NORTON
M 105-53

192

$\frac{1}{4}$ Corner to Section 25 and 26.
Found - $\frac{1}{2}$ " I.P. and BT's. as recorded in Ren. #17, by G. G. Stewart.
18", now 24" B.Oak, alive, S.11°W. 82.5 ft., shows good scar.

12", now 20" W.Oak, alive, N.34°E. 5.8 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 28 S R 7 W.
Office, 1968 $\frac{1}{4}$ S 26 S 25

New BT's: 7" D. Fir S. 82° E. 18.7 ft. mkd: " $\frac{1}{4}$ S25 CS BT".
9" Laurel S. 74° W. 16.7 ft. mkd: " $\frac{1}{4}$ S26 CS BT".

This corner lies at fence corner, fences N - E - W.

Feb. 1983
2/8/85
C.S. H.O.
C.S. 43/19

193

Section Corner to Sections 23 - 24 - 25 - 26.
Found - Old squared Post, No trace of I.P. called for in Ren. #16.
8" B.Oka, now down & rotted, N.42 $\frac{1}{2}$ °W. 31.2 ft., no scribe found.
6", now 10" W.Oak, alive, S.54°W. 32.5 ft., open & find scribe.
Rescribed: "T28S R7W S26 CS BT".

(continued over)

Wm. C. Stiles, Seek, Inc.
For L. & H. Lumber Co.
March 23, 1967
C. S. File No. 55/32 Map M 32 - 76

Frank Jones
& W. Penley
2/1/68
C.S. File
No. 52/79

Vernon "Ray" Tracy
Jack Heritage & V. Perron
September, 1968
C. S. File No. 52/79

SEPT 68