

Douglas County Surveyor's Record of  
Government Corners Renewed

T 28

T. S.

R 7

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

236

Center north 1/16 Sec. 6

Found - A 15" now 16" Madrone with partially healed double blaze and scribe marks visible, bears S.25°W., 54.0 ft. Tree is now down. See M 13 - 19

Set - 1" x 36" I. Pipe with brass cap 8" above ground marked:  
"County Surveyors Office"

T 28 S  
C  
CN 1/16 | S 6  
C

1977

New BT's- A 5" D. Fir bears S.58 1/2°E., 41.0 ft. double blazed and scribed CN 1/16 S6 CS BT.

A 13" Madrone bears S.84 1/2°W., 108.5 ft. double blazed and scribed CN 1/16 S6 CS BT.

R. B. Kimberling  
M. W. Cline  
Douglas Co. Surveyor  
Office  
July 6, 1977  
C.S. 59/38

7/6/77

Center 1/4 Corner for Sec. 23

Set - By proportionate measurement, set 3/4" I. Rod for corner.

RE-RENEWED, SEE CORNER NO. #254

3/78

F.L. Ingram  
For: Dennis Johnston  
3/78 C.S. 60/5

1/4 Corner for Sec. 34, and Sec. 3 of T.29-7.

Found - Boyer's 1/4 corner, mound of 4 or 5 rocks, one being approx. 4" x 8" x 10" and the remains of a cedar post. Ren. #78.

Oak near E-W fence with good scar N.41°15'W., 386.5 ft. 386.5 ft.

53" B. Oak with visible "B.T." N.60°30'E., 257.7 ft.

O. Oak with good scar S.78°10'E., 293.9 ft.

Set - 3/4" Rod at Boyers Corner.

10/78

William Ruppert  
For: David Stine  
M 73 - 73  
October 1978

Sec. Corner to Secs. 33 and 34; and Secs. 3 and 4 T.29S. R.7W.

Fd. - Orig. 30" Oak with deep axe markds bears S.80°E., 155.1 ft.

24" now 36" Cedar with healed face bears S.27 1/2°E., 44.5 ft.

See Ren. #77.

7" now 10" Oak with healed face bears S.89°W., 61.0 ft.

14" now 30" double oak stump with healed face bears N.34°E., 181.0 ft.

Set - 5/8" x 30" Iron Rod from bearing trees.

Placed BT tags on all trees.

Glenn Baughman  
LS# 536  
For: Douglas Co.  
Lumber  
Aug. 1980  
M 85 - 35  
C.S. 58/144

240

Section corner for Sections 14, 15, 22 and 23.

Found - Iron pipe with 1971 County brass cap W.C. properly marked. Ren. #215 firmly set flush with ground.

1 1/4" x 26" iron rod lying buried at approx. corner location. Ren. #215

12" now 14" D. Fir bears S.61°E., 73.6 ft. from wit. cor. Partially healed well pitched over single blaze with an "8" visible.

16" now 20" D. Fir, bears N.64°W., 108.6 ft. from Wit. Cor. Well healed single blaze.

Both 5/8" I.R.'s set "north" of cor. for reference

8" now 33" D. Fir bears N.28 1/2°E., 25.1 ft. to center. Ren. #69

Did not find either 5/8" I.R.'s set N.70°30'E., for reference.

Set - Using the two 5/8" I.R.'s set north of the cor. for ref. I RESET the 1 1/4" x 26" iron rod. While digging the hole I find what I assume to be the stone set in Ren. #69, since this stone fits both the wit. cor. and the two ref. 5/8" I.R.'s, I drive the 1 1/4" x 26" I.R. alongside stone until flush with ground and end is directly over stone. I tied two points to cor. for additional ref. (see sketch)

Sec. cor. now lies in a gravel pull off 7.5 ft. northerly of north edge of pavement. Stone is approx. 16" in the ground.



Greg Quibell  
Deputy, Doug  
Co. Surveyor  
Off.

Witnesses:  
Karen Mosley  
April 9, 1981

1/4 Corner for Secs. 13, & 24.

Set - 5/8" x 30" I.R. with plastic cap mkd. RS 901 from one orig. BT.

BT fd.- 20" B. Oak stump (hollow) with a scribe negative, bears S.7°E., 7.26-ft.

New BTs- 24" B. Oak bears S.57°E., 18.0-ft.

10" Madrone bears N.85°W., 17.48-ft.

4/23/82

Max H. Hull LS 901  
For: Griffis, Bob  
April 23, 1982  
M 92 - 4  
C.S. 58/179