

Douglas County Surveyor's Record of  
Government Corners Renewed

T 28

T. S.

R 7

R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97501

1/4 Corner for Section 12; and Sec. 7 of T.28-6

255

Found - A 1" dia. octagonal gun barrel firmly set and protruding  
3" from ground. Set by Frear. Ren. #99

Possible orig. BT stump hole containing rotted oak wood lies  
in vicinity of record call N.36°W., 26 lks.

Other original BT gone.

4" madrone now a 14" D.B.H. madrone bears N.08°E., 10.9 ft.

Center of tree is rotted out. No evidence of blaze or scribing  
is found. Ren. #99

30" black oak, now a stump rotted to ground bears N.64 3/4°W.,

25.7 ft. In rotted fragments of trunk is found wood formerly  
covering a single blaze with reverse scribing, "1/4 S BT"

(preserved at the Douglas County Surveyors Office) Ren. #99

An 8" now a 11" D.B.H. black oak bears S.44°E., 11.4 ft.

(Rec. S.46°E.) Dist. to center of crown. (Rec. Dist. 11.9 ft.  
measures to center of trunk at height of upper blaze.) Tree

has well healed double blaze. No scribing visible. Ren. #113

An 8" now a 12" D.B.H. white oak bears S.54 1/2°W., 34.0 ft.

Tree has healed double blaze, no scribing visible. Ren. #113

New Accessories:

A DCSO BT tag is attached to NE madrone from Ren. #99 and marked  
per record.

A DCSO BT tag is added to SE oak from Ren. #113 and marked  
S.44°E., 11.4 ft.

Note: Corner is 450 ft. + north of intersection of Happy Valley Rd. and  
Lookingglass Rd. and 150ft. + west of Happy Valley Rd. Corner is  
uphill from roadway on east slope of a ridge. Corner lies 1 1/2 ft.  
north of point where east-west fence and remains of fence running  
south intersect.

7/30/84

256

Section corner for Secs. 13 and 24; and 18 & 19 of T.28-6

CORNER REPORT ONLY.

Found - A 1982 County brass cap on a I.P. flush with ground. Ren. #243

A 12" double trunked maple with visible scribing in partially  
healed blaze on east for "S R 7 W S13 CS" bears N. 11 1/2°W.,  
46.1 ft. (Rec. N.9°W., 46.1 ft.) See Ren #'s 223 & 243

A 19" now 20" maple with visible scribing in a partially healed  
single blaze "T28S R6W S18 CSBT" bears N.56°E., 159.8 ft.

(Rec. N.62°E., 158.9 ft.) is to southerly maple of two maples  
which root crowns have grown together.

A 48" now a 46" cottonwood with visible scribing in a partially  
healed double blaze "28S R7W S13 CS BT" bears N.25°W., 21.7 ft.  
(Rec. N.22 1/2°W.)

A 47" now 43" cottonwood with a boat spike 6 ft. above ground.  
Spike bears S.47°E., 3.1 ft. (Rec. S.44°E.)

Iron pipe per Ren. #223 not found. Probably removed when field was plowed.

8/29/84

257

North 1/4 Corner for Section 6 (only)

Found - GLO 1924 brass cap on a 2 in. I.P. protrudes 16 inches above  
ground properly marked.

16" now a 27" W. oak with a well healed single blaze bears  
S.87°W., 15.8 ft. (Rec. S.85°W., 15.0 ft.) 1924 resurvey.

10" W. oak now a depression in the ground bears S.48 1/2°E.,  
28.7 ft. Orig. (1924 resurvey)

8" now a 25" D. fir with a well healed double blaze bears S.20°E.,  
45.0 ft. (Rec. S.18°E.) Ren. #131

New Accessory:

A 5/8" I.R. with an alum. cap stamped "Douglas Co. Rd. BDPA  
R-W 40" protrudes 4 in. above ground bears N.43°E., 33.8 ft.

Corner lies in a open field, 55.5 ft. south of Reston Rd. #5.

9/13/84

R. W. Smith  
Stephen Flause  
Douglas County Surveyors  
Office  
July 30, 1984  
C.S. 62/18

Douglas County  
Surveyors Office  
Randall Smith  
Stephen J. Flause  
Aug. 29, 1984  
C.S. 62/21

Douglas County Sur-  
veyors Office  
Randall W. Smith  
Stephen J. Flause  
Sept. 13, 1984  
C.S. 62/21