

Douglas County Surveyor's Record of
Government Corners Renewed

T 28

T. S.

R 7

R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97501

274

Section Corner for Section 36 and Sec. 6 of T.29-6, Sec. 31
of T.28-6 and Sec. 1 of T.29-7

Found - 1985 DCSO 2½" dia. brass cap on a 1½" O.D. iron pipe which
protrudes 16" above ground. Ren. #117

Orig. 10" laurel now 24" dia. at base 3 ft. high rotted Oak
stump with axe mark (mix-up in orig. rec. See Ren. #67 and
Ren. #117) bears N.71¼°W., 39.6 ft. (agrees with orig. and
Ren. No. 117. Possible problem with distance in Ren. 67.

15" now 20" dia. D. fir with a fully healed double blaze, bears
N.27°E., 55.6 ft. Ren. No. 117

15" now 23" dia. D. fir with a fully healed double blaze,
bears N. 28°W., 47.9 ft. Ren. No. 117

13" now 18" dia. D. fir with a fully healed double blaze bears
S.54°W., 124.6 ft. Ren. No. 117

18" dia. 4 ft. high rotted D. fir stump, previously opened
with illegible scribing visible, blaze faces west, stump is in
a slide area, bears S.60°W., 54.7 ft. One of Eppstein's BTs
Ren. #67. See comments in Ren. #117

SE BT of Eppstein's looked for, not found.

Other BTs by Eppstein not looked for.

New BT - 12" madrone bark scribed "T29S R6W S6 CS BT" bears S.43°E., 39.0'.
Corner lies on a westerly slope.

2/6/90

275

¼ Corner for Secs. 22 and 27.

Found - A 1½" O.D. x 36" long iron pipe, brass cap lying on ground. Iron
pipe is bent. (Ren. # 209). Ren. # 226.

6" now 14" dia. W. Oak with fully healed dbl. blaze, bears
S.51½°E., 36.7 ft. (Rec. S.49°E., 36.7). Ren. #209.

12" now 31" dia. 18" high pine stump, possible lower blaze, no
scribing found, bears N.43¼°W., 66.3 ft. (Rec. N.42°W., 66.3
ft.). Ren. # 209.

Set - A 1½" O.D. x 32" long iron pipe with brass cap is set flush with
ground at referenced plumb position of flanges from found iron
pipe. Brass cap from Ren. # 209 and 226 placed along east edge
of new BC/IP at bottom of hole.

New BT's- 42" dia. maple dbl. blazed & scribed "¼ S22 CS BT", bears
N.77½°E., 120.2 ft.

11" dia. multi trunk B. Oak dbl. blazed & scribed "¼ S22 CS BT"
on most southerly trunk, bears N.18¼°W., 141.9 ft. to center of
root crown.

Corner lies in a field approx. 70 ft. northerly of Co. Rd. # 108
(Strickland Canyon Rd.), and 100 ft. west of Mile Post 6.

Douglas County
Surveyors Office
Randall Smith
Stephen Flause
Feb. 6, 1990
C.S. 64/5

Douglas County
Surveyor's Office
Randall W. Smith
Stephen J. Flause
Jan. 7, 1993
C S 64/39