

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 7 1/2 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

H. L. Eppstein
Wit. B. A. Lane
Fitzpatrick
Hollis Green
June, 1930

N. E. Corner of Section 6.
Standard Government Post set by Minch, U.S. Surveyor, in 1924. S. 6
From Which: Red Fir 24" diam. bears S. 23°W., 30.0 ft. R. 7 1/2
Red Fir 12" diam. bears S. 63°W., 20.0 ft.

1

H. L. Eppstein
Wit. B. A. Lane
Lige Mathews
June 1930

Corner Sections 1 & 6 R. 7 1/2 W. & R. 8 W.
This corner was set by me in 1922. Reset by Minch in 1924 with
Standard Gov't Post. I marked witness trees, which were not #17
changed: Red Fir 24" diam. bears S. 30°30"E., 32.8 ft. marked C.S.
T. 28 S., R. 7 W., S. 6 E. T.
Red Fir 30" diam. bears S. 11°W., 29.5 ft. marked C. S.
T. 28 S., R. 8 W., S. 1 B. T.

2

James W. Byron
Milo Godfrey
July 29, 1957
C. S. File No. 49/5

R8W R7 1/2 W
Corner Sections S1 | S6 T 28 S.
S12 | S7
Found 2" Iron Pipe with Brass cap marked "U.S. General Land Office Survey".
Also found 32" Fir N. 72°W. 34.8 ft. showing good scar-did not chop out.
18" W. Fir N. 37°E. 23.8 ft. showing good scar-did not chop out.
14" Fir S. 19°W. uprooted & down.
Chinquapin brush growing at location for S. E. BT.
New Trees: 22" D. Fir S. 70 1/2°W. 22.6 ft. Bark Scribe T28S R8W S12 CS BT.
8" I. Cedar S. 49°E. 28.5 ft. Blaze & Scribe T28S R7 1/2 W. S7 CS BT.
July 29, 1957

3

1/4 Section Corner to Sec. 18, T28-7 1/2 W & Sec. 13, T28-8W.
Found - Brass Cap at Corner. N.E. BT. now snag. N. W. BT. O.K.
New BT: 12" W. Fir bears S. 5°E. 13.5 ft. scribed 1/4 S18 CS BT.

4

East 1/4 Corner Section 6 only,
Found - Brass Cap at Corner and 16", now 22" Fir Stump N. 47°W. 23.1 ft.,
We open & find good scribing. S. W. BT. not found.
New BT's: 12" R. Fir bears N. 75°W. 28.7 ft. scribed 1/4 S 6 CS BT.
14" R. Fir bears N. 29 1/2°W. 39.7 ft. scribed 1/4 S 6 CS BT.

5

1/4 Section Corner to Sec. 6, T28-7 1/2 & Sec. 1, T28-8W.
Found - Brass Cap & N. W. BT., now stump. S. E. BT. is O.K.
New BT: 17" R. Fir bears N. 70°W. 37.0 ft., recently scribed 1/4 S 1 &
other scribing.

6

Corner to Sections 6 and 7 only.
Found - Brass Cap at Corner & S. W. BT. Okay.
Marked New BT: 12" Cedar bears N. 22°E. 4.3 ft. scribed 1/4 S CSBT.

7

Corner to Sections 7 and 18 only.
Found - Brass Cap at Corner. The S.W. BT. is now snag, shows good
scribing. The N.W. BT. is alive, shows good scars.
New BT: 20" R. Fir bears S. 48°W. 32.1 ft. scribed S18 T28S R7 1/2 W CS BT.

8

Section Corner to Secs. 7 & 18, T28-7 1/2 W & Secs. 12 & 13, T28-8W.
Found - Brass Cap at Corner. 36" Fir S. 80°W. 6.6 ft., alive & in
good condition.
Dogwood, down & dead, S. 74°E. 12.5 ft., showing old scribing.
30" Fir, dead snag, N. 17°E. 38.9 ft.
36" Fir, uprooted & dead, N. 26°W. 34.3 ft.
New BT: 18" D. Fir N. 54 1/2°W. 77.0 ft. scribed T28S R8W S12 CS BT.

9

1/4 Corner to Sec. 7, T28-7 1/2 W & Sec. 12, T28-8W.
Found - Brass Cap at Corner. S.E. BT. is O.K. & S.W. BT. now stump.
New BT: 12" R. Fir bears N. 5°W. 14.2 ft. scribed 1/4 S12 CS BT.

10

James W. Byron, Deputy County Surveyor
Milo Godfrey
Clete Putnam
May 1961
C. S. File No. 52/79