

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Sec. corner to secs. 7 and 18, T28S, R8W and 12 and 13, T28S, R9W. **24**
I set stake for this corner from a 60 inch Fir which bears N.35°00'E., 14 lks.
dist., the only bearing tree of the original four trees marked.
I mark a 60 inch fir, S.27°15'W, 43.30 feet dist. for new bearing tree for this
corner

C. S.
Iemanowski
April, 1953
For the Coos
Bay Inbr.
File 41/153

SEE CORNER NO. 27

1/4 corner to 11 & 14.
Found 1 1/2" round axle, set by Epstein in 1930, recorded Vol. 1, page 116.
I mark -REN. #39
10" Madrone S 11 - BT., N.53°E., 23.6.
14" R. Fir S.14 E. T. S.15°E., 49.6.

Floyd Frear
D. Owens-Oh
Ray Johnson
C. Stubbs
Wm. Cooper
File 41/270

SEE CORNER NO. 142

Center 1/4 section corner to section 22.
Set at the intersection of the N-S and E-W centerlines of section 22.
Corner point is a rock in place, 4 feet by 4 feet, protruding 4 feet above
the ground, from which
A Chinquapin, 10, bears N.0°10'E., 162 lks.

N. E. Britt
Co. Surveyor
July 16 & 17,
1880.
Vol. 1,
Page 82.

FD OK 7/93 M117-37 Hemburger

Section corner to secs. 7 & 18, T 28 S., R 8 W., and secs. 12 & 13, T 28 S.,
R 9 W. **27**
Found a 3 inch x 3 inch x 36 inch stake at corner on shoulder of road REN. #24
and bearing trees as recorded by Frear in 1953 except for the original
B. T. which has been removed for road widening. The 1953 renewal -REN. #22
B. T.s check for bearings and distance.
Set an iron pipe with Brass Cap 4 inches under surface marked

James W. Byron, Deputy County
Surveyor
April 25, 1956.
C. S. File No. 47/90.

12/7 T 28 S County Surveyors Office, 1956.
13/18 R 9 W R 8 W

Coos Co. Doug. Co.
All trees in this area are to be removed for B. P. A. line. I scribe
near ground. Stumps to remain.

I scribe:

- These should be
feet.
R 61
- 6 inch R. Fir, S.83°E., 26.5 feet, T28S, R8W., S 18 CS BT.
 - 5 inch R. Fir, N.66°E., 90.0 feet, T28S, R8W., S 7 CS BT. (Bark scribe).
 - 6 inch R. Fir, N.54°W., 84.0 feet, T28S, R9W., S 12 CS BT. (Bark scribe).
 - 6 inch R. Fir, S.41°W., 91.0 feet, T28S, R9W., S13 CS BT. (Bark scribe).

Section corner to secs. 1, 2, 11 & 12. **28**
Found 30 inch rotted (Fir) stump scribed BT-real old scribe. I believe it
is original S. W. BT. I use this BT to set corner.
Set iron pipe with brass cap mkd. County Surveyors Office, 1956, 2/1
T 28 S, R 8 W. 11/12 #166

James W. Byron, Deputy County
Surveyor.
Sept. 4, 1956.
C. S. File No. 47/136.

From which:

- 14 inch R. Fir, bears N.24°W., scribed T 28 S., R 8 W., CS BT S 2,
6.8 feet dist.
- 14 inch R. Fir, bears S.76°E., 13.3 feet, scribed T 28 S, R 8 W, CS BT,
S 12, BT.
- 22 inch Hemlock bears S.17 1/2°W., 23.5 feet scribed T 28 S, R 8 W, S 11
CS BT.
- 14 inch R. Fir bears N.22 1/2°E., 29.0 feet scribed T 28 S, R 8 W., S 1
CS BT.
- Also found 1 inch Iron pipe, bears S.32°W., 3.5 feet.

Section Corner to Section 10, 11, 14, & 15. **29**
Found 2"x2" rotted Fir stake 6 inches above ground with scribe marks visible.
At approx. bearing & distance N 56°30'E 86.3 ft. found uprooted & badly
rotted Fir. Scribe marks "CS S10" were plainly visible. REN. #1641
At S 65°E 143 lks found badly rotted fragments of Oak stump, one portion
showed reverse scribe marks. Not legible but unmistakably scribing.

James W. Byron, Dep. Co. Surveyor
M. Godfrey
J. Fee
July 31, 1957
C.S. File No. 49/5

Blaze & Scribe New Trees:

- 4 inch D. Fir N 71°W 40.4 feet marked "S 10 CS BT.
- 8 inch D. Fir S 65°W 72.8 feet marked T28S, R8W, S 15 CS BT.
- 7 inch W. Oak (forked 30" above ground Diam. below Fork 7") N 74°E 29.1 ft.
marked S 11 CS BT.
- 8 inch Madrone S67°E 36.5 feet marked T28S, R8W S 14 CS BT.

At Corner set Iron Pipe with Brass Cap stamped County Surveyors Office
1957 T28S R8W 10/11 Sections
15/14

FD OK
8/14/84
Done
Office
C.S. 27-2/21