

Government Corners Renewed

28 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO. EUGENE, ORE. 21881

F. J. Cole Deputy
Wit: Chas. Wilson
S. A. Gurney
J. W. Gurney
1915
Jan.

010 Ren Val. 1/16/16

CORNERS OF WM. WEEKLEY D.L.C. NO. 41

S. E. Exterior "L" Corner.

Renew corner from stump of original B.T. and marked:
A White Fir in diam. N.65°E., 8 lks.

PROBABLE COR. IS REN. #17-120
SEE REN. NO. 143 SAME AS NOT #143

30

N. W. Corner of Claim 41.

Renew corner from original tree which is dead,
Marked: a Fir 12" in diam. S.79°45'E., 68 lks.

31

N. E. Corner of Claim 41.

Renewed from stump of Orig. Ash BT., no marks visible.
Set Oak Post from which:
A 7" Willow S.78°W. 114 links.

SEARCHED FOR 3/3/70
NOT FOUND
J.M.P. C.S. 52/70

32

J. W. Cole, Co. Surveyor
Wit: W. H. Coats
H. Bergh
E. Richardson
Feb. 1923

U. 2/29
2/6/28

S. E. Corner of Lathrope D.L.C. #37.

Renewed this corner from original BT. which shows scribe marks on being chopped open but is much larger than called for in field notes. Set an Iron Pipe 1" X 30", marked a new tree:
A White Oak 8" diam. bears S. 14.7 ft.
A Chittim 10" diam., not marked bears East 0.5 ft.

33

N. E. Corner of Lathrope Claim 37.

Set from stump of old BT. Identified by its position only.
Set an Iron Pipe 1" x 30". Also Cedar Post from which:
A Pine 16" diam. bears S. 30°00'W., 90 ft.
A White Oak 42" diam. bears S. 14°00'E., 139.5 ft.

34

Set Corner of Section 29, 30, 31 and 32.

Set corner from old BT. Other trees gone.

Marked new trees as follows:

- Fir 12" bears N.50°W., 3.2 ft.
- Fir 8" bears S.43°W., 7.8 ft.
- Fir 8" bears S.16°E., 13.0 ft.
- Fir 10" bears N.81°E., 4.8 ft.

35

1/4 Corner between Section 29 and 32.

Set Corner from old BTs. which were badly rotten.

Marked New BTs.: Red Fir 10" diam. bears N.42°W., 1 lks.
Red Fir 6" diam. bears S.41°W., 1 lks.

36

1/4 Corner between 11 and 12.

Set 1 1/2" x 2' Ford shaft from one old BT., a 30" Fir.
Marked new BTs.: W. Fir 16" diam. bears N.44°30'W., 96 ft.
W. Fir 14" diam. bears N.35°00'E., 120.5 ft.

37

1/4 Corner between 2 and 11.

Set a Yewwood Post from old BT., a 36" Cedar.
Marked new witness trees: W. Fir 6" diam. bears N.65°W., 14.0 ft.
R. Fir 14" diam. bears S.80°E., 19.2 ft.

38

1/4 Corner between 14 and 11.

Set a Dodge axle half way on line between section corners.
Quarter Corner lost, trees gone.
Marked new BTs.: Fir 30" diam. bears S.63°E., 82.0 ft.
Fir 12" diam. bears N.12°W., 120.0 ft.

39

1/4 Corner between 10 and 11.

Set a 3" x 3" x 30" Oak Stake from two Oaks, O.B.T.
Marked new BTs.; Black Oak 24" diam. N.26°W., 73.0 ft.

40

Section Corner between 10, 11, 14, and 15.

Set a post for corner from O.B.T. in Section 11 which had scribe marks, other trees in evidence but cut down and partly burned.

41

H. L. Eppstein
Wit: C. Martin
E. Edmonds
J. Frederickson
Nov. 5, 1924

CS 8/28
48-54

H. L. Eppstein, Co. Surveyor
Witnesses: Harley Johnson
B. A. Lane
G. C. Sellers
March 4, 1930

U. 4/26/29
CS 14/5/28

RE-RENEWED, SEE CORNER NO. #202

SEE CORNER NO. 58

SEE CORNER NO. 63

SEE CORNER NO. 62

SEE CORNER NO. 25

SEE CORNER NO. 76

SEE CORNER NO. 29

REN. #1 & 41
SHOULD BE COMBINED - SEE OLD REN. VAL. PG. 116
FOR RE-RENEWAL, SEE # 29
12/22/58