

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 28 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

$\frac{1}{4}$  Corner between Sec. 36, T28-8W. & Sec. 31, T28-7W. 30-A  
Set - I. Pipe from one Old BT. and 1 Stump (Ford survey Corner)  
Marked - 16" Fir bears S.17°E. 533.0 feet 98  
24" Bl. Oak bears N.44°W. 116.0 feet.

Township Corner 28 and 29 S. R. 7 & 8 W. #152 30B  
Set Iron Pipe and remarked 4 standing Old BT's.  
(Ford Survey Twp. Corner).

Hathorn's  $\frac{1}{4}$  Corner on East Side of Section 25. 31-A  
I renewed this corner from stump s of Orig. BT's. which I identified by their size and position.  
Set - Steel Flow Post,  $\frac{1}{2}$ " x 3" x 24" for corner from which:  
Stump bears N.35°W. 108.6 feet  
Stump of 30" Oak bears N.30°E. 136.6 feet. SEE 1924 G.L.O. RESURVEY  
Marked New BT's: 18" W. Oak bears N.81°30'W. 72.2 feet  
18" W. Oak bears N.32°30'E. 56.6 ft.  
(Trees marked  $\frac{1}{4}$  S CS BT.)

$\frac{1}{4}$  Corner W. Side of Section 30, T28-7W. (Ford's Corner) 32-A  
I renewed this corner from Orig. BT's. which are alive and showed scribe marks plainly when chopped. I could not harmonize the calls for directions and distances to these trees with the facing of the blazes, so I set the corner where both trees faced & this position also checked with the tie to this corner made by Hathorn during his retracement of the Township Line.  
Set - Iron Bar  $1\frac{1}{2}$ " x 30" and a Cedar Post 4x4x36 from which #153  
Original BT's. bear as follows:  
14" Bl. Oak bears N.25°E. 91.7 ft. SEE 1924 RESURVEY G.L.O.  
18" Bl. Oak bears N.1°00'W. 85.1 ft.  
Marked New BT's: 24" Fir bears N.69°W. 5.4 ft.  
16" Fir bears N.27°E. 17.0 ft.  
~~SEE COR #117 IN T28S, R7W~~

Corner to Sections 24 and 25 on the Township Line btwn. Ranges 7 & 8. 33-A  
Renew this corner from Original Bearing Trees: #105  
Large Bl. Oak bearing scribe marks N.58°E. 30 lks.  
20" W. Oak bearing scars S.72°E. 76 lks. SEE 1924 RESURVEY  
A Hole where a tree stood bears N.18°W. 38 lks.  
A Stump of a Lrg. Bl. Oak S.72°W. 30 lks.  
Set - Fir Post 5" x 5" x 50", Also two conglomerate Rocks. 8"x10"x12"  
8" Fir bears N.46°15'E. 17.6 ft. From Which:  
10" Fir bears S.38°W. 19.8 ft.  
12" Fir bears N.24°W. 12.3 ft.  
24" Fir bears S.52°30'E. 20.0 ft.  
~~SEE COR #50 IN T28S, R7W~~

South Closing Corner to Sections 35 and 36, T27-8W. #175 34-A  
Location of Corner determined from testimony of Arthur M. Mathews,  
(See C. S. File No. 42/194)  
At Corner Point Set  $\frac{1}{2}$ " Iron Rod with stake alongside, from which:  
No Bearing Trees available.  
Drove climbers Rock Nail in cliff face, S.46°00'E. 16.0 feet dist. No. 42/194  
(Rock Nail has circular head with 1" diam. steel ring attached.)

Closing Corner to Sections 33 and 34, T27-8W. 35-A  
Found - Cedar Stake at Corner, down, badly decayed, scribe visible.  
24" Fir N.34°E. 37.6 ft., cat face.  
22" Fir N.61°W. 26.4 ft., cat face, badly burned.  
Set - Steel Tube with Survey Cap at Corner.  
Scribed - 22" Fir N. 1°E. 28.2 ft.  
25" Fir N.70°W. 31.4 ft.  
Note - This corner lays about 35 ft. North of E-W ridge in old growth Fir Stand and falls about 100 ft. North of the North line of Section 4, T28S., R8W.

G.G. Stewart, D.C.S.  
Wit: H. Nichols &  
J.H. Coats  
S. McBee  
Nov. 8, 1922

M-2  
CS  
FIVE  
5/37  
10-25-1921

Jesse W. Cole, Co. Surveyor  
Wit: W. H. Coats, Walter Coats  
N. E. Richardson  
February & March 1923

Gene E. Johnson  
Mar. 15, 1955  
C.S. File No. 42/194

G. Robert Lecklider  
Wit: Dale McFarland  
January 1961  
C.S. File No. 51/162

(Note: Property is To Be Type for Res)