

Douglas County Surveyor's Record of
Government Corners Renewed

M.W.W. 28 T. S. 8 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Section Corner to Sections 9 & 16. 42
 Found recently cut wooden stake at Corner from which:
 A 48 inch Fir Snag bears S 32°E 6.6 feet. Old but very legible bark scribing reads 1/4 S BT.
 A 24 inch Hemlock with good scar facing corner bears N 41 1/2°W 17.8 feet.
 Find newly blazed & scribed trees: 12 inch Yew N 22°W 29.7 ft. scribed 1/4 S 9 BT.
 24 inch W. Fir S 50°E 53.7 feet scribed 1/4 S 16 BT.
 Yellow tags on both new BTs were signed "L. V. Olson", May, 1957.
 R.H. Gee's business card was tacked on the Yew BT.
 At Corner set iron pipe with brass cap stamped: County Surveyor's Office 1957
 T28S, R8W, 1/4 Sec. 9
16

1/4 Section Corner to Sections 15 & 22. 43
 Found 2 1/2 inch iron pipe at Corner. REN. #13+19
 Found 36 inch Fir Stump (bark scribe) S 66°E 13.6 feet, Scribing apparent done with pocket knife, CS 1/4 S BT. REN. #6 124
 Found 22 inch Chinquapin with good scar facing corner S 38°W 8.5 feet.
 Did not chop out scar. Reblaze & scribe this tree:
 22 inch Chinquapin S 38°W 8.5 ft mark 1/4 S 22 CS BT
 Blaze & Scribe: 6 inch W. Fir N 32°E 25.3 feet.
 Other tree apparently destroyed by logging operations.

1/4 Section Corner to Section 34 & 35. 44
 Found 21 inch W. Oak S 51°E 35 feet. Has been chopped out several years ago. Face is exposed & badly rotted but some scribing is still visible. I could make out a "T", a "3", & a "5" along with fragments of other letters & numbers not legible. REN. #4
 Found 36 inch W. Oak S 50°E 99 feet. Both upper & lower faces are exposed but so badly rotted no trace of scribing can be seen. No trace remains of other BTs.
 At Corner point, which lies 2 ft. west of a fence corner, Set iron pipe with brass cap stamped County Surveyor's Office, 1957, T 28S, R 8W, 1/4 S 34|35.
 Blaze & Scribe 2 new trees:
 13 inch Cedar bears S 73°E 31 feet scribed 1/4 S 35 CS BT.
 8 inch W. Oak bears S 80°W 61.4 feet scribed 1/4 S 34 CS BT.

Section Corner to Section 1, 6, 7, & 12. 45
 Found 2 inch iron pipe with brass cap marked U.S. General Land Office Surv. #191
 T 28S R 8W R 7 1/2 W
1|6
12|7
 Also Found: 32 inch Fir N 72°W 34.8 feet showing good scar, did not chop out
 18 inch W. Fir N 37°E 23.8 ft. showing good scar, did not chop out
 14 inch Fir S 19°W uprooted & down.
 Chinquapin brush growing at location for S.E. BT.
 New Tree: Bark Scribe 22 inch D. Fir S 70 1/2°W 22.6 ft. T28S, R8W S 12 CS BT.
 Blaze & Scribe 8 inch incense Cedar S 49°E 28.5 ft. T28S, R 7 1/2 W
S 7 CS BT.

Section Corner to Section 15, 16, 21, & 22. F.O. OK 6/93 M 117-37 46
 Found: Original S.E. BT. now 36 inch sang. This tree was bark scribed. Bark with scribing "R 8" laying on ground at base of tree. Also I find evidence of Fir tree at record distance & bearing for S.W. original BT. I can find no evidence of N.E. original BT, nor S.W. original BT (which would fall in Cat Road.)
 Set brass cap marked 16|15
21|22 T 28 S, R 8W, County Surveyor's Office, 1957.
 From which: 14 inch W. Fir bears N 82°W 46.7 feet scribed T28S, R8W, CS BT.
 30 inch R. Fir bears S 47°W 39.0 feet scribed S21, T28S, R8W, CS BT.
 15 inch W. Fir bears N 86°W 42.0 feet scribed S16, T28S, R8W, CS BT.
 (This tree damaged severely, will probably die)
 10 inch R. Fir bears N 73°E 60.0 feet scribed S15, T28S, R8W, CS BT.
 26 inch Hemlock bears S 2 1/2°E 39.5 feet scribed S22, T28S, R8W, CS BT

James W. Byron, Deputy County Surveyor
 M. Godfrey
 J. Fee
 July & August, 1957
 C.S. File No. 49/5