

Douglas County Surveyor's Record of
Government Corners Renewed

28 T. S. 8 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

47

Renew C. Corner to Section $\frac{32}{615}$ T 27 $\frac{1}{2}$ R 8W
T 28 S

Found both original BTs.:

30 inch Fir now 36 inch S 48°W 35.0 feet. Good bark scribing.
BT in good condition.

36 inch Fir S50°E, Now 35 inch. Record distance 46 lks., I find it to be
26 lks. Good bark scribing, tree alive & in good condition. Note BTs
face to corner as located.

Also found 8 inch Ewewood N 64 $\frac{1}{2}$ °W 10.0 feet scribed S 5 on East side and
S 6 on West side. (Not old scribing, may be about 15 years old)

Set Brass cap at corner marked: County Surveyor's Office, 1957. S $\frac{32}{615}$ T27 $\frac{1}{2}$,R8W
From Which: 12 inch Ewewood bears S31°W 14.4 feet T28S, R8W

Scribed T28S, R8W, S 6 CS BT.

7 inch Hemlock bears S 83°E 20.0 feet scribed S 5 CS BT.

6 inch Ewewood bears N 68°W 32.8 feet scribed T27S, R8W, S32 CS BT.

Renew Corner to Section $\frac{31|32}{6}$ T 27S R 8W.
T 28S

48

Found original N 5°W, 26.4 feet 30 inch Fir snag now. Good bark scribing,
also find Fir stump 36 inch Bark gone, bears N 75°E 33.0 feet.
Record 30 inch Fir N 54°E 33.0 feet.

Position of corner determined by the one remaining BT. from which:

A real old 3"x3"x36' Ewewood stake bears S 38 $\frac{1}{2}$ ° E 15.0 feet, No scribing
On Stake.

Set brass cap at Corner marked Sec. $\frac{31|32}{6}$ T 27S, R8W County Surveyor's
T 28S, R8W. Office, 1957.

From which: 6 inch Ewewood bears N 49°E, 9.0 feet, scribed T27S, R8W S32 CS BT.

8 inch Hemlock bears N 73°W 59.0 feet, scribed T27S, R8W, S31CS BT.

24 inch Hemlock bears S 2 $\frac{1}{2}$ °W 45.0 feet, scribed T28S, R8W, S6 CS BT.

Section Corner to Section $\frac{6|520}{718}$

49

Found: Original 36 inch Hemlock. Good scribing - open face - N 24°W 39.6 ft.
Base of small rotted Hemlock Stump N 35°E 15.2 feet.

15 inch Ewewood S 42°E 14.5 feet. Shows old weathered face, no
scribing. Found checks for original S.E. BT dist. only.

Original S.W. BT not found.

Set Brass Cap at Corner marked sec. $\frac{6|5}{718}$ T 28S, R 8W, County Surveyor's
Office, 1957.

New Bearing Trees: 18 inch Hemlock S13°W 37.6 feet, scribed S 7 T28S, R8W CS BT.

15 in. Ewewood S 42°E 14.5 ft., scribed S 7 T28S, R8W, CS BT.

6 in. Hemlock N 2°E 52.2 ft. scribed S 5 CS BT.

$\frac{1}{2}$ Section Corner to Section 6 & 7.

Found: Original N.E. BT now 40 inch Fir. ~~Open old face & find scribing "S".~~
S.W. BT not found.

Set Brass Cap at corner marked: County Surveyor's Office, 1957 $\frac{1}{2}$ S 6
T 28S, R 8W.

New Bearing Trees: 16 inch Ewewood S 49°E 20.2 ft. scribed $\frac{1}{2}$ S 7 CS BT.

8 inch Chinquapin N 27 $\frac{1}{2}$ °W 9.7 ft. scribed $\frac{1}{2}$ S 6 CS BT.

Section Corner to Sections 22, 23, 26, & 27.

51

Found: Original 24 inch Fir Now 40 inch Fir, BT shows good bark scribe,
T 28S, R8W, S 27 - 55°W 40.9 feet.

All other original BTs down.

Set Brass Cap at corner marked County Surveyor's Office, 1957 $\frac{22|23}{27|26}$
T 28S, R 8W.

New Bearing Trees: 8 inch R. Fir S 55°W scribed T28S, R8W, S 27, CS BT.

10 inch R. Fir N 89°W scribed T28S, R8W, S 22, CS BT.

10 inch Cedar N 21°E 17.5 ft scribed S 23, CS. BT.

16 inch Maple S 36°E scribed T28S, R8W, S 26, CS BT.

$\frac{1}{2}$ Section Corner to section 7 & 8.

52

Found Original N.W. BT now 24 inch Hemlock, open face, scribe marks "B".

Also found Corner tree now 20 inch Hemlock & S.E. BT.

(Cont'd next page)

James W. Byron, Deputy County Surveyor
M. Godfrey
J. Fee
July & August, 1957
C.S. File No. 49/5

RE-RENEWED SEE CORNER NO. #172

Visited By
Blm 8/73
OK cor.
z.f.