

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 28 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

(continued)

Set - Brass Cap at Cor. Mkd: County Surveyor's 9 S 1 S 6 8  
Office, 1970 W S 12 S 7 W  
New BT's: 48" D. Fir S.82°E. 28.8 ft. mkd: T28S R8W S7 CS BT.  
14" Hemlock S.82°W. 85.7 ft. mkd: T28S R9W S12 CS BT.  
Note - 36" D. Fir Stump S.45°W. 30.4 ft., has been rescribed S12 BT.  
No other trees available.

C.S.  
File 54/113

4/22/70

1/4 Corner to Sections 13 and 14. (Witness Corner)

Set - 1" I. Pipe for Witness Corner by prop. measurement.  
(1/4 cor. bears N. 1° 12'45"E. 11.26 ft.)

New BT's: 8" Ash N.62° 51'W. 12.4 ft. mkd: "WC 1/4 S14 BT".  
8" Ash S.54°37'E. 13.0 ft. mkd: "WC 1/4 S13 BT".

May, '71

MARCH 71

Gee, Roger H.  
For: Liles  
Filed  
M 41 - 67

JAN 1972

Corner S31 T28S R7W  
S 6 T29S R7W

Found - Both Fir BT's. recorded by Mensh. Each is now down, We  
open & find good scar on each B.T. Ren. #30B  
Brass Cap (1924) not found.

Set - Brass Cap mkd: S31 T28S R7W County Surveyor's  
S 6 T29S Office, 1961

New BT's: 6" Cedar bears N.31 1/2°E., 82.7 ft. scribed S31 T28S R7W CS BT.  
12" R. Fir Bears S.28 1/2°E., 99.7 ft. scribed S6 T29S R7W CS BT.

152

James W. Byron, Deputy Co. Surv.  
Milo Godfrey  
Clote Putnam  
April & May 1961  
C.S. File No. 49/50

West 1/4 Corner to Section 30 T. 28-7

Found - Brass Cap at corner & stump on SE BT shows good scribing,  
1/4 30. SEE ALSO #32A

New BT's: 9" W. Oak, S.25°E., 33.1 ft. scribed 1/4 S30 CS BT.  
23" Cedar, N.6°E., 46.0 ft. scribed 1/4 S30 CS BT.

153

1/4 Corner to Section 14 and 15.

Set a Brass Cap Mkd: T.28S, R.8W, W.M. 1/4 S15, S14 1972

Found - Orig. 24" Doug. Fir BT Stump, badly rotted, scribes visible,  
bears S. 5° E. 14.5 ft.

I Scribed: 12" Douglas Fir "1/4 S, S14 BT" bears S.31 1/2°E. 42.0 ft.  
16" Douglas Fir "1/4 S, S15 BT" bears West, 47.0 ft.

8/24/72

154

Bruce A. Shaner  
For: U.S.B.L.M.  
Map File:  
M 42 - 66

Section Corner to Sec. 3 & 4 T.29-8 and Secs. 33 & 34 T.28-8.

Found - Brass Cap mkd. County Surveyor's Office T28S T29S R8W S33 S34  
S4 S3 1957. Ren. #73

Possible 12" Laurel, broken off, face rotted, bears N.20°W., 38.2 ft.

22" Douglas Fir, bark scribe bears N.73°W., 47.6 ft.

16" Douglas Fir, bears S.16°W., 18.8 ft.

Original 36" Douglas Fir, now down, bark scribes visible, bears  
N.78°E., 37.6 ft.

Original 18" Laurel, rotted stump, scribes vis. on piece of wood  
inside stump, bears S.80°E., 37.0 ft.

16" White fir, now down, bears S.59°E., 18.6 ft.

New BT's - I scribe 16" Douglas Fir, bears N.22°E., 27.7 ft.

I scribe 8" White Fir, bears S.88°E., 41.6 ft.

155

Bruce A. Shaner  
For: U.S.B.L.M.  
Map File:  
M 42 - 67

1/4 Corner, Sections 23 & 26.

Set - Brass Cap

New BT's - 7" White Fir, bears N.56°E., 9.9 ft.

7" White Fir, S.30°W., 15.6 ft.

156

Sun Studs Inc.  
by Baughman Survey  
M 47 - 76  
March 1973

Center 1/4, Section 23.

Set - Brass Cap

New BT's - 10" Black Oak, bears N.85°E., 26.6 ft.

8" Black Oak, bears N.78°W., 20.0 ft.

157

(2070 10001 1000)