

Douglas County Surveyor's Record of
Government Corners Renewed

T 28

T. S.

R 8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

174

1/4 Corner for Section 6; and section 1 of T.28-9

Found - Orig. 12" now 14" chinquapin snag 12 ft. tall. Fragmentary scribing "3" visible in previously opened face.
Orig. 12" now 14" rotted chinquapin windfall with reverse scribed BT visible on remains of stump. Scribed 1/4 visible on rotted remains of tree.
7" fir with scribed 1/4S BT. Ren. #171
8" fir with scribed 1/4S BT. "
10" hemlock stump. "

Gregory Quibell, Deputy
Doug. Co. Surveyors Office
Karen Reed
April 26, 1982
C.S. 61/30
(See C.S. 61/33 for
Floyd Vandervelden
Information)

The 7" fir, 8" fir and 10" hemlock stump all have "W" nails & Weyerhaeuser BT tags.
Set - I set a 1" x 30" I.P. with brass cap attached at record bearings and distance from the 14" chinquapin windfall, N.85°E., 15.2 ft. (23 links) Cap marked "Douglas County Surveyor" T28S R8W 1/4 S1 S6 R9W 1982.
The 14" chinquapin snag matches rec. for bearing (S.70°E.) but not for distance. 23.8 ft. (36 links.) Rec. 56 links. If orig. notes have a 20 link error, then this tree would also match record.

Note: The two fir BTs mentioned in Ren. #171 plus the 10" hemlock stump mentioned in Ren. #171 do not fit with this cor., but instead fit with a 1 1/2" fir stake which bears S.70°E., 8.4 ft. from set brass cap. I scratch "void" across existing BT tags on these trees

New BT's- 7" fir scribed "1/4 SBT" (per Ren. #171) bears N.53 1/2°E., 11.0 ft (scribing does not face cor.)
8" fir scribed "1/4S BT" (per Ren. #171) bears S.54°E., 4.2 ft. (scribing does not face cor.)
7" fir scribed "1/4 S1 CS BT" in double blaze bears N.28 1/2°W., 6.3 ft.
8" fir scribed "1/4 S1 CS BT" in double blaze bears S.4°W., 18.1 ft
10" hemlock stump with "W" nail in face bears N.66°E., 45.0 ft.

Brushed line runs north & south out of corner. Line crossing tag south approx. 500 ft.

4/26/82

175

Southeast corner for Sec. 35 only of T.27-8.

Found - Marking on rock wall at the base of 100 ft. high bluff, including "BO, T27S, R8W," and "S46E, 16" which is the bearing and distance listed by Johnson in 1955. (Ren. #34A)
No evidence of piton with circular ring, but evidence where originally driven in crack in rock face. Found no trace of 3/4" iron rod for corner.

Set - 1 1/2" iron pipe with brass cap using Johnson's bearing and distance measured from rock wall described above

From which:

6" douglas fir, scribed BT, bears N.52 1/2°E., 16.0 ft.

11/26/79

176

Section corner for Secs. 1, 2, 11 and 12

Found - County brass cap on I.P., firmly set, protruding 8" from ground. Ren. #28

Orig. Fir, 30" now a rotted 30" dia. stump approx. 18" tall. Stump has rotted fragment of face with clearly legible "BT".
No other original trees found.

Found from Ren. #28: (See Also Ren. #166)

14" R. fir, now 22" dia. stump 4 ft. tall bears N.24°W., 7.1 ft. (rec. N.24°W., 6.8 ft.) Tree has well healed double blaze.

14" R. fir now 18" dia. fir stump 8" tall bears S.80 1/2°E., 13.3 ft. (Rec. S.76°E., 13.3 ft.) No scribing found.

22" hemlock now a 32" D.B.H. stump approx 5 ft. tall bears S.17 1/2°W., 23.5 ft. Tree has partially healed double blaze with scribing "SBT" visible.

14" R. Fir now a 21" D.B.H. Douglas fir, bears N.21°E., 29.6 ft. (Rec. N.22 1/2°E., 29.0 ft.) Tree has well healed double blaze.

No scribing visible.

1" iron pipe protruding 2" above ground bears N.33 1/2°W., 3.3 ft. (Rec. N.32°W.)

New BTs - 9" D.B.H. W. Fir, bears S.5 1/2°E., 64.2 ft. scribed "T28S R8W S12 CS BT" on a double blaze.

8" D.B.H. W. fir bears N.50°W., 24.7 ft. scribed "T28S R8W S2 CS BT" on a double blaze.

Tags on found accessories are altered to show measurements from the renewal.

8/24/84

Henry Reppeto
For: Weyerhaeuser Co.
Nov. 26, 1979
C.S. 58/219

Douglas Co. Surveyors Office
S. J. Flause - R. W. Smith
August 24, 1984
C.S. 62/21

RE-RENEWED NO. 190