

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 28 T. S. R 8 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

Section corner for Sections 1 and 2 only *FO. OK 9/94 B/ DeGROOT M 120-67* **184**
 Found - 1961 County brass cap. Ren. #95
 20" fir bears S.2½°W., 73.5 ft. Closed face. (1961)
 38" fir stump bears S.40½°E., 57.42 ft. Chop marks visible on
 badly rottenstump. Ren. #88
 36" laurel bears N.14°E., 117.0 ft. (Rec. 114.6 ft.) No scribing
 visible on double face. (1961)
 New BT - 9" fir bears S.29°E., 72.6 ft. scribed T28S R8W S1 BT.

1/4 Corner for Section 1 only, north boundary. **185**
 Found - 1960 1½" iron pipe set by Ramsey. Ren. #91
 31" white oak bears N.87°E., 218.5 ft. Rotted face (orig.)
 44" black oak down and decaying. (orig.)
 50" cedar bears S.36°W., 63.3 ft. (rec. 57.4 ft.) Closed face. (1960)
 New BT - 14" black oak bears S.24°E., 101.6 ft. scribed N 1/4 S1 BT.

Section corner for Sec. 36 of T.27-8 and Sec. 31 of T.27-7 only. **186**
 Found - 1961 County brass cap. Ren. #106
 Scribe marks on a fir stump which has been destroyed and
 dragged out of position.
 New BTs - 4" fir bears N.46°E., 34.4 ft. scribed X BT.
 8" fir bears N.78°W., 47.9 ft. scribed T27S R8W S36 BT.

Section corner for Sec. 1; and Sec. 6 of T.28-7½ **187**
 Found - 1924 GLO 3¼ brass cap on a 3" I.P. (See Ren. 2 in R. 7½)
 23" rotted fir stump, 3 ft. tall, bears S.12°W., 30.3 ft.
 (Rec. 31.0 ft.) No scribing. (1924)
 25" rotted fir stump bears S.29°E., 34.3 ft. No scribing. (1924)
 New BTs- 8" fir bears S.6½°E., 136.0 ft. scribed T28S R7½W S6 BT.
 8" fir bears S.31°W., 198.3 ft. scribed T28S R8W S1 BT.

1/4 Corner for Sections 2 and 1. *FO. OK 9/93, BAUGHMAN 1993-0067* **188**
 Set - 2½" alum. cap on a 2½" x 30" alum. flared pipe in a cultivated
 field. Ramsey's 1960 1½" I.P. bears S.04°23'09"W., 15.88 ft.
 See Ren. No. 87
 New BTs - 11" fir bears S.74°W., 188.0 ft. scribed 1/4 S2 BT.
 9" oak bears S.63°E., 143.4 ft. scribed 1/4 S1 BT.
 An unrecorded 1" iron pipe bears N.87°47'28"E., 12.76 ft. from corner.

Center 1/4 Corner for Section 1. **189**
 Set - An alum. cap on a 2½" x 30" alum. flared pipe. in B.P.A. R/W.
 Ramsey's 1960 I.P. bears S.00°57'15"E., 4.29 ft. from corner.
 See Ren. No. 90 and 159
 New BTs - 9" fir bears N.45°W., 59.9 ft. scribed C 1/4 S1 BT
 5" fir bears N.19°E., 69.0 ft. scribed C 1/4 S1 BT
 An unrecorded 1" iron pipe bears S.60°26'40"W., 29.92 ft. from corner.

Section corner for Secs. 1, 2, 11 and 12. **190**
 Found - 1956 County brass cap on a 1" I.P. See Ren. No's 176, 166, 28
 30" badly rotted, orig. fir stump bears S.78°W., 18.5 ft.
 Fragmentary scribing visible on loose piece of wood.
 18" fir stump bears S.76°E., 13.3 ft. No scribing visible. (1956)
 21" fir stump, 4 ft. tall, bears N.24°W., 6.8 ft. Healed face.
 32" hemlock stump, 5 ft. tall, bears S.17½°W., 23.5 ft. Scribing
 partially visible. (1956)
 21" fir bears N.21°E., 29.6 ft. (Rec. N.22½°E., 29.0 ft.) Closed
 Face. (1956)
 8" fir bears N.50°W., 24.7 ft. Scribing visible. (1984)
 10" fir bears S.05½°E., 64.0 ft. Scribing visible. (1984)
 New BT - 7" fir bears S.63°W., 81.65 ft. scribed T28S R8W S11 BT.
 An unrecorded 1" I.P. bears S.34°13'36"W., 3.25 ft. from corner.

*FO. OK 9/93, BAUGHMAN
1993-0067*

Ronald G. Geisler L.S. #1988
 For: Champion International Corp.
 Nov. 1985- Jan. 1986
 M 90 -79