

Douglas County Surveyor's Record of  
Government Corners Renewed

T 28

T. S.

R 8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

199

Wayne L. Rogers  
For: BLM  
June 20, 1989  
C.S. 63/87

1/4 Corner for Sections 34 and 35  
CORNER REPORT

Found - County Surveyors iron post 1 1/4" diam., found in top of road cut bank loosely set projecting 18" above ground. Ren. #44  
Orig. BT, an Oak 38" dia. bears S.50°E., 150 lks. healed double blaze.  
1934 BT by Boyer, A white oak 21" dia., bears S.49 1/2°E., 53 lks. dist., with healed double blaze. Ren. #4  
A cedar, 21" diam., bears S.71 1/4° E., 47 lks. dist. healed double blaze. Ren. No. 44  
A white Oak, 10" diam., bears S.82 1/2°W., 93 lks. dist. with healed double blaze. Ren. No. 44

Monument was referenced out and reset projecting 6" above ground.  
No new accessories established.

Corner is located in cut bank on East edge of Suicide Creek Road.  
6/20/89

200

Section Corner for Sections 25 and 36 only.  
(No monument and no orig. BTs found.)

Set - 1 3/8" O.D. iron pipe with a DCSO 2 1/2" brass cap, is set 18" below ground. mkd. "Douglas County Surveyors T28S R8W S25 | R7W 1989"  
A hub and tack is set over top of BC position S36 |  
of true section corner determined from Ren. #196.  
referenced position of witness corner. True corner set 25 ft. east of witness corner.

New BTs-18" dia. alder ref. tree with PK nail from Ren. #196, PK/nail bears S.88°W., 85.5 ft. (BT tag refers to wit. cor.)  
24" dia. alder double blazed and scribed "T28S R8W S36 CS BT" bears S.25 3/4°W., 51.9 ft.  
24" dia. 6 ft. high alder stump in a multi trunked clump of dead snags, has a partially healed double on east trunk, scribing visible "B 8" bears S.63°W., 45.2 ft. (Wit. cor. BT, from C.S. 5/37)  
28" dia. double trunked alder double blazed and scribed on south-east trunk "T28S R8W S25 CS BT" bears N.58°W., 172.5 ft.

Corner lies in a newly developed field.

6/28/89

201

Witness Corner for Section Corner for 25 and 36 only.

Found - 24" dia. 6 ft. high alder stump in a multi trunked clump of dead snags, has a partially healed double blaze, with scribing visible "B 8" bears S.35°W., 26.5 ft. agrees with Ren. #196.  
BT also referenced with a PK nail in Ren. #196. PK nail bears S.38°W., 25.33 ft. (Rec. S.42°W., 25.33 ft. compass apparently read wrong in Ren. #196.) BT tag refers to true corner.

SW Cor DLC #39 not checked this renewal. See Ren. #196.  
NE and NW BTs gone.

18" dia. alder with PK nail in blaze, bears S.87°W., 60.49 ft. agrees with rec. (Ren. #196) (PK nail used as ref. to set wit. cor.) BT tag refers to wit. cor.

17" dia. alder snag with a record bearing of S.01°W., 45.89 ft. PK nail not used as ref. to set corner. Tree is pushed over and out of position.

Witness corner position is determined from two trees referenced with PK nails in Ren. #196. (See above accessories). The marks "RESET 1989" are added to brass cap that had been saved in the Douglas County Surveyors Office. BC/IP is buried 24" below ground. A hub and tack is set over BC/IP.

New BTs -24" dia. alder double blazed and scribed "T28S R8W S36 CS BT" bears S.3 1/4°E., 46.9 ft. Also a renewal tree for true section cor. Bt tag refers to true section corner.

28" dia. double trunked alder double blazed and scribed on south-easterly trunk "T28S R8W S25 CS BT" bears N.53°W., 152.2 ft. Also a renewal tree for true section corner. BT tag refers to the true section corner.

Corner lies in a newly developed field.

6/28/89

Douglas County  
Surveyors Office  
Randall W. Smith  
Stephen J. Flause  
June 28, 1989  
C.S. 62/63

Douglas County  
Surveyors Office  
Randall W. Smith  
Stephen J. Flause  
June 28, 1989  
C.S. 62/63