

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 28 S. T. S. R. 8 W. R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 97101

Bruce Shaner  
For: Superior Lumber Co  
June 1993  
M 112-78; C.S. 63/153

211

1/4 Corner for Section 30; Section 25 T28-9.  
Found - 3 1/2" Brass Cap on a 2 1/2" iron pipe from which:  
18" Hemlock stump (rec. 12") face overgrown, bears S.39°E., 15.3 ft. (rec. 14.2 ft.)  
26" Hemlock (rec. 10") face overgrown, bears N.39 1/2°W., 23.1 ft.  
New Accessories -  
12" W.Fir, bears N.80°W., 47.3 ft. scribed "1/4 S25 BT"  
22" W.Fir, bears S.1°E., 2.3 ft. scribed "1/4 S30 BT"  
18" Hemlock, bears S.28°E., 40.2 ft. scribed "1/4 S30 BT"  
6' steel fence post North 0.5 ft. from corner.  
Note - Corner is S.60°E about 400 ft. from U.S.B.L.M. logging road.

212

Center 1/4 Corner for Section 30.  
Set - 2 1/2" Brass Cap on a 1" x 30" Galv. iron pipe 24" in the ground.  
New Accessories -  
10" D.Fir, bears S.2°E., 24.4 ft. scribed "C 1/4 S30 BT"  
12" D.Fir, bears S.62°W., 20.2 ft. scribed "C 1/4 S30 BT"  
6" D.Fir, bears N.69°W., 16.8 ft. scribed "C 1/4 S30 BT"  
10" D.Fir, bears N.23°E., 21.0 ft. scribed "C 1/4 S30 BT"  
Note - A found 1" x 30" iron pipe bearing N.22°W., 3.8 ft. was placed alongside Brass Cap.  
Corner is 600 ft. east from old mainline logging road.

Donald Bentz,  
L.S. #839  
For: Superior Lumber Co.  
July 1993  
M 112-89

213

Center 1/4 Cor. Sec. 16  
Set - 5/8"x30" I.R. with cap mkd: "i.e. ENGINEERING"  
BTs - 12" Hemlock, N.79 1/2°E., 16.0' - Blazed  
4" Chinquapin, S.18°E., 13.2' - Blazed  
8" Fir, S.22°W., 15.8' - Blazed  
A 5/8" I.R. in a 14" Hemlock bears N.6 1/2°E., 0.57'.

7/93

Donald Bentz  
L.S. #839  
For: Superior Lumber Co  
Aug. 1993  
M 117-61

214

Center 1/4 Cor. Sec. 28  
Set - 5/8"x30" Iron Rod w/cap mkd; "i.e. ENGINEERING"  
BTs - 16" Hemlock, bears N.62°E., 18.65', (Pd blazed as a Cor. Tree)  
14" Hemlock, bears S.70 1/2°E., 9.2'  
10" Fir, bears, S.70°W., 2.5'  
8" Fir, bears, N.14°W., 24.2'  
ALL TREES SCRIBED W/ BT TAGS

8/93

215

1/4 Corner for Sec 12 & Sec. 7 of T.28-7 1/2  
Found - 2 1/2" dia. Brass cap on a 1" O.D. iron pipe protruding 8" above ground. (1924) See renewal # 102.  
Accessories Found -  
10" now 19" dia. D.Fir with a fully healed single blaze, bears S.59°E., 9.9 ft. (1924)  
8" now 12" dia. 4 ft. high D.Fir stump with a fully healed single blaze, bears S.31°W., 7.3 ft. (1924)  
12" now 17" dia. D.Fir with a fully healed double blaze, bears N.5°W., 14.2 ft. (1961)  
New Accessories -  
6" dia. Pine, double blazed and scribed "1/4 S12 CS BT" bears S.55 1/2°W., 34.9 ft.  
7" dia. D.Fir double blazed and scribed "1/4 S12 CS BT" bears N.43°W., 39.5 ft

D.C.S.O. Randall Smith,  
Stephen Flause, May 23, 1994  
C.S. File 64/51

FDOK  
BY B. Shaner 7/96  
M124-30  
CS 65/8-12B

John Safstrom  
for: Coos Bay Timber  
Sept. 1961  
C.S. 63/161

216

1/4 cor. sec. 19 & 24 of T28-9  
Monument set - 1 1/2" i.p. 3' long was driven 2' in ground  
New Accessories - Hemlock 22", bearing East 28.8', measured to center of tree & scribed 1/4 S 19 BT.  
D. Fir stump 48" bearing S.52°W., 25.9', measured to nail in face & scribed 1/4 S 24 BT.

RE-RENEWED CORNER NO. # 217