

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

North  $\frac{1}{4}$  Corner to Section 2 only, T30-1W.

Found - unrecorded 1967 alum. cap mkd: USPC Prod. Corp. T29S RLW  
(See Shrum's Survey M 36 - 14) RE 1287 #154

New BT's: 7" D. Fir S. 47° W. 11.7 ft. mkd.  $\frac{1}{4}$  S2 CS BT.  
9" D. Fir S. 52° W. 21.9 ft. mkd.  $\frac{1}{4}$  S2 CS BT.

**RE-RENEWED, SEE CORNER NO. #154**

2/7/68

8

$\frac{1}{4}$  Corner to Section 34 only, T29-1W.

Found - 16x12x10 Stone mkd. " $\frac{1}{4}$ ".  
30", now 34" D. Fir, N. 40 $\frac{1}{2}$ ° E. 87.8 ft., shows good scar.  
?30" Pine, now 25", N. 51 $\frac{1}{2}$ ° W. 79.2 ft., shows good scar.

Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's T 29 S  
Office, 1968 T 30 S RLW  $\frac{1}{4}$  S 34

Bearing Trees O. K. and Tagged.

Note - This corner lies 33.0 ft. E. of  $\frac{1}{4}$  Cor. Sec. 3 only, T30-1W.  
Also 25" Pine N. 51 $\frac{1}{2}$ ° W. was used for both corners.

2/20/68

9

$\frac{1}{4}$  Corner to Section 3 only, T30-1W.

Found - Stone, out of place, mkd. " $\frac{1}{4}$ ".  
10", now 28" S. Pine, S. 45° E. 57.4 ft., shows good scar.  
9"?, now 25" S. Pine, N. 30° W. 56.1 ft., shows good scar.

Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's T29S  
Office, 1968 T30S RLW  $\frac{1}{4}$  S 3

New BT: 15" S. Pine S. 5° W. 19.6 ft. mkd.  $\frac{1}{4}$  S3 CS BT.

Note - This corner lies west of  $\frac{1}{4}$  Cor. Sec. 34 only, T29-1W. 33.0 ft.

2/20/68

Township Corner to Sections 31, T29-1E & Sec. 6, T30-1E.

Found - Stone at Corner, but no marks.  
24" D. Fir, now down, S. 49° E. 12.5 ft.  
10" Cedar, now 13", N. 61° E. 7.9 ft., opened for scribe "BT".

Set - Brass Cap at Cor. Mkd: County Surveyors R T 29 S R  
Office 1 S 1 S 31 1  
1968 W S 6 E  
T 30 S

New BT's: 15" Fir N. 27° E. 12.3 ft. mkd. T29S R1E S31 CS BT.  
31" D. Fir S. 58° E. 29.0 ft. mkd. T30S R1E S6 CS BT.  
12" D. Fir S. 76° W. 16.4 ft. mkd. T30S RLW S1 CS BT.

10

$\frac{1}{4}$  Corner to Section 1 only, T30-1W.

Found - No Corner Stone.  
40" D. Fir, now stump, N. 66° W. 28.4 ft., opened for scribe " $\frac{1}{4}$ ".  
24" D. Fir, now stump, S. 51° W. (Rec. S. 30W) 35.6 ft.  
Using 1 bearing & 2 distances, I renew corner. T 30 S

Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyors R T 30 S R  
Office 1  $\frac{1}{4}$  S 1 1  
1968 W E

New BT's: 22" Cedar S. 57° W. 42.0 ft. mkd.  $\frac{1}{4}$  S 1 CS BT.  
15" Laurel N. 40° W. 34.2 ft. mkd.  $\frac{1}{4}$  S1 CS BT.

Note - This corner lies in old skid road, running N. & S., 266.4 ft.  
South of Township Corner, see above.

2/28/68

12

Township Corner to Sec. 31, T29-1E. & Sec. 36, T29-1W & Sec. 1, T30-1W.

Found - Fir Stump, out of place, opened for scribe marks "B S".  
By using 40" Pine Stump, line tree, 71.9 ft. south of corner:  
Set - Brass Cap at Cor. Mkd: County Surveyors R T 29 S R  
Office 1 S 36 S 31 1  
1968 W S 1 E

Note - I set this corner 211.2 ft. north of  $\frac{1}{4}$  S31 only, See Ren. #13.  
New BT's: Laurel N. 55° W. scribed T29S RLW S36 CS BT.  
14" Cedar N. 51° E. 70.0 ft. mkd. T29S R1E S31 CSBT.  
No trees available in S.W. Quad.

6/12/68

**RE-RENEWED, SEE CORNER NO. #126**

John M. Powell  
Frank Jones & W. Penley  
February, 1968  
C. S. File No. 54/59