

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S., T. S. R. 1 W. R.W.W.M.

ROBE-CHAPMAN CO., EUGENE, ORE. 21881

West  $\frac{1}{4}$  Corner to Section 31 only, T29-1E. 13

Found - 5" Fir, down & out of place, opened for scribe " $\frac{1}{4}$ ".  
6" Laurel, now dead & out of place, S. 42° E. 31.7 ft.,  
found possible scribe marks.  
40" Pine Stump, probable line tree, 139.3 ft. north of corner,  
b6 using line tree and Laurel BT., I set:  
Set - Brass Cap at Cor.Mkd: County Surveyor's T 29 S R 1 E  
Office, 1968  $\frac{1}{4}$  S 31  
New BT's: 12" Fir S. 75° E. 23.0 ft. mkd.  $\frac{1}{4}$  S31 CS BT.  
12" Y.Pine N. 71° E. 36.3 ft. mkd.  $\frac{1}{4}$  S31 CS BT.  
Note - This corner lies 211.2 ft. south of Twp. Cor., See Ren. #12.  
6/12/68

$\frac{1}{4}$  Corner Section 1 Only, T30S-R1W. 14

Found - Stone, firmly set at  $\frac{1}{4}$  corner mkd: " $\frac{1}{4}$ " on south face.  
12", now 32" D.Fir, N. 80°W. 17.8 ft., tree badly scared  
and burnt, scribe visible, " $\frac{1}{4}$ ".  
12", now 34" D.Fir, S. 77° W. (Rec.S.87W) 20.5 ft., has  
burnt cat face.  
Set - Brass Cap at Cor.Mkd: County Surveyor's T 29 S R 1 W  
Office 1968  $\frac{1}{4}$  S 1  
Rblzd. & Rscbd: 34" D.Fir S.77°W. 20.5 ft.mkd.  $\frac{1}{4}$  S1CSBT. T 30 S  
New BT: 9" Hemlock S.64°E. 14.0 ft. mkd.  $\frac{1}{4}$  S 1 CS BT.  
Note - This corner lies 205.3 ft. E. of  $\frac{1}{4}$  cor. Sec. 36 only, T29-1W,below.

$\frac{1}{4}$  Corner Section 36 only, T29-1W. 15

Found - Stone, firmly set at P corner, mkd: " $\frac{1}{4}$ " on north face.  
16", now 21" D.Fir, N. 6° E. 48.8 ft., some scribe work visible.  
16", now 30" Pine, N. 28 $\frac{1}{2}$ °W. 70.6 ft., shows scar.  
Set - Brass Cap at Cor.Mkd: County Surveyor's T 29 S R 1 W  
Office 1968  $\frac{1}{4}$  S 36  
T 30 S  
Bearing Trees O.K. and Tagged.  
Note - This corner lies 205.3 ft. W. of  $\frac{1}{4}$  Cor.Sec. 1, T30-1W, see above.

Section Corner to Secs. 3 & 4, T30-1W. & Secs. 33 & 34, T29-1W. 16

Found - 10", now 15" Cedar Corner Tree, shows good scars.  
12", now 15" D.Fir, N. 70°E. 38.9 ft., shows good scar.  
16", now 25" Cedar, S.54°W. 12.5 ft., shows good scar.  
12", now 16" Laurel, N.56°W. 31.7 ft., shows scar, some scribe  
marks visible.  
Set 15" D.Fir, now dead, S.10°E. 32.3 ft., opened for scribe "3".  
Set - Brass Cap at S.side of Corner Tree Mkd: T 29 S R 1 W  
County Surveyor's S 33 | S 34  
Office 1968 S 4 | S 3  
T 30 S  
New BT: 6" Laurel S. 7° E. 28.0 ft. mkd. "T30S R1W S3 CS BT".  
All other BT's. O.K. and Tagged.

South  $\frac{1}{4}$  Corner to Section 35 only. 17

Found - 2 $\frac{1}{2}$ " Aluminum Cap in 1968 (Set in June 1967, See M 36-14)  
4" D.Fir, S. 24° W. 16.0 ft. (Dead)  
9" D. Fir N. 16° W. 14.5 ft. (Down)  
Set - 8" D. Fir, N. 32° E. 19.9 ft. Mkd: S $\frac{1}{4}$  S35 BT.  
**RE-RENEWED, SEE CORNER NO. #155**

Section Corner to Sections 2 and 3 only, T30-1W. 18

Found - White Fir Stump 26", S. 86°W. 59.2 ft.  
30" Cedar Stump, S. 85° E. 39.40 ft.  
Set - 2 $\frac{1}{2}$ " Aluminum Cap and 6" Fir S.56°E. 22.45 ft.  
12" Fir S.27°W. 27.60 ft.  
5" Fir N.20°W. 42.95 ft.  
**RE-RENEWED, SEE CORNER NO. #119**

F.D. OK. #17/77 - D. GAYLORD - DOUG. Co. Deputy - E.S. 59/42

John M. Powell  
Frank Jones & W. Penley  
June and July, 1968  
C. S. File No. 54/59

Thomas E. Shrum, Jr.  
For: U.S. Plywood  
June, 1967  
C.S. 55/106 & M 36 - 14