

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 1 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21001

Section Corner to Sections 35 and 36 only, T29-1W. 19

Found - Sugar Pine Stump, Corner

RE-RENEWED, SEE CORNER NO. #153
26" Sugar Pine N. 35° E. 5.30 ft. (down)
16" Fir N. 53° W. 34.5 ft.
Set - 2 1/2" Aluminum Cap and 24" Fir N. 45° E. 13.70 ft.

Section Corner to Sections 2 and 1 only, T30-1W. 20

Found - Brass Cap and 30" Hemlock S. 40° W. 11.2 ft.

RE-RENEWED, SEE CORNER NO. #149
Set - 32" Fir S. 46° E. 20.9 ft.
28" Fir S. 60° W. 17.50 ft.
24" Fir N. 41° 30' E. 45.80 ft.

21

1/4 Corner to Section 15 and Section 16.

Found - Orig. Stone, firmly set (12x10x5) at corner mkd: "1/4" on west face.

Orig. 36", now 42" D. Fir, N. 70° W. 15.2 ft., shows good scar.

Orig. 15", now 21" D. Fir, N. 12° E. 46.2 ft., shows good scar.

All Bearing Trees O. K. and Tagged.

Set - Brass Cap at Cor. Mkd: County Surveyor's T. 29 S. R 1 W
Office S 16 | S 15
1969

22

Section Corner to Sections 21 - 22 - 27 - 28.

Found - Orig. 18x15x5 Stone, firmly set mkd. with notches.

Orig. 24", now 40" D. Fir, N. 31° E. 15.8 ft., shows good scar.

Orig. 12", now 28" R. Fir, S. 64° E. 17.2 ft., shows good scar.

Orig. 12" R. Fir, now stob, S. 25° W. 20.5 ft., scribe visible.

Orig. 10", now 15" D. Fir, N. 54° W. 19.1 ft., scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
Office S 21 | S 22
1969 S 28 | S 27

New BT: 30" D. Fir S. 15° W. 11.2 ft. mkd: T29S R1W S28 CS BT.

All other BT's. O. K. and Tagged.

23

1/4 Corner to Section 21 and 28.

Found - Orig. Stone, set firmly at 1/4 cor. mkd. "1/4" on north face, stone 15x10x4.

36", now 42" Cedar, N. 45° E. 27.1 ft., shows good scar.

24", now 30" Cedar, S. 53° W. 13.2 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
Office 1/4 S 21
1969 S 28

No new bearing trees marked, tagged trees.

24

1/4 Corner to Section 28 and 27.

Found - 20x12x10" Orig. Stone, firmly set, mkd: "1/4" on west face.

Orig. 50" S. Pine, now stump, N. 67° E. 13.2 ft., scribe visible.

No trace of other Orig. BT., location falls in road.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
Office 1/4 S 28 | S 27
1969

New BT's: 11" Sugar Pine S. 27° W. 18 ft. mkd: S28 CS BT
9" D. Fir N. 24° E. 11.4 ft. mkd: S27 CS BT

Note - Road No. 2827 bears west 50.0 ft.

25

Section Corner to Sections 15 - 16 - 21 - 22.

Found - Stone, 15x12x5, set firmly at corner mkd. with notches.

40", now 48" Fir, N. 39° E. 66.0 ft., shows good scar.

12", now 42" S. Pine, S. 64° E. 38.3 ft., shows faint scar.

30" D. Fir, now stump, S. 70° E. 31.7 ft., opened for scribe.

40" D. Fir, now stump, N. 45° W. 46.9 ft.

(continued next page)

Thomas E. Shrum, Jr.
For: U.S. Plywood
June, 1967
C.S. File 55/106 M 36-1A

John M. Powell
Frank Jones & W. Penley
April, 1969
C. S. File No. 54/82