

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 1 W. R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

(continued)

#26  
Cont.

Set - Brass Cap at Cor. Mkd: County Surveyor T 29 S R 1 W  
Office S 16 | S 15  
1969 S 21 | S 22

New BT's: 8" R.Fir N.83°W. 9.7 ft. mkd: T29S R1W S16 CS BT.  
7" R.Fir N.21°E. 5.9 ft. mkd: T29S R1W S15 CS BT.  
12" D.Fir S.86½°E. 38.0 ft. mkd: T29S R1W S22 CS BT.

26

¼ Corner to Section 22 and Section 23.

Found - No trace of Corner Stone or S. W. BT., corner lies in clear-cut unit.

Orig. 18" D.Fir, now stump, S.30°E. 35.6 ft., opened for scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W  
(Steel Fence Post Office ¼  
alongside Brass Cap) 1969 S 22 S 23

New BT: 42" D.Fir S. 42° E. 178.0 ft. mkd: "¼ S23 CS BT".

Also Set ¾" I. Rod North 15.0 ft. & 5/8" I. Rod North 25.0 ft.

27

¼ Corner to Sections 14 and 23.

Found - 30", now 38" Corner Tree, good scars on North & South face.  
20", now 28" Cedar, S.29°E. 37.0 ft., shows good scar.  
36", now 41" D.Fir, N.40°W. 15.8 ft., tree opened before pitched over, scribe visible.

Set - Brass Cap on East side of Corner Tree mkd: T 29 S R 1 W  
County Surveyor's ¼ S 14  
Office, 1969 S 23

All BT's. O. K. and Tagged.

28

¼ Corner to Sections 15 and 22.

Found - 18x10x6 Stone, firmly set at corner, mkd. "¼" on North face.  
20" D.Fir, now stump, S.45°E. 50.2 ft., shows good scar.  
8" D.Fir, now stump, N.14°E. 6.6 ft., opened for scribing, rotten face but found definite scribe marks.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W  
Office ¼ S 15  
1969 S 22

New BT's: 7" D.Fir N. 44° E. 25.2 ft. mkd: "¼ S15 CS BT".

19" Laurel S. 48° W. 38.8 ft. mkd: "¼ S22 CS BT".

29

¼ Corner to Sections 21 and 22.

Found - 18x12x8" Stone mkd: "¼".  
24", now 30" Cedar, S.88°W. 29.0 ft, scribe visible, "¼ 21 T".  
20, now 36" D.Fir, N.81°E. 60.1 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W  
Office, 1969 ¼ S 21 S 22

All Bearing Trees O. K. and Tagged.

30

Section Corner to Sections 17 - 18 - 19 - 20.

Found - 16x10x5 Stone at corner, notches visible, 5 on E. & 3 on S.  
36" D.Fir, now Snag, N.46°E. 59.4 ft., shows good scar.  
40", now 55" D.Fir S.12°E. 24.4 ft., shows good scar.  
36", D.Fir, now stob, S.50°W. 54.1 ft., shows good scar.  
36", now 44" D.Fir, N.43°W. 17.2 ft., ptchd. over, scribing visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W  
Office S 18 | S 17  
1969 S 19 | S 20

New BT's: 6" D.Fir S.83°W. 7.0 ft. mkd: "T29S R1W S19 CS BT".

12" D.Fir N.60°E. 33.1 ft. mkd: "T29S R1W S17 CS BT".

John M. Powell  
Frank Jones & W. Penley  
April, 1969 C. S. File No. 54/82