

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 2188T

31
 $\frac{1}{4}$ Corner to Sections 16 and 17.
 Found - No trace of corner stone.
 14", now 30" W. Fir, N. 39° W. 23.8 ft., shows good scar.
 40" D. Fir, now snag, S. 88° E. 19.8 ft., scribing visible.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
 Office, 1969 $\frac{1}{4}$ S 17 | S 16
 New BT: 28" D. Fir S. 31° E. 48.3 ft. mkd: " $\frac{1}{4}$ S16 CS BT".

32
 $\frac{1}{4}$ Corner Sections 19 and 30.
 Found - No trace of Corner Stone nor N.E. Bearing Tree.
 30" W. Fir, now stump, S. 7° W. 21.1 ft., opened for scribe " $\frac{1}{4}$ S B".
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
 Office $\frac{1}{4}$ S 19
 1969 S 30
 New BT's: 14" Cedar N. 18° W. 80.4 ft. mkd: " $\frac{1}{4}$ S19 CS BT.
 10" Cedar N. 52° W. 85.9 ft. mkd: " $\frac{1}{4}$ S19 CS BT.
 This corner lies in large cut unit. No other trees available.

33
 $\frac{1}{4}$ Corner to Section 30 and 31.
 Found - 18x10x10 Stone " $\frac{1}{4}$ on north side.
 30", now 39" D. Fir, N. 60° E. 50.8 ft., shows good scar.
 30", now 40" D. Fir, S. 3° E. 65.3 ft., opened for scribe "BT".
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
 Office $\frac{1}{4}$ S 30
 1969 S 31
 New BT's: 7" D. Fir N. 67° E. 13.5 ft. mkd: " $\frac{1}{4}$ S30 CS BT.
 12" D. Fir S. 35 7/8° E. 15.1 ft. mkd: " $\frac{1}{4}$ S31 CS BT.

34
 Section Corner to Sections 29 - 30 - 31 - 32. *Find. OK. L. HERSTEIN CS. 6/24 5/18/81*
 Found - 6", now 17" D. Fir, N. 20° W. 17.2 ft., shows good scar.
 6", now 12" Laurel, S. 52° W. 19.8 ft., scribe visible, "29".
 6", now 9" Laurel, S. 81° E. 18.5 ft., scribe visible.
 6" Laurel, now down, N. 8° E. 24.4 ft., down on face.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
 Office S 30 | S 29
 1969 S 31 | S 32
 Reblazed & Rescribed: 12" Laurel S. 52° W. 19.8 ft. mkd: T29SR1WS31 CS BT.
 New BT's: 9" D. Fir S. 65° E. 9.6 ft. mkd: T29S RLW S32 CS BT.
 17" Cedar N. 44° E. 46.4 ft. mkd: T29S RLW S29 CS BT.

35
 Section Corner to Sections 16 - 17 - 20 - 21.
 Found - No trace of Stone at Corner.
 36", now 50" D. Fir, N. 44° E. 49.5 ft., shows good scar.
 10", now 16" D. Fir, N. 29° W. 32.3 ft., shows good scar.
 30" D. Fir, now stump, S. 32° E. 44.3 ft., opened for scribe "S21".
 18" W. Fir, now burnt stump, S. 42° W. 31.7 ft.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
 Office S 17 | S 16
 1969 S 20 | S 21
 New BT's: 6" R. Fir S. 31° E. 33.8 ft. mkd: T29S RLW S21 CS BT.
 13" Y. Pine S. 12° W. 44.3 ft. mkd: T29S RLW S20 CS BT.

36
 Section Corner to Sections 17 and 16 only.
 Found - Old Orig. BT. Stump, N. 71° W. 32.3 ft. which was destroyed
 but found scribing on old face.
 No trace of Stone, nor S. E. Bearing Tree.
 12" Hemlock, down & rotten, S. 45° W. 23.1 ft., found definite scribe mks.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
 Office S 9
 1969 S 17 | S 16
 New BT's: 6" Hemlock S. 81° W. 20.6 ft., mkd: T29S RLW S17 CS BT
 6" Hemlock S. 71 $\frac{1}{2}$ ° E. 7.0 ft., mkd: T29S R1S @16 CS BT.
 14" Cedar N. 17° W. 33.0 ft., mkd: T29S RLW S9 CS BT.
 Note - This corner lies 103 ft. East of Corner to Secs. 8 & 9 only.

JOHN M. POWELL
 Frank Jones & W. Penley
 April & May, 1969
 C.S. File No. 54/82

RE-RENEWED, SELF-DENIED NO. 139