

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 1 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

JOHN M. POWELL
Frank Jones & W. Penley
April & May, 1969
C.S. File No. 54/82

Section Corner to Sections 8 & 9 only. 37
Found - Orig. 8", now 10" Yew, N.13°E. 18.5 ft., scribe visible.
Orig. Cedar, now down, onface.
G.L.O. 1922 Brass Cap, properly marked.
New BT: 26" Maple N. 36° W. 52.4 ft., mkd. T29S R1W S8 CS BT.
Note - This corner lies 103 ft. west of corner to secs. 17 & 16 only.

Section Cornerto Sections 15 & 16 only. 38
Found - Orig. 10" D.Fir S. 10° E. 18.5 , shows good scar.
1962 BT's: 15" D.Fir, now down, S. 22° W. 15.0 ft. See. Ren. #3.
14", now 15" D.Fir, N.62°E. 32.0 ft., pitched over scrb. visible.
Co.Surv. Brass Cap mkd. in error in1962, & Stone at Sec. Cor.
Remarked Brass Cap as follows: County Surveyor's T 29 S | R 1 W
Office S 10
1962 S 16 | S 15
New BT: 26" W.Fir S. 70° W. 47.0 ft. Mkd: T29S R1W S16 CS BT.
Note - This corner lies 128.7 ft. East of Sec. Cor. to Secs. 9 & 10 only.

Section Corner to Sections 9 & 10 only. 39
Found - 1922 U. S. G. L. O. Brass Cap, properly marked.
12", now 15" D.Fir, N. 40° E. 17.8 ft., shows good scar.
18", now 23" D.Fir, N. 38° W. 27.7 ft., shows good scar.
New BT: 7" D.Fir S. 18½° W. 16.8 ft., mkd: T29S R1W S16 CS BT.
Note - This corner lies 128.7 ft. E. of Sec. Cor. to Secs.15 & 16 only.

Section Corner to Sections 23 - 24 - 25 - 26. 40
Found - 18 x 14 x 19 Stone, firmly set & chipped, no marks.
40", now 55" D.Fir, N.23°W, 19.1 ft., shows good scar.
20", now 19" W.Fir, S.64°W. 6.6 ft., rotten face found, definite
scribe marks.
30", now 37" D.Fir, N.82°E. 18.5 ft.(Record 24.4'), shows good scar.
No trace of S. E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S | R 1 W
Office S 23 | S 24
1969 S 26 | S 25
Reblzd. & Rescbd: 29" W.Fir S.64° W. 6.6 ft. mkd: T20S R1W S26 CS BT.
New BT: 13" R.Fir S.83°E. 86.9 ft. mkd: T20S R1W S25 CS BT.

¼ Corner to Sections 23 & 24. 41
Found - 30", now 48" Cedar, S.76°E. 50.2 ft., opened for scribe.
18" Hemlock, now down & rotted, S.46°W. 5.3 ft.
15 x 10 x 8 Stonefound mkd. "¼", firmly in place.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
Office, 1969 ¼ S 23 | S 24
Reblzd. & Rescbd. 48" Cedar S.76°W. 50.2 ft., mkd: ¼ S24 | CS BT.
New BT: 9" Cedar N.14°W. 19.7 ft., mkd: T29S R1W S23 CS BT.
Note --This corner lies approx. 35.0' south of spring branch.

Section Corner to Sections 28 - 29 - 32 - 33. 42
Found - 16 x 10 x 8 Stone, firmly set with 4 notched on E. & 1 on south.
36", now 48" D.Fir, N.32°W. 46.2 ft., opened for scribe.
12", now 16" W.Fir, S.66°E. 27.7 ft., shows good scar.
No trace of N.E. or S.W. BT's.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 1 W
Office S 29 | S 28
1969 S 32 | S 33
New BT's: 16" Cedar S.29½°W. 31.7 ft., mkd: T29S R1W S32 CS BT.
25" W.Fir N.27½°E. 42.8 ft. mkd: T29S R1WS28 CS BT.

¼ Corner to Sections 22 and 27. 43
Found - Chisled + in bedrock of river bank, as recorded.
16" W.Oak, now dead, S.54½°E. 103.6 ft., shows good scar. #128
16", now 22" D.Fir, N.1°W. 77,2 ft., shows good scar.
New BT: 11" D.Fir S.69°E. 118.5 ft., mkd: ¼ S27 CS BT.
No good place for Witness/Corner as all Bed Rock or in low area.
This cor. lies on the E. bank of S.Umpqua River .visible from Rd. on W. Bank.