

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

1/4 Corner to Sections 28 and 33.

Found - 14" D. Fir, now stob, N. 36° W. 11.9 ft., scribe visible.  
14", now 16" D. Fir, S. 18° E. 14.5 ft., shows good scar.  
12 x 12 x 8 Stone, no marks on stone.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office  
1969 T 29 S R 1 W  
1/4 S 28  
S 33

New BT: 15" D. Fir N. 76° E. 19.4 ft. mkd: "1/4 S28 CS BT.

44

1/4 Corner to Sections 32 & 33.

Found - 15 x 8 x 6 Stone mkd: "1/4" on W. face, firmly in place.  
18" W. Fir, now down, N. 48° E. 20.5 ft., opened for scribe.  
18" W. Fir, now down, S. 58° W. 38.9 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1969 T 29 S R 1 W  
1/4 S 32 | S 33

New BT's: 13" W. Fir S. 50° W. 12.8 ft. mkd: "1/4 S32 CS BT.  
10" D. Fir N. 23° E. 4.5 ft. mkd: "1/4 S33 CS BT.

45

1/4 Corner to Sections 17 and 18.

Found - 30" D. Fir Corner Tree, now shows good scars on E. & W. Sides.  
20", now 29" D. Fir, N. 22° E. 21.1 ft., shows good scar.  
8" Hemlock, now down, S. 8° W. 17.2 ft., scribe visible.

Set - Brass Cap on S. Side of Cor. Tree Mkd: County Surveyor Office, 1969 T 29 S R 1 W  
1/4 S 18 | S 17

New BT: 14" Hemlock S. 55° E. 56.4 ft. mkd: "1/4 S17 CS BT.  
No trees available in west quadrant, S18.

46

1/4 Corner to Sections 17 and 20.

Found - 36" D. Fir, now 41", shows good scar.  
18" Cedar, now 34", shows scar & part of rotten face.  
15 x 12 x 10 Stone Mkd: 1/4 on W face.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor Office, 1969 T 29 S R 1 W  
1/4 S 17 | S 20

Reblazed & Rescribed: 34" Cedar S. 43° W. 30.4 ft. mkd: "1/4 S20 CS BT.

47

1/4 Corner to Sections 24 and 25.

Found - 18" D. Fir, now stump, shows good scar.  
24 x 7 x 6 Stone firmly set: "1/4 cor. mkd. 1/4 on N. Face  
No trace of D R S E P T because of Rd.

Renewal  
Set - Brass cap at 1/4 Cor. Mkd: County Surveyors Office, 1969 T 29 S R I W  
1/4 S 24  
S 25

New Bearing Trees  
6" Hemlock S 29 E 10 9', Scribed 1/4 S 25 CS BT  
6" Hemlock N 52 1/2 E 12 6'

Note: This cor. lies 60' West of Rd. on top of high cut. 5-8-69

48

1/4 Corner to Sections 25 and 36 T 29 S RIW

Found -- 10" Yew, now 10", N 65 E 48.2' Scribe visible 1/4 S 25  
Stone at 1/4 Cor. Mkd. 1/4 on N Face S W Br.

Possible large fir cut with burnt face (S.W. BT)

Set - Brass cap at 1/4 Cor. Mkd: County Surveyors Office, 1969 T 29 S R I W  
1/4 S 25  
S 36

49

New BT: 6" Hemlock N 67 E 9.8 ft.

Scribed 1/4 S 25 Cs BT

5" Hemlock S 82 1/2 E 5.4 ft. Scribed 1/4 S CS BT

This cor. in very old unit, very brushy, no good BTS 5-9-69

JOHN M. POWELL  
Frank Jones & W. Penley  
April & May, 1969  
C.S. File No. 54/82