

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Section Corner to Section 36 Only **7-29-2**, 63  
Found - 14" D. Fir, now 18", N 24 1/2 W 52.1' Shows good scar.  
48" Pine, now snag, S 88 1/2 W 40.3' Scribe visible "B"  
Also - Brass cap properly marked 1917, at 1/4 cor Mkd: S 36  
New Bearing Tree 7" D. Fir S 75 W 7.2' Scribed 1/4 S 36 CS BT  
Note: This Cor. lies 23.8 North of 1/4 Cor S 31.  
7-25-69

Section Corner to Sections 18 and 19 only 64  
Found -- 40" Pine, now 52", N 11 E (Rec. N 8 E) 80.5' Shows good scar.  
10" D. Fir, now 24", S 55 E 81.2' Shows good scar  
Also 20x12x10 Stone 3 notches on North & South edges.  
Set - Brass cap at Sec. cor. Mkd:

|                  |       |      |   |
|------------------|-------|------|---|
| County Surveyors | T 29S |      |   |
| Office, 1969     | R     | S 18 | R |
|                  | 2 S24 | S 19 | I |
|                  | W     |      | W |

New Bearing trees  
12" Cedar N 89 E 14.8 Scribed 729S RIW S 18 CS BT  
17" D. Fir S 28 E 17.0 Scribed T 29S RIW S 19 CS BT  
Note: This cor. lies 17.8' south of 13-18  
24 | 4-30-69

1/4 Corner to Sec. 19, T29-1W, and Sec. 24, T29-2W. 65  
Found - 20" D. Fir, Now 39", N20E 47.2 (Rec. 52.1) Shows good scar.  
6" D Fir, now 26", S 65 W 122.1' Shows faint scar  
Also: Brass cap at 1/4 cor Mkd. 1/4 S 24 | General land office, 1917  
Original stone along side cap mkd. 1/4.  
Remarked Brass cap as follows: General land office T 29 S

|  |           |  |   |
|--|-----------|--|---|
|  | 1/4       |  |   |
|  | R         |  | R |
|  | 2 S24/S19 |  | I |
|  | W         |  | W |

New Bearing tree  
10" Cedar S;3 W 4.2 ft. Scribed 1/4 S 24 CS BT  
7-30-69

Section Corner to Section 13 and 24 66  
Found - 14" D Fir, now 29", S 54 W 75.9' Shows good scar  
Also mound of stone by cor.  
Also 18x12x8 stone at Sec. Cor 3 notches on North & South edges.  
Set - Brass cap at Sec. Cor Mkd.

|                  |        |          |   |
|------------------|--------|----------|---|
| County Surveyors | T 29S  |          |   |
| Office, 1969     | R      | S 13/S18 | R |
|                  | 2 S 24 |          | I |
|                  | W      |          | W |

New Bearing trees:  
10" D Fir N 51 W 41.7 ft. Scribed T 29S R 2 W S 13 CS BT  
Old BT ok & tagged.  
Note: This cor. lies 17.8' North of 24 | 18  
19 | 7-30-69

Section Corner to Section 19 and 30 67  
Found - 12" Cedar now down N 39 E 48.2' Shows good scar  
24" D. Fir S 51 E 15.2' Shows good scar  
Also 16x12x8 stone firmly set at sec. cor. mkd. 4 notches on North,  
and 2 notches on South edges.  
Set - Brass cap at sec. cor. mkd.

|                  |       |           |   |
|------------------|-------|-----------|---|
| County Surveyors | T 29S |           |   |
| office, 1969     | R     | S25   S19 | R |
|                  | 2     | S30       | I |
|                  | W     |           | W |

New Bearing trees: 6" D. Fir N 30 E 15.2' Scribed T29 S RIW S19 CS BT  
10" D. Fir S 80 W 18.1' Scribed T 29S R2W S25 CSBT  
Note: This cor. lies 25' South of 24 | 19  
25 | 7-30-69

JOHN M. FOWELL  
Frank Jones & W. Penley  
April & May, 1969  
C. S. File No. 54/82