

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29S T. S. R. 1 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21801

80

$\frac{1}{4}$  Corner to Section 25 Only  
Found - Basalt Stone 13" x 8" x 6" Mkd. " $\frac{1}{4}$ " on West face at cor. point  
& BT's as follows:

36", now 40" Fir, S. 60°W, 25.1 Ft.; alive; shows good scar.

20", now 22" Madrone, N. 56.°W. 4.0 Ft. alive. Shows scar. We  
rescribe " $\frac{1}{4}$  S 25 CS BT" At cor. point set 1" I.P.F. & Brass cap mkd:

County Surveyors T 29S  
Office, 1969  $\frac{1}{4}$  R S25 | RIE  
1W

and mkd. New B.T.

16" Pine S. 15°W. 23.5 Ft. Mkd. " $\frac{1}{4}$  S25 CS BT"

This corner lies on N. E. slope in dense fir, chinquapin and madrone.

5-16-69

Section Corner to Sections 19, 20, 30, 29 *Fnd. OK L. HERZSTEIN C.S. 6/24 5/18/81*

Found - 18" Pine, now 41", N 44E 153.1 Shows scar

8" Laurel, now 14", S 88E 129.0 Shows old axe work rotten

face. 6" D Fir; now 15, S. 51W 186.6 Shows scar.

18" Laurel, now stump hole, N 25W 160.4

Also - 15x10x8 Stone firmly set at sec. cor. Mkd. 5 notches on the East  
2 South.

Set - Brass cap at Sec. Cor Mkd.

County Surveyors T 29S RIW  
Office, 1969

S19 | S20  
S30 | S29

New BT's 19" D Fir S 59°W 15.8 Scribed T29S RIW S 30 CS BT

19" D Fir N 48° W 18.7 Scribed T 29S RIW S19 CS BT

12" D Fir S 68° E 5.2 Scribed T 29S RIW S29 CS BT

12" Cedar N 58°E 20.1 Scribed T29S RIW S20 CS BT 6-4-69

81

$\frac{1}{4}$  Section Corner to Sections 30 and 29 *Fnd. OK L. HERZSTEIN C.S. 6/24 5/18/81*

Found - 40" D. Fir, now stob, N43E 33.0 Scribe visible  $\frac{1}{4}$  S 29 BT

18" Cedar, Now down, N 45W 8.6 Tree lying on face & rotting.

15x8x5 stone firmly set at  $\frac{1}{4}$  cor Mkd.  $\frac{1}{4}$  on W Face.

Set - Brass cap at  $\frac{1}{4}$  Cor. Mkd:

County Surveyors Office, 1969  
T 29S RIW

$\frac{1}{4}$   
S30/S29

New BT's 12" R Fir N33E 34.6 Scribed  $\frac{1}{4}$  S29 CS BT

10" Cedar S73 W 16.7 Scribed  $\frac{1}{4}$  S30 CS BT 6-4-69

82

$\frac{1}{4}$  Section Corner to Sections 35 and 36

Found - 30" D Fir Cor. tree, now 38", shows good scars

24" D Fir, now stump, N43W 29.0 Opened for scribe "BT"

Set - Brass cap on East side of 38" Cor. tree Mkd:

County Surveyors T 29S RIW  
Office, 1969

$\frac{1}{4}$   
S35/S36

New Bearing trees

10" Cedar S 10E 24.0 Scribed  $\frac{1}{4}$  S36 CS BT

8" Cedar N63E 50.0 Scribed  $\frac{1}{4}$  S 36 CS BT

No trees to the West old clear cut unit.

5-9-69

83

JOHN M. POWELL  
Frank Jones & W. Penley  
April & May, 1969  
C. S. File No. 54/82