

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

84

Section Corner to Sections 26, 25, 35, 36
 Found - 24" D. Fir, now stump, S 80 E 17.1 Scribe visible T 29 S RIW
 24" D. Fir, now stump, N65E 38.8 Shows good scar
 24" D. Fir, now stump, S71W 27.7 Shows good scar
 30" D Fir, Now down, N74W 19.1 Shows good scar

Stone approx. size at Cor.
 Set - Brass Cap. at Sec. Cor. Mkd:
County Surveyors T 29S RIW
 Office, 1969 S26 | S25
 S35 | S36

New BT's: 10" Cedar N18E 35.3 Scribed T29S RIW S25 CS BT
 14" Cedar N23W 27.2 Scribed T29S RIW S26 CS BT
 25" D. Fir S77W 46.0 Scribed T29S RIW S35 CS BT
 19" Cedar S88E 96.3 Scribed T29S RIW S36 CS BT 5-9-69

85

$\frac{1}{4}$ Corner to Sections 34 and 35
 Found: 18" W. Fir, now down and cut, N6E 19.8 Stump lying on face.
 48" D. Fir, now stump, S76W 50.8 Opened stump for scribing " $\frac{1}{4}$ "
 No trace of Cor. stone due to logging in area
 Set - Brass cap at $\frac{1}{4}$ Cor. Mkd:

County Surveyors T29S RIW
 Office, 1969 $\frac{1}{4}$
 S34/S35

New BT's: 10" Hemlock N 58W 9.4 Scribed $\frac{1}{4}$ S34 CS BT
 15" R. Fir N 59E 36.3 Scribed $\frac{1}{4}$ S35 CS BT 5-12-69

86

$\frac{1}{4}$ Corner to Sections 26 and 35
 Found - 16" Cedar, now 18", S12W 29.7 Scribe visible S35
 16" Fir, now stump, N 31 $\frac{3}{4}$ W 31.0 Scribe Visible "26" BT.
 Found stone approx. size, no marks, at Cor.
 Set - Brass cap at $\frac{1}{4}$ cor Mkd.:

County Surveyors T29S RIW
 Office, 1969 $\frac{1}{4}$
 S26
 S35

New Bearing Tree
 11" R Fir N 76 W 32.4 Scribed $\frac{1}{4}$ S26 CS BT
 S.W. BT OK & Tagged 5-12-69

87

Section Corner to Sections 15 and 14
 Found - 14" D Fir, now dead, S38W 15.2 Shows good scar
 14" D Fir, now down, N 52 E 5.3 Tree rotted
 Also - Stone 14x8x6 Stone firmly set at $\frac{1}{4}$ Cor. Mkd. $\frac{1}{4}$ on West face.
 Set - Brass cap at $\frac{1}{4}$ Cor. Mkd:

County Surveyors T29S RIW
 Office; 1969 $\frac{1}{4}$
 S15/ S14

NBT's 17" D. Fir S87 $\frac{1}{2}$ °W 29.2 Scribed $\frac{1}{4}$ CS BT
 18" D Fir N84°E 34.2 Scribed $\frac{1}{4}$ CS BT
 Scribing done with axe 6-3-69

88

Sections Corner to Sections 15, 14 22, 23
 Found- - 40" D. Fir, now 46", N57W 21.8 Shows good scar.
 48" D. Fir, now 51", N22E 29.0 Shows good scar
 40" D Fir now 47" S 54W 32.3 Shows good scar
 No trace of S. E. BT (10" Laurel)
 Also - Found Cor. stone Approx. 18x12x10 notches on E & S faces.
 Set - Brass Cap at Sec. Cor Mkd:

County Surveyors T 29S RIW
 Office: 1969 S15 | S14
 S22 | S23 6-3-69

JOHN M POWELL
 Frank Jones & W. Penley
 April & May, 1969
 C. S. File No. 54/82