

Douglas County Surveyor's Record of  
Government Corners Renewed

T 29 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell  
Frank Jones & W. Penley  
C. S. File No. 54/82

Umpqua Nat'l. Forest  
By J. A. Hoffbuhr  
C.S. File 55/158  
Map M 40 - 4

Section Corner to Sections 22, 23, 27, 26.  
Found - 40" D. Fir, now 45", N16E (Rec. N22E) 38.9 Shows good scar  
30" D. Fir, now S10E, (Rec. S5E) 49.5 Shows good scar  
24" D. Fir, now 27", S44W (Rec. S47W) 31.0. Shows good scar  
16" R. Fir, now 20", N43W (Rec. N37½W 38.9) Shows good scar  
Parts of scribe "S2" visible.  
Also - 22x10x6 stone firmly set at Sec. Cor. Mkd. 2 notches on the South&East sides  
Set - Brass cap at Sec. Cor. Mkd:

County Surveyors	T29S	RIW
Office, 1969	S22	S23
	S27	S26

All Bearing trees ok & tagged 6-10-69

93

¼ Corner to Section 23 & 26  
Found -- 20"D Fir, now down, N5W 16.5 Tree lying on face, scribing found  
"3" "B" No trace of SW BT or Cor. stone.  
Set - Brass cap at ¼ Cor Mkd:

County Surveyors	T29S	IW
Office:	¼	S23
		S26

New BT's 14" Hemlock S35E 34.9 Scribed 1/4 S26 CS BT  
7" Cedar N30W 33.3 Scribed ¼ S 23 CS BT 6-10-69

94

C.C Section Corner to Sections 7 & 18 Only T29-1E  
Found - 14" D. Fir, Now 18", N58E 42.2 Shows good scar.  
10" D. Fir, Now 14", S41E 27.1 Shows good scar  
Also- 20x8x6 stone firmly set at Sec. Cor Mkd. 4 notches on the South  
2 on the East CC on the East.  
Set - Brass cap at Sec. Cor. Mkd:

County Surveyors Office, 1969		
T29S		
R	S7	R
I S13	S18	I
W		E

New Bearing tree  
13" D. Fir N73W 17.7 Scribed T29S RIW S13 CC CS BT 6-6-69

95

¼ Corner to Section 13 Only  
Found - D. Fir, Now 27", S59W 20.0' Shows good scar.  
Laurel, Now 14", 15.6 Opened for scribe "¼"  
Also - Stone firmly set at ¼ Cor. Mkd. ¼ on West Face  
Set - Brass Cap. at ¼ Cor Mkd.

County Surveyors	T 29S
Office, 1969	R R
	I S13 I
	W ¼ E

New BT's  
5" Laurel N72W 32.6' Scribed ¼ S13 CS BT 6-6-69

96

Section Corner to Secs. 31 & 32, T29-1W. and Secs. 5 & 6, T30-1W.  
Found - 1½" Diam. Iron Bolt. Also found Orig. Stone with 5 notches  
on West Side, See Ren. #1.  
Replaced 1½" Bolt with 2" Diam Pipe with 2½" Brass Disk stamped:

T 29 S	R 1 W
S 31	S 32
S 6	S 5
T 30 S	R 1 W
R.L.S. 222	

1970 from which bears:

Orig. BT, A 30" Madrona, blowdown, N.88°E. 32.9 ft.  
Orig. BT, A 22" White Fir, blown down, S.38°E. 32.9 ft.  
12" White Fir, scribes visible, S.11°W. 18.9 ft.  
9" Black Oak BT., N.85°W. 9.6 ft.  
Orig. BT, A 24" Fir, now a stump, (logged off) N.61°W. 25.1 ft.

7/2/70

97

RE-RENEWED CORNER NO. # 112