

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 1 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97881

98

$\frac{1}{4}$  Corner to Section 31, T29-1W. and Sec. 6, T30-1W.  
Found - 1" Diam. Iron Rod, See Ren. #4.  
Replaced Rod with a 2" diam. Pipe with 2 $\frac{1}{2}$ " Brass Disk, stamped:  
T 29 S R 1 W from which bears:  
 $\frac{1}{4}$  S 31 12" Fir N.4°E. 17.4 ft., shows good scar.  
S 6 Orig. BT found 30" Stump S.88°E. 31.8 ft.  
T 30 S R 1 W 14" Alder S.66°E. 7.2 ft., scribes visible.  
R.L.S. 222 21" Sugar Pine S.15°W. 8.7 ft.  
1970 14" Fir N.75°W. 18.6 ft.  
Orig. BT found 30" Fir Stump N.70°W. 21.8 ft.

FD. BC. 9/93 PLESKE  
M 117-62

$\frac{1}{4}$  Corner to Sections 31 and 32. #133 99  
Found - 18"x12"x8" Basalt Stone in place with " $\frac{1}{4}$ " scribed on W. face.  
Orig. BT., A 14" Madrona, down on face & rotten, S.78°E. 11.2 ft.  
Replaced Stone with 2" Pipe with 2 $\frac{1}{2}$ " Brass Disk, stamped:  
T 29 S R 1 W from which bears:  
 $\frac{1}{4}$  S 31 / S 32 Scribed New BT's:  
R.L.S. 222 9" Fir scribed ( $\frac{1}{4}$  S32 BT) N.83 $\frac{1}{2}$ °E. 50.5 ft.  
1970 8 $\frac{1}{2}$ " Madrona scribed ( $\frac{1}{4}$  S31 BT) N.87°W. 40.2 ft.  
Buried Original Stone Monument alongside Pipe.

RE-RENEWED SEE CORNER NO.

By J. A. Hoffbahr  
Umpqua National Forest  
July 2, 1970  
C.S. File 55/159 - M 40 - 4

$\frac{1}{4}$  Corner to Sections 29 and 32. 100  
Set - 2" Pipe with 2 $\frac{1}{2}$ " Brass Disk, stamped:  
Set by Single Proportionate Measurement  
T 29 S R 1 W from which bears:  
 $\frac{1}{4}$  S 29 Scribed New BT's:  
S 32 6" Madrona scribed ( $\frac{1}{4}$  S29 BT) N.13 $\frac{1}{2}$ °E. 37.1 ft.  
R.L.S. 222 13" Madrona scribed ( $\frac{1}{4}$  S32 BT) S. 7 $\frac{1}{4}$ °E. 43.6 ft.  
1970

RE-RENEWED SEE CORNER NO. #134

$\frac{1}{4}$  Corner to Sec. 32, T29-1W. and Sec. 5, T30-1W. 101  
Found - 24"x20"x8" Ironstone with " $\frac{1}{4}$ " scribed on North Face  
Set - 2" Pipe with 2 $\frac{1}{2}$ " Brass Disk, stamped:  
T 29 S R 1 W from which bears:  
 $\frac{1}{4}$  S 32 Orig. BT: 30" Fir (blowdown) shows good scar, S34W. 25.7'  
S 5 Orig. BT: 30" Stump, lying on face, shows good scar,  
N. 57° W. 10.6 feet.  
T 30 S R 1 W Scribed New BT: 8" Fir scribed ( $\frac{1}{4}$  S32 BT) N.70 $\frac{1}{4}$ °E. 36.3'.  
R.L.S. 222 Scribed New BT: 6" W. Fir scribed ( $\frac{1}{4}$  S5 BT) S64W. 14.9 ft.  
1970 Left Original Stone Monument beside New Monument.

RE-RENEWED SEE CORNER NO. #144

Center  $\frac{1}{4}$  Corner Section 32. 102  
Set - 2 $\frac{1}{2}$ " Iron Pipe with 2 $\frac{1}{2}$ " Brass Disk, Stamped:  
T 29 S R 1 W from which bears:  
C  $\frac{1}{4}$  S 32 Scribed 17" Doug. Fir (C $\frac{1}{4}$  S32 BT) S13 $\frac{1}{2}$ °E. 27.9 ft.  
R.L.S. 222 Scribed 15" Doug. Fir (C $\frac{1}{4}$  S32 BT) S.86°W. 20.5 ft.  
1970

RE-RENEWED SEE CORNER NO. #135

$\frac{1}{4}$  Section Corner betwn. Sections 19 and 20. 103  
Found - 6"x8" Stone 10" above ground & firmly in place with " $\frac{1}{4}$ "  
scribed on west face.  
Set - 2" Iron Pipe with 2 $\frac{1}{2}$ " Brass Disk, stamped:  
T 29 S R 1 W from which bears:  
 $\frac{1}{4}$  S 19 | S 20 6" D. Fir scribed " $\frac{1}{4}$  S19 BT, bears N.20°W. 21.5'  
R.L.S. 222 7" D. Fir scribed " $\frac{1}{4}$  S20 BT", bears S.52°E. 9.7'  
1970

J. A. Hoffbahr  
For: Umpqua Nat'l. Forest  
Sept. 1970  
C.S. File 55/168 M 42 - 7

$\frac{1}{4}$  Section Corner btwn. Sections 20 and 29. 104  
Corner set by proportionate measurement.  
Set - 2" Iron Pipe with a 2 $\frac{1}{2}$ " Brass Disk, stamped:  
T 29 S R 1 W from which bears:  
 $\frac{1}{4}$  S 20 10" W. Fir scribed " $\frac{1}{4}$  S20 BT" bears N.4° E. 13.7 ft.  
S 29 6" Ash scribed " $\frac{1}{4}$  S29 BT" bears S.26°W. 14.5 ft.  
R.L.S. 222  
1970

RE-RENEWED SEE CORNER NO. 141

Sept. '70