

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 1 W. R.W.W.M.

ROKE-CHAPMAN CO. EUGENE, ORE. 3181

105

Center 1/4 Section Corner Section 20.

Set - 2" I. Pipe with 2 1/2" Brass Disk stamped:

T 29 S R 1 W from which bears:
C 1/4 S 20 4" Ponderosa Pine scribed "C 1/4 S20 BT" bears N.26 1/2°W. 9.9'
R.L.S. 222 5" Ponderosa Pine scribed "C 1/4 S20 BT" bears S.52°W. 4.3 f
1970

Sept. '70

1/4 Corner between Sections 20 and 21.

Set by proportionate measurement.

Set - 2" Iron Pipe with 2 1/2" Brass Disk stamped:

T 29 S R 1 W from which bears:
S 20 | S 21 12" W. Fir scribed "1/4 S21 BT", bears N.74°E. 22.2 ft.
R.L.S. 222 10" W. Fir scribed "1/4 S20 BT", bears N.63°W. 27.3 ft.
1970

Sept. '70

1/4 Section Corner btwn. Sections 16 and 21.

Set by proportionate measurement.

Set - 2" Iron Pipe with 2 1/2" Brass Disk stamped:

T 29 S R 1 W from which bears:
1/4 S 16 12" W. Fir scribed "1/4 S21 BT" bears S.40°W. 40.0 ft.
S 21 6" W. Fir scribed "1/4 S16 BT" bears N. 5° E. 34.0 ft.
R.L.S. 222
1970

Sept. '70

Center 1/4 Section Corner, Section 21.

Set - 2" Iron Pipe with 2 1/2" Brass Disk stamped:

T 29 S R 1 W from which bears:
C 1/4 S 21 12" Red Fir scribed "C 1/4 S21 BT" bears S. 1° E. 22.0 ft.
R.L.S. 222 10" W. Fir scribed "C 1/4 S21 BT" bears N. 3° W. 12.8 ft.
1970

108

CENTER 1/4 CORNER FOR SECTION 29.

Set - 2" Iron Pipe with 3" Bronze Disc Stamped:

T 29 S R 1 W
C 1/4 S29
RLS 934

From which bears:

1971
A 12" D. Fir scribed C1/4 S29 BT, S.29 1/2° W. 19.0 ft.
A 16" D. Fir scribed C1/4 S29 BT, N.26 3/4° E. 17.1 ft.

10/6/71

1/4 Section Corner btwn. Sections 28 and 29.

Set - 2" Iron Pipe with a 3" Bronze Disc. Stamped:

T 29 S R 1 W
1/4 S 29 | S 28
RLS 934 #129
1971

From which bears:

A 16" W. Fir scribed "1/4 S29 BT, N.76 1/4° W. 42.1 ft.
A 16" W. Fir scribed "1/4 S28 BT, N.36 1/4° E. 41.1 ft.

Note - No Evidence of Orig. Corner found, corner reestablished by proportionate measurement from section corners.

10/6/71

Center 1/4 Corner, Sec. 31

Set - Brass cap mkd. T295. R1W, WM C1/4 S31 1973 RS 430

BT's @ 12" Cedar scribed "C1/4 S31 BT" bears S.32°E., 16.8 ft.
16" D. Fir scribed "C1/4 S31 BT" bears N.81°W., 50.0 ft.
Brass disc mkd. RS 430 attached to both trees.

10/23/73

J. A. Hoffbuhr
For: Ump. National Forest
Sept. 3, 1970
C. S. File No. 55/168 Map M 42 - 7

Victor M. McLind
For: Umpqua Nat'l. Forest
October, 1971
Map File M 42 - 39

Bruce A. Shaner
for, Umpqua Nat'l
Forest
M 49 - 43
10/23/73

RE-RENEWED SEE CORNER NO. 140

RE-RENEWED SEE CORNER NO. #129

RE-RENEWED SEE CORNER NO. 145

MARCH 71

JAN. 1972