

Douglas County Surveyor's Record of  
Government Corners Renewed

T 29

T. S.

R 1

R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE., 21881

122

Section corner for Sec. 6; and Sec. 1, T29-2 only. (North boundary)  
Found - 1917 GLO brass cap on 3" I.P. solidly set in ground and properly stamped.

A 18" D. Fir stump with a healed blaze bears S.35°W., 9.24 ft.

A 14" D. Fir stump with a healed blaze bears S.66°E., 31.8 ft. (Rec. 30.36 ft.)

New BO's-A 3/4" Iron rod set in a 20" Cedar stump, 1" Alum cap stamped R.M. on iron rod, bears N.58°W., 11.2 ft.

A 3/4" Iron rod with 1" Alum. cap stamped R.M. set in a 19" D. Fir stump bears S.88°E., 39.0 ft.

Placed County BT signs on all 4 stumps.

Corner in a clearcut unit. No trees near by.

3/16/78

Dennis Gaylor  
U.S.F.S.

Deputy, Doug. Co.  
Surveyors Office  
March, 1978  
C.S. 59/46

123

Section corner for Secs. 27, 28, 33 and 34.

Found - Orig. corner stone found out of place. Stone has one notch on what was south edge, 3 notches on what was east edge, and "X" on top. Corner stone appears to have been knocked loose by falling rocks, as corner point falls in a steep talus slope. Corner stone slid approx. 5 ft. down slope. Stone is 15" x 8" x 4". (See also C.S. 54/82, copy attached to field notes, C.S. 59/46, of a NF corner infor.)

A 12" Yew bears S.59°E., 28.38 ft. Previously opened & now down. No scribing found. A U.S.F.S. location sign is attached & reads "1-23-41 H.H. located by compass & chaining". This sign apparently set by Howard Haskell, who did extensive corner search in this tsp. in the Spring of 1941. (U.S.F.S employee).

A 26" Alder bears N.19°W., 70.62 ft. Previously opened. No scribing visible.

A 10" Maple bears S.11°W., 45.1 ft. (Rec. S.8°W., 50.16 ft.) Previously opened & now down. No scribing. This BT is on a slope 70% above corner.

Set - Using the orig. Yew and Alder BTs for reference, at the corner point I SET a 2 1/2" Brass cap on a 1" I.P. stamped:

County Surveyors Office      T 29 S R 1 W  
1978                                      S 28 | S 27  
   S 33 | S 34

I bury the corner stone on East side of brass cap.

New BT's- A 8" Yew bears S.72°E., 26.7 ft. scribed "T29S R1W S34 CS BT" on a double blaze.

A 24" Sugar Pine bears N.40°E., 117.5 ft. scribed "T29S R1W S27 CS BT" on a double blaze. This BT is across Francis Creek.

A boulder, 35 ft. x 35 ft. x 30 ft. high on East edge of Francis Crk. bears N.56°E., 67.0 ft.

A 8" D. Fir bears N.87°W., 23.4 ft. scribed "T29S R1W S28 CS BT" on a double blaze.

A 15" Yew bears S.41°W., 68.6 ft. scribed "T29S R1W S33 CS BT" on a double blaze.

Also Found -

A location sign (U.S.F.S.) nailed to the new BT (yew) to the SE This sign reads "MM 2-5-48" "0 ch \_\_\_ of sec. cor".

Original BT to the NE is gone.

I discount the Maple BT as it does not fit record bearing and distance. It may have been originally slope chained. See copy of "not found" notes for more information on this corner.

I placed County BT signs on the three original BT's and the four new BT's.

Center line Francis Creek to the North is 64 ft. (rec. is 66 ft.)

Center line Francis Creek to the East is 48 ft. (Rec. is 49.5 ft.)

Top of bluff to West is 67 ft. horiz. & 99 ft. slope dist. (Rec. is 99 ft.)

3/22/78

Dennis Gaylor, U.S.F.S.  
Deputy, Douglas County Surveyors Office  
Witness - Roland Simshauser  
March 22, 1978  
C.S. 59/46