

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 29      T. S.      R 1      R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

**128**

Wayne Rogers  
For: U.S. forest  
Service  
Dec. 8, 1978  
C.S. 58/185  
M 70 - 45

1/4 Corner for Secs. 27 and 22  
Found - 1910 Bedrock with chisled + and 1/4, on the east side of the S. Umpqua River.  
16" Oak (now dead) S.54 1/2°E., 157 lks. (still exists and shows good scars)  
16" Fir (now 24") N.1°W., 117 lks. (good tree)  
A 1969 BT, a 11" D. Fir now 14", S.69°E., 118.5 ft. Good tree.  
Ren. #43  
Set - At the position of the + chisled in bed rock I star drilled a hole into the rock and firmly grouted a 3" brass disk (with a 4" twisted and fluted stem) into place. In the grouting process it was necessary to completely cover up the chisled 1/4 sign.  
Set - A steel fence post above bedrock and high water easterly about 30 feet with signs 54-4 and 54-9 attached by wire.  
Brass disk is stamped T29S R1W 1/4 S22 S27 1978 PLS 1004.  
12/8/78

**129**

Wayne Rogers  
For: U. S. Forest  
Service  
Dec. 1978  
M 70 - 44 A & B

1/4 Corner for Secs. 29 and 28.  
Found - 1971 Brass cap per M 42 - 39. Ren. #110  
20" Fir stump, N.76°W., 42.1 ft.  
20" Fir stump (Rec. N.36°E.) N.72°E., 41.1 ft.  
New BT's-6" Fir, S.49°E., 18.56 ft.  
6" Fir, S.45°W., 16.77 ft.

**130**

Center 1/4 Corner for Secs. 28  
Set - 2" x 30" I.P. and brass cap stamped: T29S R1W C 1/4 S28 1978 PLS 1004.  
BT's - 10" Chinquapin, S.68°E., 5.27 ft.  
10" Yew wood, N.44°E., 18.70 ft.  
7" Chinquapin, S.9°E., 19.83 ft.  
9" Chinquapin, S.32°W., 27.62 ft.

12/78

**131**

Wayne Rogers  
For: U.S. Forest  
Service  
Dec. 1978  
M 70 - 45

Center 1/4 Corner for Sec. 27  
Set - 2" x 30" I.P. and 3" Brass cap stamped: T29S R1W C 1/4 S27 1978 PLS 1004.  
BT's- 6" Fir, S.19°W., 25.99 ft.  
20" Fir, S.58°E., 7.98 ft.  
10" Chinquapin, N.42°E., 29.53 ft.  
28" Fir, N.43°W., 44.12 ft.

12/78

**132**

FD. BC. 9/93  
PIESKE M117-62

Township corner, Sec. 31, and Sec. 36 of T29-2; Sec. 1 of T30-2 and Sec. 6 of T30-1  
Found - 1" Iron pipe, 10" above the ground with a 2 1/2" brass cap mkd. T29S R2W R1W S36 S31 S6 S1 T30S 1917"  
Ren. #6

From which:  
A 22" Oak bears N.70°W., 37.0 ft.  
An 18" Oak stob bears N.8°E., 47.5 ft.  
An 18" Oak stump bears S.89°E., 118.8 ft.  
An 18" D. Fir bears N.44°W., 26.8 ft.  
A 16" D. Fir bears N.73°E., 17.5 ft.  
An 18" D. Fir bears S.9°E., 13.0 ft.  
A 12" D. Fir bears S.41°W., 33.0 ft.  
New BT - 10" D. Fir bears S.25°E., 38.4 ft., I marked "T30S R1W S6 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

July 1979

**133**

Leonard Herzstein,  
U.S.F.S, Deputy, Doug.  
Co. Surveyors Office  
J. Landrum; T. Wolford  
April 28, 1981  
C.S. 61/19

1/4 Corner for Sections 31 and 32  
Found - 2" I.P. with brass cap properly marked, firmly set, projecting 6" above ground. Ren. #99 with orig. basalt stone alongside. Orig. BT, a roothole, S.78°E., 11.2 ft. with a rotten madrone of indeterminate size alongside with no marks visible.  
13" D. fir, N.83 1/2°E., 50.5 ft. with healed double blaze. Ren. #99  
9" madrone snag, N.87°W., 40.0 ft. with S.M. "1/4 S31 BT" visible on partly healed double blaze. (Rec. 40.2 ft.) Ren. #99  
New BT's- 6" D. fir, S.16°W., 39.9 ft. marked "1/4 S31 CS BT" on double blaze