

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 29

T. S.

R 1

R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 97401

134

1/4 Corner for Sections 29 and 32

Found - 2" I.P. with properly marked brass cap, firmly set, projecting 6" above ground. Ren. #100  
6" madrone snag, N.13°E., 37.1 ft. with S.M. "1/4 S29 BT" visible on partly healed double blaze. Ren. #100  
14" Madrone snag, S.7 1/2°E., 43.6 ft. with S.M. "1/4 S32 BT" visible on partly healed double snag.  
New BT's - 9" W. fir, N.67°E., 23.4 ft. marked "1/4 S29 CS BT" on double blaze  
6" D. fir, S.21°E., 68.3 ft. mkd. "1/4 S32 CS BT" on double blaze.  
- - - - - 4/29/81

Leonard Herzstein  
U.S.F.S.; Deputy  
Doug. Co. Surveyors  
Office  
Witnesses: J.  
Landrum; T.  
Wolford  
April 1981  
C.S. 61/19

135

*FD. BC. 9/93 PIESKE M 117-62*

Center 1/4 Section 32  
Found - 2" I.P. with brass cap, properly mkd., firmly set, projecting 6" above ground. Ren. #102  
22" D. fir, S.13 1/2°E., 27.9 ft. with fragmentary S.M visible on partly healed double blaze.  
16" D. fir stump, S.86°W., 20.5 ft. with frag. S.M. visible on partly healed double blaze.  
New BT - 8" I. cedar, N.35°E., 31.4 ft. marked "C 1/4 S32 CS BT" on double blaze.  
Corner is 150 ft. west of USFS Rd. #294 just up the hill from Jct. with road #294-K  
- - - - - 4/27/81

Leonard Herzstein  
U.S.F.S.; Deputy  
Doug. Co. Surveyors  
Office  
Witness: Tom  
Wolford  
May 12, 1981  
C.S. 61 / 24

136

CW 1/16 Corner in Sec. 21.  
Found - 2" iron pipe set by J.A. Hoffbuhr, OLS #222, in 1970, firmly set, projecting 6" above ground, with Brass Cap marked: T.29S RLW.CW 1/16 S21 RLS 222 1970 M 42 - 7  
BT's marked by Hoffbuhr in 1970: A roothole, N42°E, 15.0', with 9" Chinquapin log alongside with scribe marks "CW 1/16 S 21 BT" visible on partly healed double blaze.  
A 20" I. Cedar, S50°W, 11.7', with healed double blaze.  
New Accessories -  
I mark new BT: A 12" S. Pine, N34°E, 22.1', scribed "CW 1/16 S21 CS BT" on double blaze.  
- - - - -

137

N 1/16 between Sec's. 28 & 29.  
Found - 2" I.P. set by Victor McLind, RLS #934, in 1971, firmly set, projecting 6" above ground, with Brass Cap marked: T29S RLW N 1/16 S29 S28 RLS 934 1971. M 42 - 39  
A 10" half-dead D. Fir, N42 1/2°E, 6.8-ft. with S.M. "N 1/16 S28 BT" visible on partly healed double blaze.  
A 14" D. Fir, S19°E, 15.5-ft., with fragmentary S.M. visible on partly healed double blaze.  
A 24" I. Cedar snag, N75 1/2°W (REC. S89°W), 35.5-ft., with S.M. "N 1/16 S29 BT" visible on partly healed double blaze.  
Set - I add 3' mound of stone, making McLind's B.C. now flush.  
New Accessories -  
A 17" D. Fir, N27 1/2°W, 14.4-ft., scribed "N 1/16 S29 CS BT" on double blaze.  
Note - Corner is 100-ft. South of Francis Creek on steep North slope.  
- - - - -

Leonard Herzstein  
U.S.F.S.; Deputy  
Doug. Co. Surveyors  
Office  
Witnesses: Jim  
Lanorum and  
Tom Wolford.  
May 19, 1981  
C.S. 61 / 24

138

SW 1/16 Corner for Sec. 29.  
Found - 2" I.P. set by Victor McLind, in 1971, firmly set, projecting 12" above ground, with Brass Cap marked T29S RLW SW 1/16 S29 RLS 934 1971. M 42 - 39  
A 24" D. Fir stump, N68 1/2°E, 3.4-ft., with Scribe Mark "SW 1/16 S29 BT" visible on partly healed double blaze.  
An 8" W. Fir, N.40°W., 11.0-ft., with healed double blaze.  
New BT - A 5" D. Fir, S.11°W., 11.6-ft., marked "SW 1/16 S29 CS BT" on double blaze.  
- - - - -