

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 29 S T. S. R 1 W R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

139

Sec. Cor. common to Sec's. 16, 17, 20, & 21.
 Found - 2" I.P. set by Douglas County Surveyors Office in 1969,
 firmly set, projecting 4" above ground, with B.C.
 properly marked. Ren. #35
 Orig. BT's: A 50" D. Fir snag, N44°E, 49.5-ft., with healed
 double blaze.
 A 30" D. Fir stump, S32°E, 44.2-ft., with scribe
 mark "S21" visible on previously opened blaze.
 A 16" D. Fir snag, N29°W, 32.3-ft., with healed
 double blaze.
 BT's marked by Doug. Co. Surveyors Office in 1969:
 An 8" White Fir (REC. R. Fir), S31°E, 33.8-ft.
 with healed double blaze.
 A 14" Sugar Pine snag (REC. Y. Pine), S12°W,
 44.3-ft., with scribe mark "T29S R1W S20 CS BT" visible
 on partly healed blaze.
 New Accessories - I mark new BT's:
 A 14" W. Fir, N45°E, 29.7-ft., scribed "T29S R1W S16 CS BT"
 on double blaze.
 An 8" D. Fir, S5°W, 40.1-ft., scribed "T29S R1W S20 CS BT"
 on double blaze.
 An 11" I. Cedar, N50°W, 48.9-ft., scribed "T29S R1W S17
 CS BT on double blaze.

140

1/4 Cor. common to Sec's. 20 & 21.
 Found - 2" I.P. firmly set, projecting 4" above ground, set by
 J.A. Hoffbuhr, OLS# 222, in 1970, with B.C. properly marked.
 BT's marked by Hoffbuhr in 1970: Ren. #106
 An 18" D. Fir (REC. W. Fir), N74°E, 22.2-ft., with healed
 double blaze.
 A 10" W. Fir snag, N63°W, 27.3-ft., with scribe marks
 "1/4 S20 BT" visible on partly healed double blaze.
 New Accessories - I mark new BT:
 A 5" W. Fir, S70°W, 43.2-ft., scribed "1/4 S20 CS BT" on
 double blaze.

141

1/4 Cor. common to Sec's. 20 & 29.
 Found - 2" dia I.P., firmly set, projecting 4" above ground, set by
 J.A. Hoffbuhr, RLS# 222, in 1970, with B.C. properly marked.
 BT's marked by Hoffbuhr in 1970: Ren. #104
 A 14" D. Fir, N4°E, 13.7-ft. (REC. W. Fir), with healed
 double blaze.
 A 10" Ash stump, S26°W, 14.5-ft., with scribe marks "1/4
 S29 BT" visible on partly healed double blaze.
 New Accessories - I marked new BT:
 A 13" D. Fir, S40°E, 26.4-ft., scribed "1/4 S29 CS BT" on
 double blaze.
 * NOTE - Corner is about 40-ft. North of private road.

142

Sec. cor. common to Sec.'s 20, 21, 28, & 29. Ren. # 56.
 Found - 1" I.P. firmly set, projecting 12" above a 3-ft. diam.
 mound of stone, with B.C. marked Comty Surveyors Office
 1969 T29S R1W S20 S21 S29 S28. Ren. # 56.
 Orig. BT's: 28" D. Fir stump bears N.50°E., 151.4-ft., with no marks visible.
 42" D. Fir stump bears S.75°E., 112.2-ft., with healed lower
 blaze.
 27" I. Cedar bears S.50°W, 47.5-ft., with healed blaze.
 32" D. Fir stump bears N.81°W., 53.5-ft., with healed blaze.
 1969 BT's: 10" D. Fir bears N.52 1/2°E., 23.7-ft. (Rec. 23.2-ft), with
 healed double blaze.
 21" D. Fir bears S.55°E., 23.4-ft., with healed double blaze.
 Set - Guard post 5-ft. North of B.C. with USFS signs #S4-2, and
 #S4-4 attached.
 New BT: 6" D. Fir bears N.59°W., 21.6-ft., scribed T29S R1W
 S20 CS BT on double blaze.

Leonard Herzstein U. S. F. S. ;
 Deputy Douglas County Surveyors Office
 Witnesses: Jim Landrum & Tom Wolford
 May 1981 C.S. 61 / 24

Leonard Herzstein, U.S.F.S.
 Deputy, Cou. Surveyors Office
 Jim Landrum
 Tom Wolford
 May 5, 1981
 C.S. 61 / 24