

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 29

T. S.

R 1

R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

151

C O N T - - -

Doug. Co. Surveyors  
Office  
Randall Smith and  
Stephen Flause  
June 13, 1985  
C.S. 62/28

Found - 1922 BT, a fir, 9" dia. now a 9" dia. 26" tall fir stump,  
bears N.30°W., 10.6 ft. Well healed single blaze.

Monument position is accepted as found.

New Accessories:

A boat spike stamped B0 1 set in a 30" dia. 16" tall fir stump,  
and bearing N.86 3/4°E., 27.0 ft. dist.

A boat spike stamped B 0 2 set in a 31" dia. 18" tall fir stump,  
and bearing N.42 1/4°W., 55.4 ft. dist.

From the end of USFS Rd. #2813-607 monument bears east approx 40 ft.  
dist. and slightly lower than road. Corner is in clear cut. No trees  
available for scribing.

6/13/85

1/4 Corner for Sections 3 and 4

152

Doug. Co. Surveyors  
Office  
Randall Smith and  
Stephen Flause  
June 19, 1985  
C.S. 62/28

Found - 1922 GLO Brass Cap, on an I.P. protruding 10 ins. above  
ground, properly marked.

BT's - 7" Hemlock, now 10" in diam Pacific Yew with a single,  
partially healed blaze, scribing visible "1/4 S3 BT", bears  
S.19°E., 27.7 ft. (Original)

10" Hemlock, now a stump hole, bears N.71°W., 11.2 ft. No  
evidence of tree found. (Original)

New BT's-6" diam. double trunked dogwood, double blazed and scribed on  
east trunk "1/4 S4 CS BT" bears S.47°W., 10.4 ft. to root crown.

7" diam. W. Fir double blazed and scribed "1/4 S3 CS BT" bears  
N.13 1/4°E., 36.6 ft.

22" diam. W. Fir double blazed and scribed "1/4 S3 CS BT" bears  
N.84 1/2°E., 37.6 ft.

153

Loyd R. Moffit  
L.S. #944  
For: U.S. Forest Serv.  
Dec. 1985  
C.S. 63/30

Section Corner for Sections 35 and 36 only. (South)

Found - 3/4" Iron pipe with 2 1/2" alum. cap exposed 14". Corner was  
re-monumented in 1967 by R.E. 4287. Ren. #19

New BT - Marked a 10" cedar BT which bears N.50°W., 71.9 ft. from the  
corner, scribed T29S R1W S35 BT.

154

Ronald Geisler  
L.S. 1988  
Champion Internat'l  
C.S. 63/34  
July 18, 1986

North 1/4 Corner for Sec. 2 only of T.30-1

Found - 2 1/2" alum. cap on a 1" I.P. extends 14" above ground. Ren. #7

9" W. fir bears S.47°W., 14.6 ft. Closed face. (1967)

19" Fir (stump) bears S.20°E., 42.2 ft. Closed face. (1967).

New BT - 6" W. fir bears S.30°E., 18.06 ft. and scribed 1/4 S2 BT. (1986).

155

Maurice E. Farr  
U.S.F.S.  
Leonard Herzstein  
Randy Lopez,  
Witnesses.  
March 26, 1987  
C.S. 62/44

South 1/4 Corner for Section 35.

Found - A 7/8" outside dia. I.P. firmly set projecting 10" above  
the ground, with a 2 1/2" Alum. cap mkd. "U.S.P.C. Prop. Cor.  
S 1/4 T.29S. R.1W RE 4287 1967 Do Not Disturb". Ren. #17

Orig. BT, a 50" D. Fir rootcrown, N.62°E., 25.5 ft. with scribes  
"BT" visible on a decayed blaze.

Orig. BT, a roothole, N.60°W., 32.5 ft. with a 45" D. fir stump  
alongside with fragmentary scribes visible on a previously  
opened blaze.

An 8" D. fir stump, N.30°E., 20.3 ft. (Rec. N.32°E., 19.9 ft.)  
with log alongside with scribes "S 1/4 S35 BT" visible on a  
single blaze.

Set - I set a 6 ft. alum. post, driven 2 ft. in the ground as a guard  
post, S.80°E., 1.2 ft. with F.S. sign #54-4 attached.

New BTs - A 6" hemlock, N.12 3/4°E., 24.0 ft., scribed "1/4 S35 BT" on a  
single blaze.

An 8" W. fir, N.67 3/4°W., 37.1 ft. scribed "1/4 S35 BT" on a  
double blaze.

A 3/4" brass washer stamped "LS 1181" is nailed flush to the base of blaze  
on both new bearing trees.

Note: Based on plat M72-24, I found the magnetic declination to be 18°E.

The corner is in a low area with running water. An 18" culvert bears  
S.14°E., 56 ft. and a 12 ft. wide rocked road bears South, 60 ft. To reach  
the corner from F.Rd. No. 28, "South Umpqua Road", turn right (south) onto  
F. Rd. No. 2980, "Zinc Creek Road", drive 4 miles and turn right onto Rd. No.  
2980-700. Drive about 2 1/4 mi. and turn left onto rocked road and drive 0.1  
miles to corner.