

Douglas County Surveyor's Record of
Government Corners Renewed

T 29 S. T. S. R 2 W R. W. W. M.

KOBE-CHAPMAN CO., EUGENE, ORE. 21881

John H. Markham, Jr.
December 12, 1961
C. S. File No. 51/221

N. E. Corner Section 6, as det. by O.B.T. 1
26" Hemlock snag bears S.59°E. 18.5 ft., found scribe, O.B.T.
At Corner Point Set 1" x 30" I. Pipe from which: 83
1½" Fir bears N.70°E. 22.6 fto, not mkd.
5" Laurel bears S.56°E. 28.0 ft. mkd: S6 R2W BT.
3" Fir bears S.41°E. 19.0 ft. mkd: S5 XX BT.
3" Fir bears S.1°W. 45.5 ft. mkd: S6 BT.
Skid Road bears South 35.0 ft. Corner lie in old logging-a real brush pile.

S. W. Corner Sec. 31, & S.E. Corner Sec. 36, T28-3W, as det. by O.B.T.'s. 2
40" Fir N.80°E. 31.5 ft., found scribe O.B.T.
52" Fir Snag N.50°W. 21.1 ft., fd. scribe O.B.T. 85
At Corner Point fd. Stone & Set 1½" x 36" Truck Axle - flange up, from which:
40" Cedar bears S.83°E. 11.9 ft. mkd: S 6 B.T.
7" La. bears N.25°E. 25.9 ft. mkd: S31 T28S R2W B.T.
6" Fir bears N:59°W. 21.7 ft. mkd: S36 B:T.
Centerline Road bears South 42.0 feet.

North Boundary T29-2W. South ¼ Corner Section 31, only, as det. by O.B.T. 3
10" dead Cedar Snag bears N. 6°E. 13.2 ft., fd. scribe, O.B.T.
22" Cedar Stump logged bears N.71°W. 12.5 ft., fd. scribe O.B.T.,
notes call for N.17°W. 82
At Corner Point Found Stone & Set 1½" x 36" Axle with flange up from which:
2" Fir bears S. 8°W. 22.2 ft. Mkd: X X X.
1½" Fir bears S.55°E. 10.2 ft., not marked.
Centerline Road bears West 36.0 ft. Corner lies in old logging.

N. W. Corner Section 4, as det. by Old BT's. 4
12" Hemlock Snag live, bears S.30°E. 27.0 ft. O.B.T.
At Cor. Pt. Set - 2" x 30" I. P. from which:
12" Hemlock bears N.66°E. 79.7 ft. mkd: S32X BT.
9" Hemlock bears N.45°E. 78.5 ft. mkd: S32 XX BT.
East End of a 16" Medal Culvert thru dam bears N.59°E. 51.0 ft.
Road bears West 120.0 ft.
Corner lies on S. W. edge of small lake.

South ¼ Corner Section 32, T28S R2W, as det. by Old BT's: 5
40" Hemlock stump, logged, bears N.11°E. 44.8 ft., fd. scribe O.B.T.
40" Hemlock Stump, logged, bears N.13°W. 18.5 ft, fd. scribe O.B.T.
At Cor. Pt. Set 1½" x 30" Axle with flange up, from which:
9" Hemlock bears S.47°W. 56.5 ft. mkd: ¼ S32 BT.
14" Hemlock bears S.13°W. 61.0 ft. mkd: ¼ S32 BT.
Road bears East 130.0 ft. distance.

N. E. Corner of Sec. 24, T29-3W. Determined by Old BT's. 6
40" Fir Snag bears S.72½°W. 124.0 ft. dist., O.B.T. Found Scribe.
40" Fir N.16°W. 170.0 ft. O.B.T.
West ¼ Corner Sec. 19, T29-2W (Brass cap) bears North 13.2 ft. dist.
At Corner Point found stone & Set 1½" x 24" Iron Pipe from which:
9" Fir bears N.42°W. 19.4 ft. dist. mkd; S13 B.T.
8" Fir bears S.67°W. 19.0 ft. dist. mkd: S24 B.T.
10" Fir bears S.31°W. 18.0 ft. dist. mkd. S24 B.T.
Creek bears North 14.0 ft. distance.

East ¼ Section Corner to Section 24, T29-3W. Determined by Old BT's. 7
30" Fir bears N.69°W. 18.0 ft. Found Scribe.
26" Fir bears S.33°W. 33.3 ft. O. B. T.
At Corner Point found Stone & 1½" x 24" Iron Pipe, from which:
26" Fir bears S.64°E. 41.0 ft. dist. mkd: ¼ S24 BT.
12" Fir bears N.82°E. 30.5 ft. dist. mkd: ¼ S24 BT.
Section Cor. 19 - 30, T29S R2W (Brass Cap) bears North 16.0 ft.
Main Top and Road bears North 585.0 feet distance.

7/73 - Fr. O.K. VRT. C.S. 56/34 - RESET STONE

John H. Markham, Jr.

John H. Markham, Jr.
For Stomar Lumber Co.
Wit: R. G. Boyd
Oct. 29, 1957
C.S. File No. 42/315