

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

8

Corner to Sections 7 & 18 only, T29S-R2W.
Found - Brass Cap at Cor. & Both BT's. - Orig. 12", now 20" Cedar
N.21°E. 28.4 ft., not N.18°E., shows good scribing
and scar. Orig. S.E. BT., now down.
New BT: 12" Yewood bears S.46°E. 28.0 ft. scribed S18 T29SR2W CSBT.

9

East $\frac{1}{4}$ Corner to Section 12, T29-3W.
Found - Stone & Both BT's, as recorded. Orig. 20", now 32" Fir
West 10.5 ft., shows good scars. Orig. SW. BT., now snag.
Note - Dist. & Bearing from $\frac{7}{8}$ " Brass Cap checks O.K. $\frac{7}{8}$ "
New BT: 22" Cedar bears S.80°W. 20.0 ft. scribed $\frac{1}{4}$ S12 CS BT.

10

Corner to Sections 1 and 12, T29-3W.
Found - Stone at Cor. & Both BT's, as recorded.
SW. BT., now stump. NW. BT. shows scribing.
Set - Brass Cap alongside Cor. Stone & Mkd:

S 1	T29S
R3W	S12
	R2W

County Surveyor's Office, 1962
New BT's: 20" Cedar bears S.81°W. 38.3 ft. scribed S12 T29S R3WCSBT.
7" Cedar bears N.22°W. 29.2 ft. scribed S1 T29SR3W CS BT.

11

Corner to Sections 12 and 13, T29-3W.
Found - Stone at Cor. Both BT's., now snags, all as recorded,
show scribing.
Brass Cap set for West $\frac{1}{4}$ S18 R2W as recorded.
New BT's: 7" R.Fir bears N.74°W. 29.3 ft. scribed S12 CS BT.
7" R.Fir bears S.58 $\frac{1}{2}$ °W. 42.3 ft. scribed S13 CS BT.

12

West $\frac{1}{4}$ Corner to Section 18, T29-2W.
Found - Brass Cap at Cor. & Both BT's, as recorded.
N.E. BT., now snag, shows scribing.
S.E. BT., now down.
New BT: 20" Fir bears S.24°E. 20.2 ft. scribed $\frac{1}{4}$ S18 CS BT.
No other BT's. scribed.

13

Corner to Sections 18 and 19 only.
Found - Orig. 42", now 48" Fir N.1°45'E. 167.0 ft., not 173.6 ft.,
shows good bark scribing & old scar.
Both Orig. BT's. for East $\frac{1}{4}$ S13, R3W. We do not find
withier corner stone.
Set - Brass Cap at Cor. Mkd: County Surveyor's

R3W	S18	R2W
	S19	T29S

Office, 1962
Note - Corners are on steep north slope.
New BT's: 12" R.Fir bears S.12 $\frac{1}{2}$ °E. 21.4 ft. scribed S19 T29S R2WCSBT.
8" R.Fir bears N.87°E. 22.6 ft. scribed S18 CS BT.

14

East $\frac{1}{4}$ Corner to Section 13, T29-3W.
Found - Both Orig. BT's., check O.K. for bearings & distances,
show scribing & scars.
Set - 2" x 2" x 4.0 ft. Stake at Cor. 10.5 ft. South of
Brass Cap. (above)
New BT's: 16" R.Fir bears S.53°W. ~~8.8~~ 8.8 ft. scribed $\frac{1}{4}$ S13CSBT.
18" R.Fir bears N.41°W. 14.5 ft. scribed $\frac{1}{4}$ S13 CS BT.

15

West $\frac{1}{4}$ Corner to Section 30 only.
Found - Stone at corner & both BT's, as recorded.
S. E. BT., now snag, shows scribing.
Set - Brass Cap at Corner stone & Mkd:

R3W	S30	West
		$\frac{1}{4}$ T29SR2W

County Surveyor's Office, 1962
New BT: 22" R.Fir bears S.36°E. 24.5 ft. scribed $\frac{1}{4}$ S30 CS BT.

James W. Byron, Deputy County Surveyor
Mike Darby and Bill Stoffel
November & December 1962
C. S. File No. 52/126