

Douglas County Surveyor's Record of
Government Corners Renewed

T. 29 S. T. S. R. 2 W. R.W.W.M.

NOKE-CHAPMAN CO., EUGENE, ORE. 21881

37

1/4 Corner to Section 33 only, T29-2W.
Found - GLO Brass Cap properly marked in 1917.
12", now 15" Cedar, N.20 1/2°E. 69.3 ft., scribe visible.
28" D.Fir, now stump, N.56°W. 48.2 ft., shows good scar.
New BT: 10" Hemlock N.49°W. 34.5 ft. mkd: 1/4 S33 CS BT.
This corner lies 42.2 ft. west of 1/4 Cor. Sec. 4, T30-2W, see below.

38

1/4 Corner to Section 4 only, T30-2W.
Found - No trace of Stone at corner.
32" D.Fir, now stump, S.20°E. 24.4 ft., opened for scribe.
14", now 26" Cedar, S.20°W. 31.9 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T29S R2W 1/4 S 4
T30S R2W 1/4 S 4
New BT: 6" Hemlock S.2°E. 19.0 ft. mkd: 1/4 S4 CS BT.
This corner lies 42.2 ft. east of 1/4 Sec. 33, T29-2W, see above.

39

Section Corner to Sections 32 & 33, T29-2W.
Found - Stone, approx. size, 4 notches E., 2 notches W.
36", now 39" D.Fir, N.21°E. 33.7 ft., shows good scar.
15", now 19" Fir, N.64 3/4°W. 37.0 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T29S R2W 1/4 S32 | S33
T30S R2W 1/4 S 4
New BT: 14" Cedar S.20°E. 28.6 ft. mkd: T30S R2W S5 CS BT.
This corner lies 62.7 ft. west of Sec. Cor. Secs. 5 & 4, T30-2W, below.

40

Section Corner to Sections 5 and 4, T30-2W.
Found - No trace of Stone at section corner.
30", now 38" D.Fir, S.29°E. 4.0 ft., shows good scar.
12" Cedar, now stob, S.22 1/2°W. 13.9 ft., opened for scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T29S R2W 1/4 S 5 | S 4
T30S R2W 1/4 S 5 | S 4
New BT's: 14" Hemlock S.64°W. 39.7 ft. mkd: T30S R2W S5 CS BT.
8" Fir N. 34° W. 10.0 ft. mkd: T29S R2W S33 CS BT.
This corner lies 62.7 ft. east of Sections 32 & 33, see above.

11/21/68

41

Section Corner to Sections 34 & 35, T29-2W.
Found - Stone at sec. cor. mkd: 2 notches on E. & 4 on W.
40", now 45" D.Fir, N.12 1/2°W. 31.0 ft., shows good scar.
24" Fir, now stob, N.32 1/2°E. 37.6 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T29S R2W S 34 | S 35
T30S R2W S 3
New BT's: 16" Hemlock N. 8° E. 26.6 ft. mkd: T29S R2W S35 CS BT.
14" Hemlock S.51 1/2°W. 33.9 ft. mkd: T30S R2W S3 CS BT.

42

Section Corner to Sections 3 and 2, T30-2W.
Found - Stone at Cor. Mkd; + on top, record dist. 33.7 E. of Sec. Cor. 34 & 35, T29-2W.
10", now 26" R.Fir, S.66 1/2°W. 15.2 ft., shows good scar.
6" Fir, now down & laying on face, S.32 3/4°E. 15.2 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T29S R2W S 35
T30S R2W S 3 | S 2
New BT's: 7" D.Fir S.71°E. 26.5 ft. mkd: T30S R2W S2 CS BT.
12" Hemlock N.14°E. 13.6 ft. mkd: T29S R2WS35 CS BT.

43

1/4 Corner to Section 3, north side, T30-2W.
Found - Stone at corner approx. size, mkd. 1/4 on N. side.
18", now 30" R.Fir, S.1°E. (Rec.S1W) 31.7 ft., shows good scar.
14", now 20" R.Fir, S.25°W. 29.7 ft., shows good scar.
Record Distance of 26.4 ft. E. of Sec. 34, T29-2.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1968 T29S R2W 1/4 S 3
T30S R2W 1/4 S 3
All Bearing Trees O. K. and Tagged.

11/26/68

John M. Powell
Jack Heritage & W. Penley
November, 1968
C. S. File No. 54/73