

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

Powell &  
Crew  
C.S. 54/73

1/4 Corner to Section 34 only, T29-2W. 44  
Found - GLO Brass Cap properly marked in 1917.  
14", now 26" D. Fir, N. 18° E. 34.3 ft., no scar visible.  
18", now 26" R. Fir, N. 72 1/2° W. 19.8 ft., shows scar.  
Reblazed & Rescribed: 26" D. Fir, N. 18° E. 34.3 ft. mkd: "1/4" S34 CS BT.  
11/26/68

Powell &  
Crew  
C.S. 54/82

1/4 Corner to Section 25 Only R. 2W T.29 45  
Found - Brass Cap in excellent condition & properly marked, 1917 & 1 BT. *BY G.L.O.*  
24" D Fir now 29" S 52° W 26.4 Ft. Shows good scar & is good for bearing  
& dist.  
8" Chinquapin now 9" N 28 1/2° W. 35.0 ft. Has rotten face & shows no trace  
of scribing & is good for bearing & Dist.

Note: Place yellow tags on both BT's. Found Brass Cap from both BT's Mkd.  
New BT's 6" D. Fir N 77° W 16.4 Ft. Scribed 1/4 S 25 CsBt.  
Note: This 1/4 S 25 only lies north 33.7 Ft. from 1/4 S 30 only range line of  
R1, 2W T29 S Plus these corners lie on steep West Side. 4-24-69

1/4 Corner to Section 30 only R. 1 W. 45 A  
Found - 2 BT's in excellent condition. No trace of basalt stone.  
10" S Pine now 16" N 45° E 19.8 Ft. Shows good scar & is good for  
bearing & dist.  
6" R Fir now 10" S 42° E 25.5 Ft. Shows good scar.  
Note: Place yellow tags on both trees.  
Set - Brass cap from bt's mkd:

County Surveyors	T 29S	
Office, 1969	R	R
	2	1/4 I
	W	S30 W

Note: This 1/4 S 30 only lies S. 33.7 Ft. from 1/4 S 25 only on range  
line of R1 2W of T 29 S. Corners lie on steep West slope.  
4-24-69

Section Corner 25 and 36 T 29 2W Only 46  
Found - 18x10x7 basalt coner stone properly marked & set at Sec. Cor.  
point.  
10" D Fir now 16" S 5 1/2° W. 13.9 Ft. Shows excellent scar.  
6" D Fir now 10" N. 17° W. 31.7 Ft. Shows excellent face.  
Note: Place yellow tags on both BT's.  
Set - Brass cap in place of corner stone Mkd:

County Surveyors	R	T 29 S	R
Office, 1969	2	S 25	S30 I
	W	S 36	W

Note: Place corner stone by brass cap  
Note: This Sec. Cor of S 25, S 36 lies No. 18.5 from Sec. Cor. of S 30,  
S 31 on Range line of R 1, 2 W of T 29S.

Section Corner 30 and 31 only 47  
Found: A 15x10x6 basalt corner stone properly Mkd.  
16" R Fir now 28" N 80° E 46.2 Ft. Has open face & scribe of (W,S,3)  
12" R Fir now 20 S 66° E 39.6 Ft. has open face shows scribe of  
(T29S R I W S 81 Bt)

Note: Place yellow tags on both bearing trees.  
Set - Brass cap in place of corner stone Mkd:

County Surveyors	T 29 S	
Office, 1969	R	S30 R
	2 S 36	S31 I
	W	W

Note: Place corner stone by brass cap.  
Note: This Sec. Cor. of S 30, S 31 lies So. 18.5 from Sec. Cor of T 29 S.  
4-24-69

JOHN M. POWELL  
Frank Jones & W. Penley  
April & May, 1969  
C. S. File No. 54/82