

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 S. T. S. R. 2 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

1/4 Section Corner 31 Only T.29-1 48  
Found - 20" D. Fir now 25" N 28E 67.3. Scribe Visible 1/4 S 31 Bt  
36" D. Fir now 40" East 49.5 Scribe visible 1/4 S 31 BT  
No trace of corner stone.  
Set - Brass cap at 1/4 cor. Mkd:

County Surveyors T 29 S  
Office, 1969 R 1/4 R  
2 S 31 I  
W

New BT's: 8" D Fir N 23 1/2 E 7.0 Scribed 1/4 S 31 C S BT  
6" D Fir S 42E 3.9 Scribed 1/4 S 31 CS BT  
Note: This cor. lies 23.8 South of 1/4 Cor. S 36 4-25-69

1/4 Section Corner to Section 36 Only 48A  
Found - 14" D. Fir now 18" N 24 1/2 W 52.1' Scribe visible "B"  
Also - Brass cap properly marked 1917, at 1/4 cor. Mkd: S 36  
New Bearing Tree 7" D Fir S 75 W 7.2 Scribed 1/4 S 36 CS BT  
Note: This Cor. lies 23.8 North of 1/4 Cor. S 31. 7-25-69  
Fd: 48" Pine, now snag, S. 88 1/2 W. 40.3 ft. scribe visible.

Section Corner to Sections 18 and 19 Only T.29-1 49  
Found - 40" Pine now 52" N 11E 81.2 Shows good scar. 10" D. Fir,  
now 24", S. 55 E. 81.2 ft. shows scar. 20x12x10 Stone 3 notches On N & S.  
Set - Brass cap at Sec. Cor. Mkd:

County Surveyors T 29S  
Office, 1969 R S 18 R  
2 S 24 S 19 I  
W W

New BT's  
12" Cedar N 89 E 14.8 Scribed 729S RIW S 18 CS BT  
17" D. Fir S 28E 17.0 Scribed T 29S RIW S 19 CS BT  
Note: This cor. lies 17.8' So. of 13-18  
24 4-30-69

1/4 Cor. Sec. 24, T29-2W & Sec. 19, T29-1W 50  
Found - 20" D. Fir Now 39" N20E 47.2 (Rec. 52.1) Shows good scar.  
6" D Fir now 26" S 65 W 122.1 Shows faint scar  
Also: Brass cap at 1/4 Cor. Mkd. 1/4 S24 ONLY, General land office, 1917  
Original stone along side cap mkd. 1/4.

Remarked Brass cap as follows: General land office T 29 S  
1/4  
R R  
2 S 24/S 19 I  
W W

New BT.  
10" Cedar S 3 W 4.2 Scribed 1/4 S 24 CS BT 7-30-69

Section Corner to Section 13 and 24 51  
Found - 14" D Fir now 29" S 54 W 75.9 Shows good scar.  
Also 18x12x8 stone at Sec. Cor. 3 notches on No. & So. edges.  
Set - Brass cap at Sec. Cor. Mkd:

County Surveyors T 29 S  
Office, 1969 R S 13 S 18 R  
2 S 24 I  
W W

New BT's:  
10" D Fir N. 51 W 41.7 Scribed T 29 S E 2 W S 13 CS BT  
Old BT OK & Tagged.  
Note: This cor. lies 17.8" North of 24 18  
19 7-30-69

Section Corner to Section 19 and 30 T.29-1 52  
Found - 12" Cedar now down N 39E 48.2 Shows good scar  
24" D. Fir S 51 E 15.2 Shows good scar

Also 16x12x8 stone firmly set at sec. cor mkd. 4 notches on North and  
2 notches on South edges

JOHN M. POWELL  
Frank Jones & W. Penley  
April & May, 1969  
C. S. File No. 54/82