

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 29 D. T. S. R. 2 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 2181

56

Section Corner to Sections 7 and 18  
Found - 8" W. Fir now 13" N 70E 19.1 Shows good scar  
8" Hemlock now snag S 43 E 9.2 Scribe visible 29S RIW S18 BT  
Also - 18x9x6 Stone at Sec. Cor mkd. 2 notches on the north edge & 4  
notches on the South.  
Set - Brass cap at Sec. Cor. Mkd:

C.S.  
File  
No.  
  
54/82

County Surveyors T 29 S  
Office, 1969 R R  
2 S12 S7 I  
W S18 W

New BT's: 13" Hemlock S 66 E 24.9 Scribed T29S RIW S18 CS BT  
Note: This cor. lies 7.9 ft. North of  $\frac{12}{13}$  18

57

Corner No. 1 of H. E. S. #140.  
Found - No trace of old corner stone.  
Orig. 18", now 28" Fir sawed stump, S. 30° E. 31.0 ft., We do not open.  
Orig. 10", now 22" Fir sawed stump, N. 49 1/4° W. 29.7 ft., Open & find  
scribe and reverse.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 2 W  
Office, 1969 Cor. #1 HES 140

New BT's: 9" D. Fir N. 6° E. 19.8 ft. mkd: "1 HES 140 CS BT".  
8" D. Fir N. 41 1/2° W. 35.7 ft. mkd: "1 HES 140 CS BT".

This corner lies on northerly side of old-unused road in cut bank.  
11/18/69

58

Corner No. 2, of H. E. S. #140.  
Found - Old Corner Stone, in place, mkd: "+" on top & "2 HES 140" on  
north side.  
Orig. 8", now 20" Pine, alive, N. 11° E. 2.0 ft., shows scar, broken  
top 60 ft. up. We Tag.

Orig. 15", now 28" Fir, alive, S. 28 1/2° E. 30.4 ft., shows good scar. Tag.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 2 W  
(Reset Stone Alongside) Office, 1969 Cor #2 HES 140

New BT: 14" Pine N. 67° W. 14.2 ft. mkd: "2 HES 140 CS BT".  
This corner lies on south edge of bench.  
11/18/69

59

Corner No. 3, of H. E. S. #140.  
Found - Old Corner Stone, in place, mkd: "+" on top & "3 HES 140 on  
north side.  
Orig. 11", now 24" Fir, alive, S. 10 1/2° W. 13.2 ft., shows good scar, Tag.  
Orig. 11" (?), now 38" Pine, alive, S. 65 1/4° W. 20.5' shows good scar, Tag.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 2 W  
(Reset Stone Alongside) Office, 1969 Cor. #3 HES 140

New BT's: 10" D. Fir N. 32° W. 10.6 ft. mkd: "3 HES 140 CS BT".  
12" D. Fir S. 69° W. 9.2 ft. mkd: "3 HES 140 CS BT".  
This corner lies on gentle, southerly slope.  
11/19/69

60

Corner No. 4 of H. E. S. #140.  
Found - Old Corner Stone, in place mkd: "+" on top & "4 HES 140" on E.  
Orig. 11", now 36" Pine, dead, S. 36° W. 47.5 ft., shows faint scar.  
Orig. 9", now 18" Fir, alive, N. 89° W. 15.2 ft., shows good scar.  
We Rescribe "4 HES 140 CS BT" above old blaze.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 2 W  
(Reset old Corner Stone Alongside) Office, 1969 Cor. #4 HES 140

New BT: 12" D. Fir S. 51° E. 32.3 ft. mkd: "4 HES 140 CS BT".  
This corner lies on ridge top, course N.E. & S.W.  
11/19/69

61

Corner No. 5 of H. E. S. #140.  
Found - Old Corner Stone, in place, mkd: "+" on top & "5 HES 140" on S.E.  
Orig. 12", now 21" Fir, alive, S. 82° W. 15.8 ft., shows good scar.  
We Rescribe "5 HES 140 CS BT".

Orig. 14", now 24" Fir, alive, N. 41° W. 11.6 ft. (Rec. N45W). We Tag.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T 29 S R 2 W  
(Reset Old Stone Alongside) Office, 1969 Cor. #5 HES 140

New BT: 14" D. Fir N. 38° W. 8.0 ft. mkd: "5 HES 140 CS BT".  
This corner lies on top of spur ridge, sloping S.W.  
11/19/69

JOHN M. POWELL  
Frank Jones & W. Penley  
April & May, 1969  
C. S. File No. 54/82

Vernon "RAY" Tracy  
Jack Heritage & V. Perron  
November, 1969 C.S. File No. 54/96

Find. OK by  
L. HEARSTEN  
9/17/81  
C.S. 6/27

Find. OK by  
L. HEARSTEN  
9/28/81  
C.S. 6/27

Find. OK by  
L. HEARSTEN  
9/28/81  
C.S. 6/27

Find. OK by  
L. HEARSTEN  
9/23/81  
C.S. 6/27

Find. OK by  
L. HEARSTEN  
9/30/81  
C.S. 6/27