

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 29 T. S. R 2 R. W. W. M.

KOIKE-CHAPMAN CO., EUGENE, ORE. 21881

Glenn Baughman
For: U.S. Forest
Service
April 1979
C.S. 58/176

111

Section Corner for Secs. 35 and 36 only. (south)
Found - 1" Iron pipe with 1968 County Brass cap. Ren. #31
 10" White Fir, S.24°W., 18.6 ft.
 20" Douglas Fir, N.10°W., 25.7 ft.
 24" Douglas Fir (snag) N.38.0 ft.
 30" Douglas Fir (down) N.45 1/2 E., 12.5 ft.
Marked: 6" White Fir, N.24°E., 31.1 ft. "S 36 B T" and attached brass
 washer stamped Land Surveyor 536 on lower face.

*FD. OK 9/93
PESKE M117-62*

Glenn Baughman
For: U.S. Forest
Service
July 1979
C.S. 58/176

112

Township corner for Sec. 36; and Sec. 31 of T.29-1; Sec. 1 of
T30-2; and Sec. 6 of T30-1
Found - 1" Iron pipe, 10" above the ground with a 2 1/2" Brass cap mkd.
 "T29S R2W R1W S36 S31 S6 S1 T30S 1917"

From which: Ren. #24
 A 22" Oak bears N.70°W., 37.0 ft.
 An 18" Oak stob bears N.8°E., 47.5 ft.
 An 18" Oak stump bears S.89°E., 118.8 ft.
 An 18" D. Fir bears N.44°W., 26.8 ft.
 A 16" D. Fir bears N.73°E., 17.5 ft.
 An 18" D. Fir bears S.9°E., 13.0 ft.
 A 12" D. Fir bears S.41°W., 33.0 ft.
New BT - 10" D. Fir bears S.25°E., 38.4 ft., I marked "T30S R1W S6 BT" on a
 double blaze and nailed a brass washer stamped "LS 536 into
 lower blaze.

Gary L. Langlitz
K. Reed; F. Silagy;
V. Woodral
Doug. Co. Surveyors
Office -
July 26, 1979
C.S. 60/34

113

1/4 Corner for Secs. 7 and 8
Found - A 1" x 36" I.P. with 1917 GLO brass cap properly marked, protruding
 15" above ground.
 An 18" D. Fir now 28" bears N.31°E., 30.4 ft. with well healed
 single blaze.
 A 10" D. Fir now 18" bears S.45°W., 25.7 ft. with well healed singl
 blaze.
Set - Pipe and brass cap deeper in ground stamped "RESET 1979".
New BT's- A 14" I. Cedar, scribed "1/4 S7 CS BT" in double blaze, bears
 S.85°W., 22.6 ft.
 A 30" D. Fir scribed "1/4 S7 CS BT" in double blaze, bears N.6°W.,
 37.1 ft.

Leonard Herzstein, U.S.F.S.
Deputy, Cou. Surveyors Office
J. Landrum
T. Wolford
May 19, 1981
C.S. 61 / 24

114

Cor.# 3 H.E.S. No. 141. Renewal # 66.
Found - 1" I.P., firmly set, projecting 12" above mound of stone,
 with B.C. marked County Surveyors Office 1969 T29S
 R2W Cor #3 HES 141 .
Orig. BT's: 42" D. Fir snag bears S.34 3/4°W, 17.2-ft., with healed blaze.
 28" D. Fir stump bears S.61 1/2°W., 6.6-ft., with healed blaze.
1969 BT's: 12" W. Fir bears South, 28.3-ft., with healed blaze. Ren.#66.
 18" D. Fir bears N.44°W, 25.0-ft., with healed blaze.
* NOTE - Corner is 50-ft. West of Deadman Creek access road.

115

Cor.# 2 H.E.S. No. 141. Renewal # 65.
Found - 1" I.P. firmly set, projecting 4" above a 3' mound of stone,
 with B.C. marked County Surveyors Office 1969 T29S
 R2W HES 141 COR 2. #126
Orig. BT's: 22" D. Fir bears N.42°E, 16.5-ft., with healed blaze.
 20" D. Fir bears S.14°E, 5.9-ft., with healed blaze, and
 re-scribed by Tracy in 1969 with healed double blaze.

116

Cor.# 6 H.E.S. No. 141. Renewal # 67.
Found - Orig. 32" D. Fir Corner tree with healed blaze on the South
 face.
 1" I.P. set by Tracy in 1969, firmly set, projecting 14"
 above ground with B.C. marked County Surveyors Office
 1969 T29S R2W Cor #6 B.O. HES 141, & lies South, 2.0-ft.
 from corner position.
Orig. BT's: 18" D. Fir, bears N.65°W., 40.3-ft., with healed blaze,
 re-scribed by Tracy in 1969, with healed blaze.
1969 BT's: 15" D. Fir bears S.27°E., 37.0-ft., with healed blaze. This