

Douglas County Surveyor's Record of
Government Corners Renewed

T29 T. S. R2 R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 91881

Cont.
Douglas Co. Surveyor's
Office
Stephen J. Flause, &
Randall W. Smith
June 6, 1985
C.S. 62/28

120
Two bearing trees from REN #33 - A 5" D. Fir, now a 9" DBH D. Fir bears S. 41°E., 17.4 ft. dist. (As per record), with fully healed single blaze. And a 30" DBH D. Fir with a fully healed single blaze and a "B" chopped into the bark. Bears S.35°W., 18.9 ft. dist. (As per record)
NEW BT's - A 6" DBH Doug. Fir, double blazed and scribed 1/4 S6 CS BT, bears S. 14 1/2°E., 18.0 ft. dist.

Loyd R. Moffit
LS #944
For USFS
Oct. 1986
C.S. 62/30

121
1/4 Corner for Section 36 only. (South)
Found - 1917 GLO brass cap on a 1" Iron pipe.
A Fir stump bears N.37°W., 31.7 ft. (to center of tree), scar visible. (1917)
A 17" Fir bears N.45°E., 11.9 ft. scars visible.(1917)
A rotted Fir stump which bears N.51°E., 23.1 ft. Old face visible. Ren. No. 27
New BT - A 12" Fir which bears N.38°E., 31.9 ft. Scribed 1/4 S36 BT with L.S. washer #944 nailed to BT scribe.

Loyd R. Moffit
L.S. #944
For: U.S. Forest
Service
Oct. 1986
C.S. 62/30

122
North 1/4 Corner for Section 2 only of T.30-2
Found - 1968 County 2 1/2" brass cap on a 1" iron pipe in a rock mound. Ren. No. 29
A 16" Hemlock which bears S.22°E., 15.8 ft. scar visible.
A Fir stump which bears S.84°E., 34.4 ft. scribe visible.
New BT - I scribed a 6" Fir which bears S.41 1/2°E., 35.2 ft. marked 1/4 S2 BT with LS 944 brass washer nailed to BT scribe.

Corner #11, HES #141

123
Found - 1" iron pipe with 2 1/2" brass cap 12" above ground set on the southwest side of an ash stump. Ren. #72
20" Ash stump. (original corner tree)
36" D. fir bears N.9°15'E., 31.7 ft. with healed blaze. (orig)
14" W. fir (down and rotted) bears N.67°45'E., 20.5 ft. (orig.)
Set - 5/8" x 30" iron rod with a 1" yellow plastic cap 27" in the ground, mkd. "ARTMAN RLS 2268" for reference monument, bears S.58°30'E., 20.0 ft.

Painted corner tree and tagged all BTs, set 6 ft. alum. post alongside rod with 54-2, 54-9, and 54-3 signs attached.

Corner #12, HES #141

124
Found - 1" iron pipe with a 2 1/2" brass cap 12" above ground. Ren. #73
30" W. fir stump bears S.3°30'E., 17.2 ft. (rotted) (orig.)
28" W. fir stump bears S.37°30'W. 22.4 ft. (rotted) (orig.)
16" W. fir (snag) bears S.57°W., 24.0 ft. with healed blaze. 1969 BT.

New BTs - 16" yewwood bears S.64°W., 11.8 ft. scribed "12 HES 141 BT" with alum. tag mkd. "ARTMAN RLS 2268" nailed flush to BT face.
9" yewwood bears N.31°E., 23.0 ft. scribed "12 HES 141 BT" with alum. tag mkd. "ARTMAN RLS 2268" nailed flush to BT face.

Painted and tagged all BTs.

James Artman
L.S. #2268
For: USFS
Nov. 1990
C.S. 63/104

Corner #13, HES #141

125
Found - 1" iron pipe with 2 1/2" brass cap 17" above ground. Ren. #74
Remains of well rotted W. fir bears N.58°30'E., 17.2 ft. (orig.)
Remains of well rotted W. fir bears S.54°E., 13.9 ft. (orig.)
14" W. fir (snag top) bears S.13°W., 21.5 ft. with healed blaze.
15" pine (snag) bears N.43°E., 32.8 ft. with healed blaze. (1969)
New BTs - 10" W. fir bears S.7°E., 18.8 ft. scribed "13 HES 141 BT" with alum. tag mkd. "ARTMAN RLS 2268" nailed flush to BT face.
14" W. fir bears S.38°E., 27.1 ft. scribed "13 HES 141 BT" with alum. tag mkd. "ARTMAN RLS 2268" nailed blush to BT face.

Painted and tagged all BTs.

11/90