

Douglas County Surveyor's Record of
Government Corners Renewed

29 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO. EUGENE, ORE. 97196

Claude Kerr
Logging Engineer
July, 1950

John H. Markham, Jr.
Engineer
Geo. Vaughn-Witness
August 17 & 25, 1950
C.S. 40/272

1/4 sec. cor. bet. secs. 16 and 21

Set a vinemapple post, from which an alder 18" dia. bears N. 11 1/2° E 15 lks. distant.

A cherry 6" dia. bears S 36° W 13 lks. distant.
June 22, 1900. Present. Jas. Newton, Cloyd Chaney, C Sellers.
The S. W. B. T. is entirely destroyed; The N. E. BT is fallen down but with plain marks.

SEC. COR. ~~3, 4, 9, & 10~~ 4 and 3.

(North T line) **SEE CORNER NO. 55**
Found a laurel that I am certain was the original B.T., but the scribe marks are gone. This BT is the Laurel bearing S 85° E for 22 lks.

I reset the corner 3" x 4" Cedar Post from this BT, and it checks well for the intersection of the old blazed lines.

I remarked four new BTs-

Inc. Cedar 20" bearing S 45° E for 35 lks., Marked T 29 S, R 3 W, S3 BT

A Fir 20", bearing S 70° W for 36 lks, marked S 4 BT.

~~Inc. Cedar, N 47° E for 34 lks, marked T 28 S, R 3 W, S 24 BT~~

~~Laurel 12", N 33° W, 39 lks, marked T 28 S, R 3 W, S 23 BT~~

6-12-51 O&C instructed by Mr. Kerr to obliterate markings in

SEC. COR. 3, 4, 9, & 10.

All BTs destroyed by old burn. Set a stake at intersection of the two old blazed lines and checked West 9.50 chs. to the ridge mentioned in field notes.

Distance checked closely.

I marked the only close tree for a new BT.

SEC. COR. 22-23-26-27

As set per govt. field notes. At Cor. point found stone marked X.

I set a 3/4 in. x 30 in. I.P. 12 in. in ground, from which

A Maple 23 in. diam. bears S 57° W, 4.0 ft. dist. marked S 27, 2880, B.T.

A Maple 20 in. diam. bears N 42° E, 6.0 ft. dist. marked S 23, 2880, B.T.

A Fir 11 in. diam. bears S 75° E 71.0 ft. dist. marked S 26, 2880, B.T.

1/4 SEC. COR. 15 and 22

Determined by old B.T.

A Cedar 36 in. diam. bears East 2.5 ft. dist., scribe legible.

At corner point set 1 in. x 30 in. I. P. 15 in. in ground, from which

A Fir 6 in. diam. bears N 33° W 18.0 ft. dist. marked 1/4 S, S 15, 2880, B.T.

A Fir 7 in. diam. bears S 44° E, 29.0 ft. dist. marked 1/4 S, S 22, 2880, B.T.

Magnetic var. sec. line. 14° 30'

SEC. COR. 14-15-22-23

Determined by old B.T.

A Cedar 55 in. diam. bears N 65° W, 30.0 ft. dist. scribe legible.

A Cedar windfall bears S 65° W 32.0 ft. dist.

At corner point set 1 in. x 30 in. I.P. 18 in. in ground, from which

A Maple 14 in. diam. bears N 39° E 12.0 ft. dist. marked 98, 2880 B.T.

An Alder 8 in. diam. bears S 72° W 51.0 ft. dist. marked S 22, T 29 S, R 3 W, 2880, B. T.

1/4 SEC. COR. 22 and 23

Determined by old B.T.

A Fir 38 in. diam. bears N 30° W 6.5 ft. dist. Scribe legible. I remark 1/4 S, B.T.

At corner point set 3/4 in. x 30 in. I.P. 15 in. in ground, from which

A Laurel 12 in. diam. bears S 60° W 43.6 ft. dist. marked 89, S 22, 2880, B.T.

A B. Oak 14 in. diam. bears S 77° E, 38.0 ft. dist. marked 1/4 S, S 23, 2880, B.T.