

Douglas County Surveyor's Record of
Government Corners Renewed

T. S. 3 R. W. W. M.

12

Pen B. Irving Dep. C. S.
N. E. Richardson
Loren Weber

CS 16/55

See Ruby

Witnesses
N. E. Richardson
Thomas Hatfield

Oct. 20, 1923.
C. W. Springer Deputy

May 27, 1941
May 27, 1941
May 29, 1941
May 29, 1941
May 31, 1941

Section corner sections 28 and 33. **SEE CORNER NO. 42**
This corner is as described in the original government field notes. The cedar corner tree is dead but excellently preserved. Drove a 2"x48" iron pipe at the base of the corner tree and re-marked both original bearing trees.

Section corner to sections 27-28-33-34. **SEE CORNER NO. 39 13**
Location identified from OBT S. 89°W. 51 lks. which I chop out and find scribe marks in excellent condition. O. B. T. N. 89°W. 53 lks. standing and in good shape remarked but not chopped out. OBT N. 62°E. 73 lks. standing and in good shape remarked but not chopped out.
Drove a 1"x48" iron pipe 40" in the ground for the corner and set a 6" x 6" x 48" Yewwood post alongside. Blazed and scribed a fir 24 ins. diam. which bears S. 6)E. 23 lks. for a new BT replacing the OBT S. 70°E. 76 lks. which has been destroyed.

T. 29 S. R. 3 W., WM. **13-A**
Post on the south boundary of section 33 20 chs. east from the SE corner of section 33.
Location identified from OBT a fir 36 ins. diam. which bears N. 28°W. 7 lks. and which I remark. Set a 4"x4"x42" fir post for the corner.

SECTION CORNER SECTIONS 28-29-32-33. **14**
Location identified from OBT a fir 24" which bears N. 60°W. 13 lks. which has fallen down, scribe marks visible. A fir snag completely burned S. 30°E. 43 lks. A laurel 42 ins. diam. N. 15°E. 88 lks. alive and in excellent shape which I did not chop out but marked with a X.
Set a cedar post 4"x6"x48" - 15" in the ground for the corner and blazed and scribed new bearing trees as follows:
A fir 26 ins. diam. which bears N. 22°W. 39 lks. **74**
A Fir 12 ins. diam. which bears S. 21°E. 90 lks.
A cedar 42 ins. diam. which bears S. 59°W. 26 lks.
A cedar 12 ins. diam. which bears N. 29°E. 76 lks.

See Vol. 3 Pg. 169
C.S. 6/29

SECTION CORNER COMMON TO SECTIONS 32 and 33 T. 29 S. and Sec. 4 and 5 T. 30 S. **15**
Reestablished from stump of only remaining B.T., called for as 24" Fir S. 8°W., 108 lks. Drove an Iron Pipe 2" x 24" in ground and marked
A 12" Black Oak S. 60°15'W., 168.9 ft.
A 10" Ash S. 52°45'E., 178.0 ft.
A 10" Alder N. 42°10'E., 17.7 ft.
A 6" Ash N. 7°50'W., 210.7 ft.

SECTION CORNER BETWEEN SECTIONS 32 T. 29 S. and SECTION 5 T. 30 S. **16**
Reestablished from stump of an Oak 15" dia. N. 82°E., 270 links and from Mr. R. Fates testimony that his fence ran between the witness trees. Drove an Iron Pin 2" x 24" in ground and set a Cedar Stake 4" x 4" x 36" also from which
A 22" Fir bears S. 45°E., 13.7 ft.
A 24" Fir bears N. 60°30'E., 43.0 ft.

SEE CORNER NO. 42

SEE CORNER NO. 39 13

SEE CORNER NO. 74

SEE CORNER NO. 90

SEE CORNER NO. 96